

Sikagard®-706 Thixo

DECLARATION OF PERFORMANCE

No. 0203030100200000031105

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	0203030100200000031105
2	INTENDED USE/S	EN 1504-2:2004 Surface protection product – hydrophobic impregnation: ingress protection (1.1), moisture control (2.1), increasing resistivity (8.1) of EN 1504-9:2008
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 1504-2:2004
	Notified body/ies:	0921

7 DECLARED PERFORMANCE/S


Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Depth of penetration	Class II: ≥ 10 mm	System 2+	
Water absorption and resistance to	alkali:		
Absorption ratio:	< 7.5 % compared with the untreated specimen	System 2+	EN 1504-2:2004
Absorption ratio:	< 10 % after immersion in alkali solution	System 2+	
Drying rate for hydrophobic impregnation	Class I: > 30 %	System 2+	
Loss of mass after freeze-thaw salt stress	Pass	System 2+	
Dangerous substances	NPD		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos Function: TMM Refurbishment At Athens on 22 April 2020 Name: Alexandros Melissourgos Function: Technical Manager At Athens on 22 April 2020







NΩ

Sika Services AG, Zurich, Switzerland

DoP No. 0203030100200000031105

EN 1504-2:2004

Notified Body 0921

Surface protection product – hydrophobic impregnation: ingress protection (1.1), moisture control (2.1), increasing resistivity (8.1) of EN 1504-9:2008

Depth of penetration Class II: ≥ 10 mm

Water absorption and resistance to alkali

Absorption ratio: < 7.5 % compared with the untreated specimen

< 10 % after immersion

Absorption ratio: in alkali solution

Drying rate for hydrophobic impregnation Class I: > 30 %

Loss of mass after freeze-thaw salt stress Pass

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE

Protomagias 15 14568 Kryoneri Attica - Greece www.sika.gr

Declaration of Performance

Sikagard®-706 Thixo 0203030100200000031105 2018.05, ver. 1 1105

