according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Revision Date: 06.12.2023 Version 6.0 Print Date 06.12.2023

Date of last issue: 27.01.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name Sikafloor®-359 N Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system, Sealing system, Product is not intended for

consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

> 15 Protomagias Street 145 68 Kryoneri / Athens

+30 210 81 60 600 Telephone Telefax : +30 210 81 60 606 E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour. Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

Specific target organ toxicity - single ex-

posure, Category 3, Respiratory system Long-term (chronic) aquatic hazard, Cat-

egory 2

H335: May cause respiratory irritation.

H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms





Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Jika

Revision Date: 06.12.2023 Version 6.0 Print Date 06.12.2023 Date of last issue: 27.01.2022 H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. H411 Supplemental Hazard Repeated exposure may cause skin dryness EUH066 Statements or cracking. Precautionary statements Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Hazardous components which must be listed on the label:

P391

Isophorondiisocyanate homopolymer Hydrocarbons, C9, aromatics

#### **Additional Labelling**

"As from 24 August 2023 adequate training is required before industrial or professional use."

Collect spillage.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B



Date of last issue: 27.01.2022



## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Isophorondiisocyanate homopolymer Contains: 3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate <= 0,49 %	53880-05-0 931-312-3 500-125-5 01-2119488734-24- XXXX	Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system)	>= 60 - < 80
Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 25 - < 40

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Revision Date: 06.12.2023 Version 6.0 Print Date 06.12.2023

Date of last issue: 27.01.2022

**Symptoms** Cough

> Respiratory disorder Allergic reactions

Erythema Loss of balance

Vertigo

See Section 11 for more detailed information on health effects

and symptoms.

Risks irritant effects

sensitising effects

May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Water

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not use a solid water stream as it may scatter and spread

Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

### 5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Revision Date: 06.12.2023 Version 6.0 Print Date 06.12.2023

Date of last issue: 27.01.2022

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Remove all sources of ignition. Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

#### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

#### 6.4 Reference to other sections

For personal protection see section 8.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary

measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Date of last issue: 27.01.2022



practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	

Contains no substances with occupational exposure limit values.

#### 8.2 Exposure controls

#### **Engineering measures**

Maintain air concentrations below occupational exposure standards.

Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Revision Date: 06.12.2023 Version 6.0 Print Date 06.12.2023

Date of last issue: 27.01.2022

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice : Prevent product from entering drains.

If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state liquid Colour yellow

Odour hydrocarbon-like

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range No data available

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : 7 %(V)

per flammability limit

Lower explosion limit /

Lower flammability limit

0,8 %(V)

ca. 45 °C Flash point

Method: closed cup

No data available Auto-ignition temperature

Decomposition temperature No data available

pΗ Not applicable

substance/mixture is non-soluble (in water)

**Viscosity** 

ca. 2.000 mPa.s (23 °C) Viscosity, dynamic

 $> 20,5 \text{ mm2/s } (40 \degree \text{C})$ Viscosity, kinematic

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Revision Date: 06.12.2023 Version 6.0 Print Date 06.12.2023

Solubility(ies)

Date of last issue: 27.01.2022

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 4,9996 hPa

Density : ca. 1,05 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Date of last issue: 27.01.2022

#### **Components:**

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

**Components:** 

Hydrocarbons, C9, aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

11.2 Information on other hazards

**Endocrine disrupting properties** 

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Revision Date: 06.12.2023 Version 6.0

Date of last issue: 27.01.2022



Print Date 06.12.2023

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### Components:

### Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic

mg/l

plants

Exposure time: 72 h

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

: This substance/mixture contains no components considered Assessment

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

(Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9

0.1% or higher...

#### 12.6 Endocrine disrupting properties

#### **Product:**

: The substance/mixture does not contain components consid-Assessment

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

### **Product:**

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Date of last issue: 27.01.2022

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 05 01\* waste isocyanates

Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated

by dangerous substances

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

 ADR
 : UN 1263

 IMDG
 : UN 1263

 IATA
 : UN 1263

14.2 UN proper shipping name

ADR : PAINT IMDG : PAINT

(solvent naphtha)

IATA : Paint

14.3 Transport hazard class(es)

Class Subsidiary risks

ADR : 3 IMDG : 3 IATA : 3

14.4 Packing group

ADR

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Date of last issue: 27.01.2022

**IMDG** 

Packing group : III Labels : 3

EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passen: 355

ger aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Flammable Liquids

14.5 Environmental hazards

**ADR** 

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/orexempted from the registration.

Country GR 000000122178

12 / 15

Date of last issue: 27.01.2022

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Revision Date: 06.12.2023 Version 6.0 Print Date 06.12.2023

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 33-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

(Number on list 74)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Petroleum products: (a) gasolines and naphthas, (b) kerosenes

(including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards

as the products referred to in points (a) to (d)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 30% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 30% w/w

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

according to Regulation (EC) No. 1907/2006

## Sikafloor®-359 N Part B

Revision Date: 06.12.2023 Version 6.0 Print Date 06.12.2023

Date of last issue: 27.01.2022

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction. May cause respiratory irritation. H335 May cause drowsiness or dizziness. H336

H411 Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic Long-term (chronic) aquatic hazard

Asp. Tox. Aspiration hazard Flam. Liq. Flammable liquids Skin Sens. Skin sensitisation

STOT SE Specific target organ toxicity - single exposure

European Agreement concerning the International Carriage of ADR

Dangerous Goods by Road

Chemical Abstracts Service CAS **DNEL** Derived no-effect level

Half maximal effective concentration EC50

**GHS** Globally Harmonized System

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG** 

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

MARPOL International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

Occupational Exposure Limit **OEL** 

Persistent, bioaccumulative and toxic **PBT PNEC** Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament REACH

> and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

**SVHC** Substances of Very High Concern

Very persistent and very bioaccumulative vPvB

#### **Further information**

#### Classification of the mixture: Classification procedure:

Flam. Liq. 3	H226	Based on product data or assessment
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method

STOT SE 3 H335 Calculation method Aquatic Chronic 2 H411 Calculation method

Revision Date: 06.12.2023

Date of last issue: 27.01.2022

according to Regulation (EC) No. 1907/2006

# Sikafloor®-359 N Part B

Version 6.0



The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN