Version 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaGard®-6250

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 Eye irritation, Category 2 Specific target organ toxicity - single ex- posure, Category 3, Central nervous	H226: Flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness.
system Long-term (chronic) aquatic hazard, Cat- egory 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	•
Hazard statements	:	H226 H319 H336 H412	Flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting ef-

SikaGard[®]-6250



Revision Date: 04.01.2024 Date of last issue: 27.01.2022	N	Version 3.1	
		fects.	
Supplemental Hazard Statements	: EUH066	Repeated exposure may ca or cracking.	ause skin dryness
Precautionary statements	: Prevention:		
	P210	Keep away from heat, hot s open flames and other igni smoking.	
	P261	Avoid breathing mist or var	oours.
	P273	Avoid release to the enviro	
	P280	Wear protective gloves/ pro eye protection/ face protec	5
	Response:		
	P303 + P361 +	P353 IF ON SKIN (or hair) ately all contaminated cloth with water.	
	P370 + P378	In case of fire: Use dry san alcohol-resistant foam to e	

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 04.01.2024 Date of last issue: 27.01.2022



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		. ,
Hydrocarbons, C9-C11, n-	Not Assigned	Flam. Liq. 3; H226	>= 40 - < 60
alkanes, isoalkanes, cyclics, <2%	919-857-5	STOT SE 3; H336	
aromatics	01-2119463258-33-	(Central nervous	
	XXXX [corresponding	system)	
	group CAS 64742-48-	Asp. Tox. 1; H304	
	9]	EUH066	
Hydrocarbons, C9-C10, n-	Not Assigned	Flam. Liq. 3; H226	>= 10 - < 20
alkanes, isoalkanes, cyclics, <2%	927-241-2	STOT SE 3; H336	
aromatics	01-2119471843-32-	(Central nervous	
	XXXX [corresponding group CAS 64742-48-	system) Asp. Tox. 1; H304	
	9]	Aquatic Chronic 3;	
	5]	H412	
		EUH066	
Phosphoric acid, C11-14-isoalkyl	154518-38-4	Skin Irrit. 2; H315	>= 1 - < 2,5
esters, C13-rich	Not Assigned	Eye Dam. 1; H318	,
	01-2119976356-25-	Aquatic Chronic 2;	
	XXXX	H411	
Alcohols, C11-14-iso-, C13-rich	68526-86-3	Skin Irrit. 2; H315	>= 0,25 - < 1
	271-235-6	Aquatic Acute 1;	
	01-2119454259-32-	H400	
	XXXX	Aquatic Chronic 2;	
		H411	
		M-Factor (Acute	
		aquatic toxicity): 1 M-Factor (Chronic	
		aquatic toxicity): 1	
For explanation of obbreviations as		aqualic locality). I	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.

SikaGard[®]-6250



Revision Date: 04.01.2024 Date of last issue: 27.01.2022	Version 3.1	Print Date 04.0
	If symptoms persist, call a physician.	
In case of eye contact :	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.	
If swallowed :	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious	s person.
4.2 Most important symptoms and	effects, both acute and delayed	
Symptoms :	Excessive lachrymation Erythema Loss of balance Vertigo See Section 11 for more detailed information on and symptoms.	health effects
Risks :	irritant effects	
	Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or o	cracking.
4.3 Indication of any immediate me	dical attention and special treatment needed	
Treatment :	Treat symptomatically.	

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media :	•	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing : media	:	Water High volume water jet
5.2 Special hazards arising from the	he	e substance or mixture
Specific hazards during fire- : fighting	:	Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion prod- : ucts	:	No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SikaGard®-6250

_



Revision Date: 04.01.2024 Date of last issue: 27.01.2022	Version 3.1	Print Date 04.01.20
for firefighters		
Further information	: Use water spray to cool unopened conta	iners.
SECTION 6: Accidental release	e measures	
6.1 Personal precautions, protect	ive equipment and emergency procedure	S
Personal precautions	 Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form tions. Vapours can accumulate in low are 	
6.2 Environmental precautions		
Environmental precautions	: Prevent product from entering drains. If the product contaminates rivers and la respective authorities.	kes or drains inform
6.3 Methods and material for cont	ainment and cleaning up	
Methods for cleaning up	: Contain spillage, and then collect with no sorbent material, (e.g. sand, earth, diaton miculite) and place in container for dispo / national regulations (see section 13).	maceous earth, ver-

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products 	
Advice on protection against fire and explosion	Use explosion-proof equipment. Keep away from heat/ sparks open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.	\$/



Revision Date: 04.01.2024 Date of last issue: 27.01.2022		Version 3.1	Print Date 04.01.2024
Hygiene measures	:	Handle in accordance with good industria practice. When using do not eat or drink. smoke. Wash hands before breaks and a	When using do not
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and place. Containers which are opened must sealed and kept upright to prevent leakag ance with local regulations.	t be carefully re-
Further information on stor- age stability	:	No decomposition if stored and applied as	s directed.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data S use.	Sheet prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *			
Contains no substances with occupational exposure limit values.							

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Workers	Skin contact		300 mg/m3 300 mg/kg
	Workers	Inhalation		1500 mg/m3
	Consumers	Skin contact		300 mg/m3 300 mg/kg
	Consumers	Inhalation		900 mg/m3
	Consumers	Ingestion		300 mg/m3 300 mg/kg

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equi	ipment
Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure:

SikaGard®-6250



Revision Date: 04.01.2024 Date of last issue: 27.01.2022	Version 3.1	Print Date 04.01.2	
	Viton gloves (0.4 mm), breakthrough time >30 min.		
Skin and body protection	 Protective clothing (e.g. Safety sh long-sleeved working clothing, lon and protective boots are addition and stirring work. 	ng trousers). Rubber aprons	
Respiratory protection	 In case of inadequate ventilation Respirator selection must be bas exposure levels, the hazards of the ing limits of the selected respirator organic vapor (Type A) and partice A1: < 1000 ppm; A2: < 5000 ppm P1: Inert material; P2, P3: hazard Ensure adequate ventilation. This exhaust extraction or by general ods for determining inhalation exp ticular to the mixing / stirring area to keep the concentrations under limits then respiration protection respiration 	ed on known or anticipated he product and the safe work- culate filter b; A3: < 10000 ppm dous substances s can be achieved by local ventilation. (EN 689 - Meth- posure). This applies in par- b. In case this is not sufficent the occupational exposure	

Environmental exposure controls

General advice	: Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform
	respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour	:	liquid off-white hydrocarbon-like			
Melting point/range / Freezing point	:	No data available			
Boiling point/boiling range	:	ca. 136 - 164 °C			
Flammability (solid, gas)	:	No data available			
Upper/lower flammability or explosive limits					
Upper explosion limit / Up- per flammability limit	•				
Lower explosion limit / Lower flammability limit	:	0,6 %(V)			
Flash point	:	ca. 29 °C Method: closed cup			
Auto-ignition temperature	:	> 200 °C			

SikaGard®-6250

Revision Date: 04.01.2024 Date of last issue: 27.01.2022 Version 3.1

Decomposition temperature	:	No data available
рН	:	not determined substance/mixture is non-polar/aprotic
Viscosity		
Viscosity, dynamic	:	ca. 370 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	ca. 5 hPa (20 °C)
Density	:	ca. 0,85 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks	Conditions to avoid	: Heat, flames and sparks.
---	---------------------	----------------------------

10.5 Incompatible materials

Materials to avoid	:	No data available
--------------------	---	-------------------

Revision Date: 04.01.2024 Date of last issue: 27.01.2022 Version 3.1



10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics: Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg LD50 Dermal (Rabbit): 3.160 mg/kg Acute dermal toxicity Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics: Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg Acute inhalation toxicity : LC50 (Rat): 4.951 mg/l Exposure time: 4 h Test atmosphere: vapour : LD50 Dermal (Rabbit): > 5.000 mg/kg Acute dermal toxicity Phosphoric acid, C11-14-isoalkyl esters, C13-rich: Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics: Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Revision Date: 04.01.2024 Date of last issue: 27.01.2022 Version 3.1



Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Hydrocarbons, C9-C11, h-ai	Kan	ies, isoaikanes, cyclics, <2% aromatics:
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 1.000 mg/l Exposure time: 48 h
Alcohols, C11-14-iso-, C13-	rich	:
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 0,42 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia (water flea)): 0,71 mg/l Exposure time: 48 h
M-Factor (Acute aquatic tox- icity)	:	1
M-Factor (Chronic aquatic toxicity)	:	1

Revision Date: 04.01.2024 Date of last issue: 27.01.2022 Version 3.1



12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:		
Assessment		The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other adverse effects		
Product:		
Additional ecological infor-	-	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product
The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Revision Date: 04.01.2024 Date of last issue: 27.01.2022 Print Date 04.01.2024

Version 3.1

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 1139
IMDG	:	UN 1139
ΙΑΤΑ	:	UN 1139
14.2 UN proper shipping name		
ADR	:	COATING SOLUTION

IMDG	: COATING SOLUTION
ΙΑΤΑ	: Coating solution

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADR	: 3	
IMDG	: 3	
ΙΑΤΑ	: 3	

14.4 Packing group

ADR

Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
Tunnel restriction code	:	(D/E)
		. ,

IMDG

Packing group	:	III
Labels	:	3
EmS Code	:	F-E, <u>S-E</u>

IATA (Cargo)

IATA (Passenger)		
Labels	:	Flammable Liquids
Packing group	:	III
Packing instruction (LQ)	:	Y344
aircraft)		
Packing instruction (cargo	:	366

: 355

in in assungui
Packing instruction (passen-
and aircraft)

yer allorally		
Packing instruction (LQ)	:	Y344
Packing group	:	III
Labels	:	Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

Revision Date: 04.01.2024 Date of last issue: 27.01.2022 Version 3.1



IMDGMarine pollutant: noIATA (Passenger)Environmentally hazardous: noIATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable

Version 3.1



Revision Date: 04.01.2024 Date of last issue: 27.01.2022

Seveso III: Directive 2012/18/EU jor-accident hazards involving da P5c	of the European Parliament and of the Council on the control of ma- ngerous substances. FLAMMABLE LIQUIDS
Volatile organic compounds :	Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: 56,4% w/w
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 56,4% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements		
H226	Flammable liquid and vapour.	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H336	May cause drowsiness or dizziness.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Full text of other abbreviation	5	
Aquatic Acute	Short-term (acute) aquatic hazard	
Aquatic Chronic	Long-term (chronic) aquatic hazard	
Asp. Tox.	Aspiration hazard	
Eye Dam.	Serious eye damage	
Flam. Liq.	Flammable liquids	
Skin Irrit.	Skin irritation	
STOT SE	Specific target organ toxicity - single exposure	
ADR	European Agreement concerning the International Carriage of	
	Dangerous Goods by Road	
CAS	Chemical Abstracts Service	
DNEL	Derived no-effect level	
EC50	Half maximal effective concentration	
GHS	Globally Harmonized System	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Code for Dangerous Goods	
LD50	Median lethal dosis (the amount of a material, given all at	
	once, which causes the death of 50% (one half) of a group of	
	test animals)	
LC50	Median lethal concentration (concentrations of the chemical in	1
	air that kills 50% of the test animals during the observation	
	period)	
MARPOL	International Convention for the Prevention of Pollution from	
	Ships, 1973 as modified by the Protocol of 1978	

Jika ®
Print Date 04.01.2024

Revision Date: 04.01.2024	Version 3.1
Date of last issue: 27.01.2022	
	• • • • • • • • • • • • • • • • • • •

OEL PBT PNEC	 Occupational Exposure Limit Persistent, bioaccumulative and toxic Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi-
SVHC vPvB	 cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN