

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: SikaScreed[®]-20 EBB Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		-

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1B Serious eye damage, Category 1 Skin sensitisation, Category 1 Long-term (chronic) aquatic hazard, Category 3

H314: Causes severe skin burns and eye damage.

- H318: Causes serious eye damage.
- H317: May cause an allergic skin reaction.
- H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	LE	
Signal word	:	Danger	•
Hazard statements	:	H314 H317 H412	Causes severe skin burns and eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting ef- fects.
Supplemental Hazard Statements	:	EUH071	Corrosive to the respiratory tract.

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Print Date 25.04.2023

I			
Precautionary statements	:	Prevention:	
		P261	Avoid breathing mist or vapours.
		P273	Avoid release to the environment.
		P280	Wear protective gloves/ protective clothing/
			eye protection/ face protection.
		Response:	
		P303 + P361 + F	P353 IF ON SKIN (or hair): Take off immedi- ately all contaminated clothing. Rinse skin with water.
		P304 + P340 + F	P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Im- mediately call a POISON CENTER/ doctor.
		P305 + P351 + F	P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove con- tact lenses, if present and easy to do. Con- tinue rinsing. Immediately call a POISON CENTER/ doctor.

Version 5.0

Hazardous components which must be listed on the label:

3-aminomethyl-3,5,5-trimethylcyclohexylamine Amines, polyethylenepoly-, triethylenetetramine fraction Adduct IA (epoxy amine adduct)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		· · · ·
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319 Acute toxicity esti- mate Acute oral toxicity:	>= 10 - < 20
		1.620 mg/kg Acute inhalation tox- icity (dust/mist): 4,178 mg/l	
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2 220-666-8 01-2119514687-32- XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 	>= 5 - < 10
		Acute oral toxicity:	
Amines, polyethylenepoly-, tri- ethylenetetramine fraction Contains: 2-(2-aminoethylamino)ethanol <= 0,3 %	90640-67-8 292-588-2 01-2119487919-13- XXXX	1.030 mg/kgAcute Tox. 4; H302Acute Tox. 4; H312Skin Corr. 1B; H314Skin Sens. 1; H317Aquatic Chronic 3;H412EUH071EUH071Acute toxicity estimateAcute oral toxicity:1.716 mg/kgAcute dermal toxicity:1.465 mg/kg	>= 5 - < 10

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

SikaScreed®-20 EBB Part B

Revision Date: 25.04.2023 Date of last issue: 19.02.2021





(1-methylethyl)-1,1'-biphenyl Contains: diisopropyl-1,1'-biphenyl >= 9,9 %	25640-78-2 247-156-8 01-2119982993-17- XXXX	Eye Irrit. 2; H319 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 2; H411	>= 5 - < 10
2,4,6- tris(dimethylaminomethyl)phenol Contains: bis[(dimethylamino)methyl]phenol <= 15 %	90-72-2 202-013-9 01-2119560597-27- XXXX	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 3 - < 5
Adduct IA (epoxy amine adduct)	68609-08-5 614-657-1 01-2120106013-80- XXXX	Acute Tox. 4; H302 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 2,5 - < 5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

4.1 Description of first aid measur	
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul- ty.
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms and	d effects, both acute and delayed
Symptoms	: Allergic reactions Dermatitis See Section 11 for more detailed information on health effects
Country GR 10000007160	4 /

Revision Date: 25.04.2023
Date of last issue: 19.02.2021

Version 5.0

and symptoms.



		and symptoms.
Risks	:	Health injuries may be delayed. corrosive effects sensitising effects
		May cause an allergic skin reaction. Causes serious eye damage. Corrosive to the respiratory tract. Causes severe burns.
4.3 Indication of any immediate	mer	lical attention and special treatment needed
Treatment	:	Treat symptomatically.
SECTION 5: Firefighting meas	sur	es
5.1 Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from	the	substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
-	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.
SECTION 6: Accidental releas	se r	neasures
6.1 Personal precautions, protect	tive	e equipment and emergency procedures
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
6.2 Environmental precautions		

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0



6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	ncl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.
7.3	Specific end use(s)		
	Specific use(s)	:	Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
Contains no substances with occupational exposure limit values.						

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0



Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Wear eye/face protection.			
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.			
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.			
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.			
Respiratory protection	:	No special measures required.			
Environmental exposure controls					
General advice	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.			

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Appearance	:	paste
Colour	:	brown
Odour	:	amine-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 101 °C Method: closed cup

Revision Date: 25.04.2023 Date of last issue: 19.02.2021





Auto-ignition temperature	:	Not applicable
		No data available
Decomposition temperature	:	No data available
рН	:	> 11 Concentration: 50 g/l 50 %
Viscosity		
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	0,07 hPa
Density	:	ca. 1,4 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available
9.2 Other information		

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid	:	No data available

10.5 Incompatible materials

Materials to avoid : No data available

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

SikaScreed[®]-20 EBB Part B

Revision Date: 25.04.2023 Date of last issue: 19.02.2021

Version 5.0



10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

benzyl alcohol:		
Acute oral toxicity	:	LD50 Oral (Rat): 1.620 mg/kg
		Acute toxicity estimate: 1.620 mg/kg Method: Calculation method
Acute inhalation toxicity	:	LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist
		Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method
3-aminomethyl-3,5,5-trimet	hylc	cyclohexylamine:
Acute oral toxicity	:	Acute toxicity estimate: 1.030 mg/kg Method: Acute toxicity estimate according to Regulation (EC) No. 1272/2008
		LD50 Oral (Rat): 1.030 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
		LD50 (Rabbit): > 2.000 - 5.000 mg/kg
Amines, polyethylenepoly-	, trie	ethylenetetramine fraction:
Acute oral toxicity	:	LD50 Oral (Rat): 1.716 mg/kg
		Acute toxicity estimate: 1.716 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Assessment: Corrosive to the respiratory tract.
Acute dermal toxicity	:	LD50 Dermal (Rabbit): 1.465 mg/kg

Print Date 25.04.2023

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0

Acute toxicity estimate: 1.465 mg/kg Method: Calculation method

REGULATION (EC) No 1272/2008

(1-methylethyl)-1,1'-bip	ohenyl:
Acute oral toxicity	: LD50 Oral (Rat): 4.650 mg/kg Method: OECD Test Guideline 401
2,4,6-tris(dimethylamir	omethyl)phenol:
Acute oral toxicity	: LD50 (Rat): > 1.999 mg/kg Remarks: Harmful if swallowed. Annex VI - Harmonised

Adduct IA (epoxy amine adduct):

Acute oral toxicity	:	LD50 Oral (Rat, female): 300 - 2.000 mg/kg
-		Method: OECD Test Guideline 423

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species Assessment	-	Rabbit Corrosive
Method		OECD Test Guideline 404
Assessment Remarks		irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species Assessment	:	Rabbit Causes serious eye damage.
Assessment Remarks		irritating Annex VI - Harmonised REGULATION (EC) No 1272/2008

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0



Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Corrosive to the respiratory tract.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

:

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:		
benzyl alcohol:		
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
3-aminomethyl-3,5,5-trimeth	ylc	yclohexylamine:
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h
		NOEC (Desmodesmus subspicatus (green algae)): 1,5 mg/l Exposure time: 72 h

Print Date 25.04.2023

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0

(1-methylethyl)-1,1'-biphenyl:

Toxicity to daphnia and other	:	LC50 (Daphnia magna (Water flea)): 0,167 mg/l
aquatic invertebrates		Exposure time: 48 h

2,4,6-tris(dimethylaminomethyl)phenol:

Toxicity to algae/aquatic	:	EC50 (Scenedesmus capricornutum (fresh water algae)): > 10
plants		- 100 mg/l
		Exposure time: 72 h

Adduct IA (epoxy amine adduct):

Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): 3,13 mg/l Exposure time: 72 h
Toxicity to fish (Chronic tox- icity)	:	LC50: 1,62 mg/l Exposure time: 96 h Species: Danio rerio (zebra fish)
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	EC50: 1,75 mg/l Exposure time: 48 h Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0



12.7 Other adverse effects

Product:

Additional ecological infor-	:	An environmental hazard cannot be excluded in the event of
mation		unprofessional handling or disposal.
		Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	UN 1759
	IMDG	:	UN 1759
	ΙΑΤΑ	:	UN 1759
14.2	2 UN proper shipping name		
	ADR	:	CORROSIVE SOLID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1- methylethyl)-1,1'-biphenyl)
	IMDG	:	CORROSIVE SOLID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1- methylethyl)-1,1'-biphenyl)
	ΙΑΤΑ	:	Corrosive solid, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0

Subsidiary risks



methylethyl)-1,1'-biphenyl)

14.3 Transport hazard class(es)

Class	
ADR : 8	
IMDG : 8	
IATA : 8	
14.4 Packing group	
ADRPacking group:IIIClassification Code:C10Hazard Identification Number:80Labels:8Tunnel restriction code:(E)	
IMDGPacking group:Labels:EmS Code:Remarks:	
IATA (Cargo) Packing instruction (cargo : 864 aircraft) Packing instruction (LQ) : Y845 Packing group : III Labels : Corrosive	
IATA (Passenger) Packing instruction (passen- : 860 ger aircraft) Packing instruction (LQ) : Y845 Packing group : III Labels : Corrosive	
14.5 Environmental hazards	
ADR Environmentally hazardous : no	
IMDG Marine pollutant : no	
IATA (Passenger) Environmentally hazardous : no	
IATA (Cargo) Environmentally hazardous : no	

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

Print Date 25.04.2023

Revision Date: 25.04.2023 Date of last issue: 19.02.2021

Version 5.0

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety health and environmen	tal regulations/legislat	ion	specific for the substance or mixture
REACH - Restrictions on the mar the market and use of certain dar	1 Safety, health and environmental regulations/legislat REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)		
	International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors		
	REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).		
REACH - List of substances subj (Annex XIV)	REACH - List of substances subject to authorisation (Annex XIV)		
Regulation (EC) No 1005/2009 o plete the ozone layer	Regulation (EC) No 1005/2009 on substances that de- plete the ozone layer		
Regulation (EU) 2019/1021 on pe tants (recast)	Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)		
	Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals		
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the reg - exempted from the reg	strea I/or gula	am suppliers, and/or ation, and/or
Seveso III: Directive 2012/18/EU jor-accident hazards involving da		nen	t and of the Council on the control of ma-
Volatile organic compounds :	(VOCV)		or volatile organic compounds ds (VOC) content: 18,55% w/w
	emissions (integrated	poll	4 November 2010 on industrial ution prevention and control) ds (VOC) content: 18,55% w/w

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

SikaScreed[®]-20 EBB Part B

Revision Date: 25.04.2023 Date of last issue: 19.02.2021

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

: Ma : Ha : Ca : Ma : Ca : Ca : Ha : Ve : To	armful if swallowed. ay be fatal if swallowed and enters airways. armful in contact with skin. auses severe skin burns and eye damage. ay cause an allergic skin reaction. auses serious eye damage. auses serious eye irritation. armful if inhaled. ery toxic to aquatic life. oxic to aquatic life with long lasting effects. armful to aquatic life with long lasting effects.
: Sh : Lo : As : Se : Ey : Sk	cute toxicity hort-term (acute) aquatic hazard ong-term (chronic) aquatic hazard spiration hazard erious eye damage ye irritation kin corrosion
	kin sensitisation uropean Agreement concerning the International Carriage of
Da : Cr : De : Ha : GI : Int : Int : Me on	angerous Goods by Road hemical Abstracts Service erived no-effect level alf maximal effective concentration lobally Harmonized System ternational Air Transport Association ternational Maritime Code for Dangerous Goods edian lethal dosis (the amount of a material, given all at nce, which causes the death of 50% (one half) of a group of
: Me air	st animals) edian lethal concentration (concentrations of the chemical in r that kills 50% of the test animals during the observation eriod)
	ternational Convention for the Prevention of Pollution from hips, 1973 as modified by the Protocol of 1978
: Oo : Pe : Pr : Re an ist	ccupational Exposure Limit ersistent, bioaccumulative and toxic redicted no effect concentration egulation (EC) No 1907/2006 of the European Parliament nd of the Council of 18 December 2006 concerning the Reg- tration, Evaluation, Authorisation and Restriction of Chemi- als (REACH), establishing a European Chemicals Agency
	ubstances of Very High Concern
r	MHCMCCHVTH ASLASESSEDCDHGINM or teMai peinSOPPR aris ca



Version 5.0

SikaScreed®-20 EBB Part B

Print Date 25.04.2023

Revision Date: 25.04.2023 Date of last issue: 19.02.2021 Version 5.0

~	Ð٧	R
v	ΓV	D

: Very persistent and very bioaccumulative

Further information

Classification of the m	Classification procedure:	
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN