

SikaCeram[®]-240 Rapid

DECLARATION OF PERFORMANCE No. 97395193

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	97395193
2	INTENDED USE/S	EN 12004:2007 + A1:2012 Adhesives for tiles in the form of cementitious adhesives intended for use in all internal and external tiling. Class C2FT
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3 and system 4
6a	HARMONISED STANDARD:	EN 12004:2007 + A1:2012
	Notified body/ies:	1599

Declaration of Performance

SikaCeram[®]-240 Rapid

97395193

2017.05 , ver. 1

1026

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire class	E	System 4	
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$	System 3	
Early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	System 3	
Tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$	System 3	EN
Tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$	System 3	12004:2007 + A1:2012
Tensile adhesion strength after freeze thaw cycles	$\geq 1,0 \text{ N/mm}^2$	System 3	
Dangerous substances	NPD		


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: TMM Refurbishment
At Athens on 11 October 2018

Name: Spyros Hatzifotis
Function: Managing Director
At Athens on 11 October 2018



.....



.....

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaCeram®-240 Rapid
97395193
2017.05 , ver. 1
1026



13

Sika Services AG, Zurich, Switzerland

DoP No. 97395193

EN 12004:2007 + A1:2012

Notified Body 1599

Adhesives for tiles in the form of cementitious adhesives intended for use in all internal and external tiling.
Class C2FT

Reaction to fire class	E
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after freeze thaw cycles	$\geq 1,0 \text{ N/mm}^2$

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaCeram®-240 Rapid

97395193

2017.05 , ver. 1

1026

3/4

BUILDING TRUST





Sika Hellas ABEE
Protomagias 15
14568, Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
SikaCeram®-240 Rapid
97395193
2017.05 , ver. 1
1026

4/4

BUILDING TRUST

