

# DECLARATION OF PERFORMANCE

## Sikafloor®-300 Rapid Level No. 115041502

1	<b>UNIQUE IDENTIFICATION CODE OF PRODUCT-TYPE:</b>	115041502
2	<b>INTENDED USE/ES</b>	EN 13813 Cementitious levelling compound
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 4 / System 3 for reaction to fire
6a	<b>HARMONIZED STANDARD:</b>	EN 13813
	Notified body/ies:	1378

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire class	A1 / A1 <sub>fl</sub>	EN 13813
Release of corrosive substances	CT	
PH value	NPD	
Water permeability	NPD	
Water vapour permeability	NPD	
Compressive strength	C50	
Flexural strength	F10	
Wear resistance	NPD	
Tensile adhesion strength	NPD	
Shock resistance	NPD	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	
Bond strength	NPD	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis  
Function: TMM Flooring  
At Athens on 23 March 2020



Name: Alexandros Melissourgos  
Function: Technical Manager  
At Athens on 23 March 2020



End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sika floor®-300 Rapid Level  
115041502  
2015.04 , Revision 1.0



15

Sika Services AG, Zurich, Switzerland

DoP No. 115041502

EN 13813

Notified laboratory 1378

## Cementitious leveling compound

Reaction to fire class	A1 / A1 <sub>fl</sub>
Release of corrosive substances	CT
PH value	NPD
Water permeability	NPD
Water vapour permeability	NPD
Compressive strength	C50
Flexural strength	F10
Wear resistance	NPD
Tensile adhesion strength	NPD
Shock resistance	NPD
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD
Bond strength	NPD

<http://dop.sika.com>**ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

**LEGAL NOTE**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Declaration of Performance**

Sika floor®-300 Rapid Level

115041502

2015.04, Revision 1.0



**Sika Hellas ABEE**  
15 Protomagias Str.  
14568 Kryoneri  
Athens-Greece  
[www.sika.gr](http://www.sika.gr)

**Declaration of Performance**  
Sika floor®-300 Rapid Level  
115041502  
2015.04 , Revision 1.0