

Revision Date: 16.02.2024 Date of last issue: -

Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

SikaForce®-479 L45 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Adhesive

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		-

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 Skin irritation, Category 2 Eye irritation, Category 2 Respiratory sensitisation, Category 1

Skin sensitisation, Category 1 Carcinogenicity, Category 2 Specific target organ toxicity - single exposure, Category 3, Respiratory system Specific target organ toxicity - repeated exposure, Category 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

1

Hazard pictograms

Danger

Signal word

Country GR 10000010322

H332: Harmful if inhaled.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317: May cause an allergic skin reaction.

- H351: Suspected of causing cancer.
- H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

SikaForce[®]-479 L45 Part B



Revision Date: 16.02.2024 Date of last issue: -		Version 1.0	Print Date 16.02.202
Hazard statements :	H315	Causes skin irritation.	
	H317	May cause an allergic skin reaction.	
		Causes serious eye irritation.	
	H332	Harmful if inhaled.	
		May cause allergy or asthma sympto ing difficulties if inhaled.	oms or breath-
		May cause respiratory irritation.	
	H351	Suspected of causing cancer.	
		May cause damage to organs throug or repeated exposure if inhaled.	Jh prolonged
Precautionary statements :	Prevention:		
	P201	Obtain special instructions befo	re use.
	P260	Do not breathe mist or vapours.	
	P264	Wash skin thoroughly after han	
	P280	Wear protective gloves/ protective gloves/ protection/ eye protection/ face protection/ tection.	
	Response:		
	P304 + P340	+ P312 IF INHALED: Remove pe air and keep comfortable for bre POISON CENTER/ doctor if you	eathing. Call a
	P342 + P311		

Hazardous components which must be listed on the label:

Formaldehyde, oligomeric reaction products with aniline and phosgene

Additional Labelling

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SikaForce[®]-479 L45 Part B

Print Date 16.02.2024

Revision Date: 16.02.2024 Date of last issue: - Version 1.0

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Formaldehyde, oligomeric reac- tion products with aniline and phosgene	32055-14-4 500-079-6 01-2119457024-46- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373	>= 25 - < 40
		specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	
		Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5	
		mg/l	
Substances with a workplace expo Titanium dioxide (> 10 µm)	13463-67-7 236-675-5		>= 5 - < 10
For explanation of abbreviations se	01-2119489379-17- XXXX		

For explanation of abbreviations see section 16.

:

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

SikaForce[®]-479 L45 Part B



Revision Date: 16.02.2024 Date of last issue: -	Version 1.0	Print Date 16.02.20
If inhaled	: Move to fresh air. Consult a physician after significant expo	sure.
In case of skin contact	: Take off contaminated clothing and shoes Wash off with soap and plenty of water. If symptoms persist, call a physician.	s immediately.
In case of eye contact	 Immediately flush eye(s) with plenty of wa Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialistic persists. 	
If swallowed	 Do not induce vomiting without medical a Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unco 	
4.2 Most important symptoms	and effects, both acute and delayed	
Symptoms	 Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed information and symptoms. 	tion on health effects
Risks	 irritant effects sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms of ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through pro- exposure if inhaled. 	
•	e medical attention and special treatment nee	eded
Treatment	: Treat symptomatically.	

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : In case of fire, use water/water spray/water jet/carbon diox-



Revision Date: 16.02.2024	
Date of last issue: -	

Version 1.0

ide/sand/foam/alcohol resistant foam/chemical powder for extinction.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion prod-	:	No hazardous combustion products are known
ucts		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.
----------------------	---	---

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up:Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see
	section 8).
	Do not get in eyes, on skin, or on clothing.
	For personal protection see section 8.
	Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
	Smoking, eating and drinking should be prohibited in the ap- plication area.



	Version 1.0	Print Date 16.02.202
	Provide sufficient air exchange and/or exhaust in Follow standard hygiene measures when handli products	
:	Normal measures for preventive fire protection.	
:	Handle in accordance with good industrial hygie practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the er	using do not
inc	luding any incompatibilities	
:	Keep container tightly closed in a dry and well-v place. Containers which are opened must be ca sealed and kept upright to prevent leakage. Stor ance with local regulations.	refully re-
:	No decomposition if stored and applied as direct	ted.
:	Cleaning with aprotic polar solvents must be ave Consult most current local Product Data Sheet p use.	
	: : :	 Provide sufficient air exchange and/or exhaust in Follow standard hygiene measures when handli products Normal measures for preventive fire protection. Handle in accordance with good industrial hygie practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the ermoluding any incompatibilities Keep container tightly closed in a dry and well-v place. Containers which are opened must be ca sealed and kept upright to prevent leakage. Stor ance with local regulations. No decomposition if stored and applied as direct consult most current local Product Data Sheet product and the ermolution of the stored product and the ermony of the stored product pr

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Formaldehyde, oligomeric reaction prod- ucts with aniline and phosgene	32055-14-4	TWA	0,02 ppm 0,2 mg/m3	GR OEL
		STEL	0,02 ppm 0,2 mg/m3	GR OEL
Titanium dioxide (> 10 μm)	13463-67-7	TWA (inhalable)	10 mg/m3	GR OEL
		TWA (respirable)	5 mg/m3	GR OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	:	Safety glasses with side-shields conforming to EN166	
		Eye wash bottle with pure water	
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-	

SikaForce[®]-479 L45 Part B



Revision Date: 16.02.2024 Date of last issue: -	Version 1.0	Print Date 16.0
	facturer specifications.	
	Suitable for short time use or protection Butyl rubber/nitrile rubber gloves (> 0,1 Contaminated gloves should be remove Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.	mm)
Skin and body protection	: Protective clothing (e.g. Safety shoes a long-sleeved working clothing, long trop and protective boots are additionally rea and stirring work.	users). Rubber aprons
Respiratory protection	 In case of inadequate ventilation wear Respirator selection must be based on exposure levels, the hazards of the pro- ing limits of the selected respirator. Use a properly fitted NIOSH approved respirator complying with an approved sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: Ensure adequate ventilation. This can exhaust extraction or by general ventilat ods for determining inhalation exposure ticular to the mixing / stirring area. In ca to keep the concentrations under the o limits then respiration protection measure Ensure adequate ventilation, especially 	known or anticipated oduct and the safe work- air-purifying or air-fed standard if a risk as- < 10000 ppm be achieved by local ation. (EN 689 - Meth- e). This applies in par- ase this is not sufficent ccupational exposure ures must be used.
Environmental exposure c	ontrols	
General advice	 Do not flush into surface water or sanit If the product contaminates rivers and respective authorities. 	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour Odour	: :	liquid viscous beige slight
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available

Upper/lower flammability or explosive limits

SikaForce[®]-479 L45 Part B



Revision Date: 16.02.2024 Date of last issue: -		Version 1.0	Print Date 16
Upper explosion limit / Up- per flammability limit	:	No data available	
Lower explosion limit / Lower flammability limit	:	No data available	
Flash point	:	> 200 °C Method: closed cup	
Auto-ignition temperature	:	> 500 °C	
Decomposition temperature	:	No data available	
рН	:	Not applicable substance/mixture is non-soluble (in water)	
Viscosity			
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)	
Solubility(ies)			
Water solubility	:	insoluble	
Partition coefficient: n- octanol/water	:	No data available	
Vapour pressure	:	0,01 hPa	
Density	:	ca. 1,6 g/cm3 (20 °C)	
Relative vapour density	:	No data available	
Particle characteristics	•	No data available	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	No hazards to be specially mentioned.
---------------------	---	---------------------------------------

10.4 Conditions to avoid

Conditions to avoid : No data available



Revision Date: 16.02.2024 Version 1.0 Date of last issue: -

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

Formaldehyde, oligomeric reaction products with aniline and phosgene:

Acute inhalation toxicity	:	LC50: 1,5 mg/l
		Exposure time: 4 h
		Test atmosphere: dust/mist
		Method: Expert judgement

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

May cause respiratory irritation.

Revision Date: 16.02.2024 Date of last issue: - Version 1.0



STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:



Revision Date: 16.02.2024 Version 1.0 Date of last issue: -

Additional ecological infor- : There is no data available for this product. mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe
	way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good

Print Date 16.02.2024

Revision Date: 16.02.2024 Date of last issue: - Version 1.0

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

: Not applicable

- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Formaldehyde, oligomeric reaction products with aniline and phosgene (Number on list 74, 56)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
Regulation (EU) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable
Severe III, Directive 2012/10/ELL of the European Darlier	~~~+	and of the Council on the control of m

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Revision Date: 16.02.2024



Date of last issue: -	
Volatile organic compounds	: Law on the incentive tax for volatile organic compounds (VOCV) no VOC duties
	Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Not applicable

Version 1.0

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements		
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H334	:	May cause allergy or asthma symptoms or breathing difficul-
		ties if inhaled.
H335	:	May cause respiratory irritation.
H351	:	Suspected of causing cancer.
H373	:	May cause damage to organs through prolonged or repeated
		exposure if inhaled.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Carc.	:	Carcinogenicity
Eye Irrit.	:	Eye irritation
Resp. Sens.	:	Respiratory sensitisation
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
GR OEL	:	Greece. Exposure limit values
GR OEL / TWA	:	Long term exposure limit
GR OEL / STEL	:	Short term exposure limit
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
1.050		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)



Revision Date: 16.02.2024	Version 1.0
Date of last issue: -	

MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN