

SikaRep®-200 Multi

DECLARATION OF PERFORMANCE

No. 80744666

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	80744666
2	INTENDED USE/S:	EN 998-1:2016 General purpose rendering / plastering
		mortar for external and internal use (GP)
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 998-1:2016

SikaRep®-200 Multi 80744666 2021.10 , Revision 2

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Water absorption	W _c 2	System 4	
Water vapour permeability	μ≤ 60	System 4	
Adhesion	≥ 0.8 MPa – FP: A (Substrate: concrete)	System 4	EN 000 1:2016
Thermal conductivity	(λ _{10, dry,mat}) 0.8 W/m·K (tab. Mean value, P=50%)	System 4	EN 998-1:2016
Reaction to fire	Class A1	System 4	
Durability	NPD*	System 4	

*NPD - No performance determined

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos Function: Target Market Manager

Refurbishment

At Athens on 27 October 2021

Name: Angeliki Zacharopoulou Function: QEHS Manager At Athens on 27 October 2021

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
SikaRep®-200 Multi	EN 1504-3:2005	47055563
SikaRep®-200 Multi	EN 998-2:2016	74946376





12

Sika Hellas	ARFE	Athone	- Graaca
Sika nelias	ABEE.	Amens	- Greece

DoP No. 80744666

EN 998-1:2016

General purpose rendering / plastering mortar for external and internal use (GP)

Water absorption	W _c 2	
Water vapour permeability	 μ≤ 60	
	≥ 0.8 MPa – FP: A	
Adhesion	(Substrate: concrete)	
Thermal conductivity	$(\lambda_{10, dry,mat})$ 0.8 W/m·K (tab. Mean value, P=50%)	
Reaction to fire	Class A1	

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE

15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

SikaRep®-200 Multi 80744666 2021.10 , Revision 2

