

Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®]-Comfort Adhesive Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Flooring system, For professional users only.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 Skin irritation, Category 2 Eye irritation, Category 2 Respiratory sensitisation, Category 1

Skin sensitisation, Category 1 Carcinogenicity, Category 2 Specific target organ toxicity - single exposure, Category 3, Respiratory system Specific target organ toxicity - repeated exposure, Category 2 H332: Harmful if inhaled. H315: Causes skin irritation.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317: May cause an allergic skin reaction.


H351: Suspected of causing cancer.

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Sikafloor[®]-Comfort Adhesive Part B

Revision Date: 05.01.2024 Date of last issue: 01.02.2022



te of	last issue: 01.02.2022		
Ha	azard statements :	H315	Causes skin irritation.
		H317	May cause an allergic skin reaction.
		H319	Causes serious eye irritation.
		H332	Harmful if inhaled.
		H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
		H335	May cause respiratory irritation.
		H351	Suspected of causing cancer.
		H373	May cause damage to organs through pro- longed or repeated exposure if inhaled.
Pr	ecautionary statements :	Prevention:	
	-	P201	Obtain special instructions before use.
		P260	Do not breathe mist or vapours.
		P264	Wash skin thoroughly after handling.
		P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing pro- tection.
		Response:	
		P304 + P340 + F	2312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
		P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

Version 4.0

Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

2,2'-methylenediphenyl diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Sikafloor®-Comfort Adhesive Part B

Print Date 05.01.2024

Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 \longrightarrow specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>= 60 - < 80

Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0



4,4'-methylenediphenyl diisocya- nate	101-68-8 202-966-0 01-2119457014-47- XXXX	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Acute toxicity esti- mate Acute inhalation tox- icity (dust/mist): 1,5	>= 10 - < 20
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1 227-534-9 01-2119480143-45- XXXX	mg/l Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT RE 2; H373	>= 10 - < 20

Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0



2,2'-methylenediphenyl diisocya- nate	2536-05-2 219-799-4 01-2119927323-43- XXXX	Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT RE 2; H373 \longrightarrow specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %	< 0,1
--	---	---	-------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures				
General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.		
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.		
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.		
In case of eye contact	:	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.		
If swallowed	:	Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.		
4.2 Most important symptoms and effects, both acute and delayed				
Symptoms	:	Asthmatic appearance Cough Respiratory disorder		
Country CP 00000021//28				

Sikafloor®-Comfort Adhesive Part B



Revision Date: 05.01.2024 Version 4.0 Date of last issue: 01.02.2022 Allergic reactions Excessive lachrymation Erythema Headache Dermatitis See Section 11 for more detailed information on health effects and symptoms. Risks irritant effects · sensitising effects Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure if inhaled. 4.3 Indication of any immediate medical attention and special treatment needed

Treatment

: Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2 Special hazards arising from	th€	e substance or mixture
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.

Print Date 05.01.2024

Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0

6.2 Environmental precautions

Environmental precautior	s :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling :	 Avoid formation of aerosol. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or exhaust in work rooms. Follow standard hygiene measures when handling chemical products
Advice on protection against : fire and explosion	Normal measures for preventive fire protection.
Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2 Conditions for safe storage, inc	cluding any incompatibilities
Requirements for storage : areas and containers	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.
Further information on stor- : age stability	No decomposition if stored and applied as directed.
7.3 Specific end use(s)	
Specific use(s) :	Cleaning with aprotic polar solvents must be avoided.
Country GR 000000214438	7



Revision Date: 05.01.2024 Date of last issue: 01.02.2022

Version 4.0

Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 ppm	GR OEL
			0,2 mg/m3	
		STEL	0,02 ppm	GR OEL
			0,2 mg/m3	

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Hand protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk as- sessment indicates this is necessary. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth-
		0 /



Revision Date: 05.01.2024
Date of last issue: 01.02.2022

Version 4.0

ods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used. Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

General advice	:	Do not flush into surface water or sanitary sewer system.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

P C	hysical state olour dour	an : :	liquid brown characteristic
	lelting point/range / Freezing pint	:	No data available
В	oiling point/boiling range	:	No data available
F	lammability (solid, gas)	:	No data available
U	pper/lower flammability or e	xp	losive limits
	Upper explosion limit / Up- per flammability limit	:	No data available
	Lower explosion limit / Lower flammability limit	:	No data available
F	lash point	:	ca. 220 °C Method: closed cup
A	uto-ignition temperature	:	No data available
D	ecomposition temperature	:	No data available
p	Н	:	Not applicable substance/mixture reacts with water
v	iscosity		
	Viscosity, kinematic	:	> 7 mm2/s (40 °C)
S	olubility(ies)		
	Water solubility	:	insoluble
-	artition coefficient: n- ctanol/water	:	No data available

_

Sikafloor®-Comfort Adhesive Part B



Revision Date: 05.01.2024 Date of last issue: 01.02.2022	Version 4.0	Print Date 05.01.2024				
Vapour pressure	: 0,01 hPa					
Density	: ca. 1,24 g/cm3 (20 °C)					
Relative vapour density	No data available					
Particle characteristics	No data available					
9.2 Other information No data available						
SECTION 10: Stability and reactivity						
10.1 Reactivity						
No dangerous reaction known	nder conditions of normal use.					
10.2 Chemical stability						
The product is chemically stable						
10.3 Possibility of hazardous read	ions					
Hazardous reactions	No hazards to be specially mentioned	l.				
10.4 Conditions to avoid						
Conditions to avoid	No data available					
10.5 Incompatible materials						
Materials to avoid	No data available					
10.6 Hazardous decomposition p	oducts					

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

	Acute toxicity Harmful if inhaled.			
	Components:			
	Diphenylmethanediisocya	nate,	isomeres and homologues:	
	Acute oral toxicity	:	LD50 Oral (Rat): > 10.000 mg/kg	
	Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after	
0			10/	47

Sikafloor®-Comfort Adhesive Part B



Revision Date: 05.01.2024 Date of last issue: 01.02.2022	Version 4.0	Print Date 05.01.2024
	short term inhalation.	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 9.400 mg/kg	
4,4'-methylenediphenyl diis	socyanate:	
Acute oral toxicity	: LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401	
Acute inhalation toxicity	: LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement	
	Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method	
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye in Causes serious eye irritation		
Respiratory or skin sensiti	sation	
Skin sensitisation May cause an allergic skin re	eaction.	
Respiratory sensitisation May cause allergy or asthma	symptoms or breathing difficulties if inhaled.	
Germ cell mutagenicity Not classified due to lack of a	data.	
Carcinogenicity Suspected of causing cancer	r.	
Reproductive toxicity Not classified due to lack of c	data.	
STOT - single exposure May cause respiratory irritation	on.	
STOT - repeated exposure May cause damage to organ	s through prolonged or repeated exposure if in	haled.
Aspiration toxicity Not classified due to lack of c	data.	
11.2 Information on other hazar	ds	
Endocrine disrupting prop	erties	
Product: Assessment	: The substance/mixture does not contain	components consid-



Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Com	ponents:

Diphenylmethanediisocyanate, isomeres and homologues:

Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
		iereie ei er i / er i igneri

12.7 Other adverse effects

Product:

Additional ecological infor-	:	There is no data available for this product.
mation		

Print Date 05.01.2024

Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	:	08 05 01* waste isocyanates
Contaminated packaging	:	15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.2	2 UN proper shipping name		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.3	Transport hazard class(es)		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	ΙΑΤΑ	:	Not regulated as a dangerous good
14.4	Packing group		
	ADR	:	Not regulated as a dangerous good
	IMDG	:	Not regulated as a dangerous good
	IATA (Cargo)	:	Not regulated as a dangerous good

Sikafloor[®]-Comfort Adhesive Part B



Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	 Conditions of restriction for the following entries should be considered: Number on list 75, 3Diphenylmethanediisocyanate, isomeres and homologues (Number on list 74, 56) 4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) o-(p-isocyanatobenzyl)phenyl isocy- anate (Number on list 74, 56)
	Diphenylmethanediisocyanate, iso- meres and homologues (Number on list 74, 56) 4,4'-methylenediphenyl diisocyanate (Number on list 74, 56) o-(p-isocyanatobenzyl)phenyl isocy- anate (Number on list 74, 56) 2,2'-methylenediphenyl diisocyanate (Number on list 74, 56)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation	: Not applicable

Sikafloor®-Comfort Adhesive Part B



Revision Date: 05.01.2024 Date of last issue: 01.02.2022	Version 4.0	Print Date 05.01.2024
(Annex XIV)		
Regulation (EC) No 1005/2009 on su plete the ozone layer	ubstances that de- : Not applicable	
Regulation (EU) 2019/1021 on persis tants (recast)	stent organic pollu- : Not applicable	
Regulation (EC) No 649/2012 of the I ment and the Council concerning the of dangerous chemicals		
jor-accident hazards involving danger	he European Parliament and of the Counc rous substances. ot applicable	il on the control of ma-
(V0	aw on the incentive tax for volatile organic OCV) VOC duties	compounds
	rective 2010/75/EU of 24 November 2010 nissions (integrated pollution prevention a	

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Not applicable

SECTION 16: Other information

Full text of H-Statement	s	
H315	:	Caus
H317	:	Mav

H315 H317 H319 H332 H334 H335 H351 H373		Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. May cause damage to organs through prolonged or repeated exposure if inhaled.	
Full text of other abbreviations			
Acute Tox. Carc. Eye Irrit. Resp. Sens. Skin Irrit. Skin Sens.	::	Acute toxicity Carcinogenicity Eye irritation Respiratory sensitisation Skin irritation Skin sensitisation	

Sikafloor®-Comfort Adhesive Part B

Revision Date: 05.01.2024 Date of last issue: 01.02.2022

STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
GR OEL	:	Greece. Exposure limit values
GR OEL / TWA	:	Long term exposure limit
GR OEL / STEL	:	Short term exposure limit
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-
		istration, Evaluation, Authorisation and Restriction of Chemi-
		cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

Version 4.0

Further information

Classification of the	e mixture:	Classification procedure:
Acute Tox. 4	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

Revision Date: 05.01.2024 Date of last issue: 01.02.2022 Version 4.0



GR / EN