

Revision Date: 12.01.2024 Date of last issue: 27.01.2022 Version 5.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1 Product identifier**

Trade name

: Sikafloor<sup>®</sup>-316 Part A

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use	: Polyurethane coating

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		-

### **1.4 Emergency telephone number**

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361f: Suspected of damaging fertility.
Long-term (chronic) aquatic hazard, Cat-	H411: Toxic to aquatic life with long lasting effects.
egory 2	

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Warning	• • •
Hazard statements	:	H226 H317 H361f H411	Flammable liquid and vapour. May cause an allergic skin reaction. Suspected of damaging fertility. Toxic to aquatic life with long lasting effects.

# Sikafloor<sup>®</sup>-316 Part A

Revision Date: 12.01.2024 Date of last issue: 27.01.2022



Precautionary statements :	Prevention:	
-	P201	Obtain special instructions before use.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
	Response:	
	P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
	P391	Collect spillage.

Version 5.0

### Hazardous components which must be listed on the label:

Hydroxyphenyl-benzotriazol derivates Pentamethyl piperidylsebacate

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

### Components

oomponenta			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
Hydroxyphenyl-benzotriazol deri-	Not Assigned	Skin Sens. 1A; H317	>= 10 - < 20
vates	400-830-7	Aquatic Chronic 2;	
	01-0000015075-76-	H411	
	XXXX		
2-methoxy-1-methylethyl acetate	108-65-6	Flam. Liq. 3; H226	>= 5 - < 10
Contains:	203-603-9	STOT SE 3; H336	
2-methoxypropyl acetate <= 1 %	01-2119475791-29-		
	XXXX		

# Sikafloor<sup>®</sup>-316 Part A

Revision Date: 12.01.2024 Date of last issue: 27.01.2022



Version 5.0

Hydrocarbons, C9, aromatics	Not Assigned 918-668-5 01-2119455851-35- XXXX [corresponding group CAS 64742-95- 6]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 5 - < 10
Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 5 - < 10
bis(neodecanoyloxy)dioctylstanna ne	68299-15-0 269-595-4 01-2120770890-48- XXXX	STOT SE 2; H371	>= 2,5 - < 5
1-methoxy-2-propanol Contains: 2-methoxypropanol <= 0,3 %	107-98-2 203-539-1 01-2119457435-35- XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 2,5 - < 5

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Do not induce vomiting without medical advice.

Sikafloor <sup>®</sup> -316 P	art A
-------------------------------	-------

<b>Sika</b> ®
Print Date 12.01.2024

Revision Date: 12.01.2024 Date of last issue: 27.01.2022 Version 5.0

Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Allergic reactions See Section 11 for more detailed information on health effects and symptoms.
Risks	:	sensitising effects
		May cause an allergic skin reaction. Suspected of damaging fertility.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : T	Freat symptomatically.
---------------	------------------------

## **SECTION 5: Firefighting measures**

5.1	Extinguishing media		
	Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
	Unsuitable extinguishing media	:	Water High volume water jet
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water
			courses.
	Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Revision Date: 12.01.2024 Date of last issue: 27.01.2022 Version 5.0



### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protecti	e equipment and emergency procedures
Personal precautions :	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.
6.2 Environmental precautions	
Environmental precautions :	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform

respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible ab-
		sorbent material, (e.g. sand, earth, diatomaceous earth, ver-
		miculite) and place in container for disposal according to local
		/ national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Advice on safe handling	:	<ul> <li>Avoid exceeding the given occupational exposure limits (see section 8).</li> <li>Do not get in eyes, on skin, or on clothing.</li> <li>For personal protection see section 8.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should</li> </ul>
		not be employed in any process in which this mixture is being used.
		Smoking, eating and drinking should be prohibited in the application area.
		Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
Advice on protection against fire and explosion		Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety
Country GR 10000000886		5

Revision Date: 12.01.2024

Date of last issue: 27.01.2022



Version 5.0

	practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	
7.2 Conditions for safe storage, inc	cluding any incompatibilities	
Requirements for storage : areas and containers	Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re- sealed and kept upright to prevent leakage. Store in accord- ance with local regulations.	
Further information on stor- : age stability	No decomposition if stored and applied as directed.	
7.3 Specific end use(s)		

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame-	Basis *	
		of exposure)	ters *		
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake			
	through the	through the skin, Indicative			
		TWA	50 ppm 275 mg/m3	2000/39/EC	
		TWA	50 ppm 275 mg/m3	GR OEL	
	chemical fac the likely cor of exposure	Further information: The notation 'skin' (D), pointing out certain chemical factors of the table of paragraph of 1 article 3, implies the likely contribution to of these chemical factors to the quantity of exposure to workers which are absorbed through the skin at the			
	direct contac	direct contact with these.			
		STEL	100 ppm 550 mg/m3	GR OEL	
1-methoxy-2-propanol	107-98-2	TWA	100 ppm 375 mg/m3	2000/39/EC	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	150 ppm 568 mg/m3	2000/39/EC	
		TWA	100 ppm 360 mg/m3	GR OEL	
		Further information: The notation 'skin' (D), pointing out certain chemical factors of the table of paragraph of 1 article 3, implies			
	the likely cor	the likely contribution to of these chemical factors to the quantity			
		of exposure to workers which are absorbed through the skin at the direct contact with these.			
		STEL	300 ppm 1.080 mg/m3	GR OEL	

Print Date 12.01.2024

Revision Date: 12.01.2024 Date of last issue: 27.01.2022

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### 8.2 Exposure controls

### **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment	
Eye/face protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection :	Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionaly recommended for mixing and stirring work.
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Environmental exposure control	ols
General advice :	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform

respective authorities.

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: transparent
Odour	: solvent-like

# Sikafloor<sup>®</sup>-316 Part A

Print Date 12.01.2024

Revision Date: 12.01.2024 Date of last issue: 27.01.2022 Version 5.0

	Melting point/range / Freezing point	:	No data available
	Boiling point/boiling range	:	No data available
	Flammability (solid, gas)	:	No data available
	Upper/lower flammability or e Upper explosion limit / Up- per flammability limit	-	
	Lower explosion limit / Lower flammability limit	:	0,8 %(V)
	Flash point	:	ca. 55 °C Method: closed cup
	Auto-ignition temperature	:	270 °C
	Decomposition temperature	:	No data available
	рН	:	Not applicable substance/mixture is non-soluble (in water)
	Viscosity Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
	Solubility(ies)		
	Water solubility	:	insoluble
	Partition coefficient: n- octanol/water	:	No data available
	Vapour pressure	:	4,9996 hPa
	Density	:	ca. 1,03 g/cm3 (20 °C)
	Relative vapour density	:	No data available
	Particle characteristics	:	No data available
2	Other information		

### 9.2 Other information

No data available

## **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

Revision Date: 12.01.2024 Date of last issue: 27.01.2022 Version 5.0



SECTION 11: Toxicological	information
No decomposition if stored	and applied as directed.
10.6 Hazardous decompositio	n products
Materials to avoid	: No data available
10.5 Incompatible materials	
Conditions to avoid	: Heat, flames and sparks.
10.4 Conditions to avoid	
	Vapours may form explosive mixture with air.
Hazardous reactions	: Stable under recommended storage conditions.
10.3 Possibility of hazardous	reactions
The product is chemically s	stable.
10.2 Chemical stability	

Acute toxicity Not classified based on available information.

### Components:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg
Hydrocarbons, C9, aromatic	s:	
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
Pentamethyl piperidylsebac	ate	
Acute oral toxicity	:	LD50 Oral (Rat): 3.230 mg/kg
-		
bis(neodecanoyloxy)dioctyl		
<b>bis(neodecanoyloxy)dioctyl</b> Acute oral toxicity		nnane:

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50: 7,5 mg/l Exposure time: 4 h

# Sikafloor<sup>®</sup>-316 Part A



Revision Date: 12.01.2024 Date of last issue: 27.01.2022	Version 5.0	Print Date 12
	Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 mg/kg	
Skin corrosion/irritation Not classified based on availa	ble information.	
Components:		
Hydrocarbons, C9, aromatic		
Assessment	: Repeated exposure may cause skin dry	ness or cracking.
Serious eye damage/eye irri Not classified based on availa		
Respiratory or skin sensitis	ation	
<b>Skin sensitisation</b> May cause an allergic skin rea	action.	
<b>Respiratory sensitisation</b> Not classified based on availa	ble information.	
Germ cell mutagenicity Not classified based on availa	ble information.	
<b>Carcinogenicity</b> Not classified based on availa	ble information.	
Reproductive toxicity Suspected of damaging fertilit	у.	
<b>STOT - single exposure</b> Not classified based on availa	ble information.	
STOT - repeated exposure Not classified based on availa	ble information.	
Aspiration toxicity Not classified based on availa	ble information.	
11.2 Information on other hazard	ls	
Endocrine disrupting prope	rties	
Product:		
Assessment	: The substance/mixture does not contair ered to have endocrine disrupting prope REACH Article 57(f) or Commission De (EU) 2017/2100 or Commission Regula levels of 0.1% or higher.	erties according to legated regulation

# Sikafloor<sup>®</sup>-316 Part A

Revision Date: 12.01.2024 Date of last issue: 27.01.2022 Print



### **SECTION 12: Ecological information**

### 12.1 Toxicity

### **Components:** Hydrocarbons, C9, aromatics: Toxicity to algae/aquatic ÷ (Pseudokirchneriella subcapitata (green algae)): 2,6 - 2,9 plants mg/l Exposure time: 72 h Pentamethyl piperidylsebacate: Toxicity to fish : LC50 (Fish): 0,97 mg/l Exposure time: 96 h M-Factor (Acute aquatic tox-: 1 icity) M-Factor (Chronic aquatic : 1 toxicity) 1-methoxy-2-propanol: Toxicity to fish : LC50 (Fish): > 100 mg/l Exposure time: 96 h Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h aquatic invertebrates 12.2 Persistence and degradability No data available 12.3 Bioaccumulative potential No data available 12.4 Mobility in soil

Version 5.0

No data available

### 12.5 Results of PBT and vPvB assessment

5

### Product:

```
Assessment
```

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

### Product:

Assessment	: The substance/mixture does not contain components consid-
	ered to have endocrine disrupting properties according to
	REACH Article 57(f) or Commission Delegated regulation

Revision Date: 12.01.2024 Date of last issue: 27.01.2022



Version 5.0

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

### Product:

Additional ecological infor- mation	:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
		Toxic to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	<ul> <li>The generation of waste should be avoided or minimized wherever possible.</li> <li>Empty containers or liners may retain some product residues.</li> <li>This material and its container must be disposed of in a safe way.</li> <li>Dispose of surplus and non-recyclable products via a licensed</li> </ul>
	waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## **SECTION 14: Transport information**

## 14.1 UN number or ID number

ADR	:	UN 1263	
IMDG	:	UN 1263	
ΙΑΤΑ	:	UN 1263	
14.2 UN proper shipping name			
ADR	:	PAINT	
IMDG	:	PAINT (solvent naphtha)	
ΙΑΤΑ	:	Paint	
14.3 Transport hazard class(es)			
		Class	Subsidiary risks
ADR	:	3	
IMDG	:	3	

Revision Date: 12.01.2024 Date of last issue: 27.01.2022 Version 5.0



_	Date of last issue: 27.01.2022		Version 5.6	
	ΙΑΤΑ	:	3	
	14.4 Packing group			
	ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code	:	III F1 30 3 (D/E)	
	<b>IMDG</b> Packing group Labels EmS Code	:	III 3 F-E, <u>S-E</u>	
	IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	366 Y344 III Flammable Liquids	
	IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	355 Y344 III Flammable Liquids	
	14.5 Environmental hazards			
	ADR Environmentally hazardous IMDG	:	yes	
	Marine pollutant	:	yes	
	IATA (Passenger) Environmentally hazardous	:	yes	

## IATA (Cargo)

Environmentally hazardous : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

# Sikafloor<sup>®</sup>-316 Part A



Revision Date: 12.01.2024 Date of last issue: 27.01.2022 Version 5.0

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors			Not applicable
REACH Information:	All substances contain - registered by our ups - registered by us, and - excluded from the re - exempted from the re		am suppliers, and/or tion, and/or
REACH - Restrictions on the ma the market and use of certain da mixtures and articles (Annex XV	ngerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)		:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer		:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)		:	Not applicable
Regulation (EC) No 649/2012 of ment and the Council concerning of dangerous chemicals		:	Not applicable

### E1

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

(including jet fuels), (c) gas oils (including diesel fuels, home	P5c	FLAMMABLE LIQUIDS
alternative fuels serving the same purposes and with similar		<ul> <li>properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)</li> <li>Law on the incentive tax for volatile organic compounds (VOCV)</li> <li>Volatile organic compounds (VOC) content: 53,46% w/w</li> <li>Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)</li> </ul>

Revision Date: 12.01.2024 Date of last issue: 27.01.2022

### Version 5.0



### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

### Full text of H-Statements

H226 H304 H317 H335 H336 H361f H371 H400 H410 H411		Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs if swallowed. Very toxic to aquatic life. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects.
Full text of other abbreviat	ions	
Aquatic Acute Aquatic Chronic	:	Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GR OEL		Greece. Exposure limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GR OEL / TWA	:	Long term exposure limit
GR OEL / STEL	:	Short term exposure limit
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG		International Maritime Code for Dangerous Goods
LD50		Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
	-	air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
Nuptry GR 1000000886		15 / /

Revision Date: 12.01.2024 Date of last issue: 27.01.2022



Version	5.0
101011	0.0

	Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament
	and of the Council of 18 December 2006 concerning the Reg-
	istration, Evaluation, Authorisation and Restriction of Chemi-
	cals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

### Further information

Classification of the mixture:		Classification procedure:
Flam. Liq. 3	H226	Based on product data or assessment
Skin Sens. 1	H317	Calculation method
Repr. 2	H361f	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN