

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor[®]-263 SL N Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Epoxy coating

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture


Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 Eye irritation, Category 2 Skin sensitisation, Category 1 Long-term (chronic) aquatic hazard, Category 2 H315: Causes skin irritation.

- H319: Causes serious eye irritation.
- H317: May cause an allergic skin reaction.
- H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)



Precautionary statements : Prevention:

Sikafloor[®]-263 SL N Part A

Print Date 07.12.2023

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0

P261 P264 P273 P280	Avoid breathing mist or vapours. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.
Response:	
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P391	Collect spillage.

Hazardous components which must be listed on the label:

bis-[4-(2,3-epoxipropoxi)phenyl]propane bis-[4-(2,3-epoxypropoxy)phenyl]methane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. p-tert-butylphenyl 1-(2,3-epoxy)propyl ether

Additional Labelling

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Components Chemical name	CAS-No.	Classification	Concentration
Chemical name	EC-No.	Classification	(% w/w)
	Registration number		(70 00/00)
bis-[4-(2,3-	1675-54-3	Skin Irrit. 2; H315	>= 25 - < 40
epoxipropoxi)phenyl]propane	216-823-5	Eye Irrit. 2; H319	20 40
epositioposis/priori grippopario	01-2119456619-26-	Skin Sens. 1; H317	
	XXXX	Aquatic Chronic 2;	
		H411	
		specific concentration	
		limit	
		Eye Irrit. 2; H319	
		>= 5 %	
		Skin Irrit. 2; H315	
		>= 5 %	
bis-[4-(2,3-	Not Assigned	Skin Irrit. 2; H315	>= 5 - < 10
epoxypropoxy)phenyl]methane	701-263-0	Skin Sens. 1A; H317	
	01-2119454392-40-	Aquatic Chronic 2;	
	XXXX	H411	
oxirane, mono[(C12-14-	68609-97-2	Skin Irrit. 2; H315	>= 2,5 - < 5
alkyloxy)methyl] derivs.	271-846-8	Skin Sens. 1; H317	
	01-2119485289-22-		
benzyl alcohol	XXXX 100-51-6	Acute Tox. 4; H302	>= 1 - < 2,5
benzyi alconol	202-859-9	Acute Tox. 4; H302 Acute Tox. 4; H332	>= 1 - < 2,5
	01-2119492630-38-	Eye Irrit. 2; H319	
	XXXX		
		Acute toxicity esti-	
		mate	
		Acute oral toxicity:	
		1.620 mg/kg	
		Acute inhalation tox-	
		icity (dust/mist):	
		4,178 mg/l	
p-tert-butylphenyl 1-(2,3-	3101-60-8	Skin Sens. 1; H317	>= 1 - < 2,5
epoxy)propyl ether	221-453-2	Aquatic Chronic 2;	
	01-2119959496-20- XXXX	H411	
Substances with a workplace expo		1	
Titanium dioxide (> 10 μm)	13463-67-7		>= 5 - < 10
	236-675-5		
	01-2119489379-17-		
For explanation of abbreviations of	XXXX		

For explanation of abbreviations see section 16.

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0



SECTION 4: First aid measures

4.1 Description of first aid measu	res		
General advice	 Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. 		
If inhaled	: Move to fresh air. Consult a physician after significant exposure.		
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. 		
In case of eye contact	 Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. 		
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 		
4.2 Most important symptoms an	d effects, both acute and delayed		
Symptoms	: Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms.		
Risks	: irritant effects sensitising effects		
	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.		
4.3 Indication of any immediate medical attention and special treatment needed			
Treatment	: Treat symptomatically.		
SECTION 5: Firefighting meas	ures		
5.1 Extinguishing media			
Suitable extinguishing media	: In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.		



Revision Date: 07.12.2023 Version 5.0 Date of last issue: 21.04.2023

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire- fighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment.
		Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform
	respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	 Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
		useu.



Revision Date: 07.12.2023 Date of last issue: 21.04.2023		Version 5.0	Print Date 07.12.2
		Smoking, eating and drinking should be prohibite plication area. Follow standard hygiene measures when handlin products	
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygien practice. When using do not eat or drink. When u smoke. Wash hands before breaks and at the en	ising do not
7.2 Conditions for safe storage, i	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ve place. Containers which are opened must be car sealed and kept upright to prevent leakage. Store ance with local regulations.	efully re-
Further information on stor- age stability	:	No decomposition if stored and applied as directed	əd.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet pr use.	rior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
Titanium dioxide (> 10 μm)	13463-67-7	TWA (inhalable)	10 mg/m3	GR OEL
		TWA (respirable)	5 mg/m3	GR OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equip	ment
Eye/face protection	: Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm)

Sikafloor[®]-263 SL N Part A

Revision Date: 07.12.2023



Date of last issue: 21.04.2023			
	Sui Vito	ntaminated gloves should be remov table for permanent exposure: on gloves (0.4 mm), akthrough time >30 min.	/ed.
Skin and body protection	long and	tective clothing (e.g. Safety shoes a g-sleeved working clothing, long tro l protective boots are additionaly re l stirring work.	ousers). Rubber aprons
Respiratory protection	: In c Res exp ing org A1: Ens exh ods ticu to k	ase of inadequate ventilation wear spirator selection must be based on osure levels, the hazards of the pro- limits of the selected respirator. anic vapor filter (Type A) < 1000 ppm; A2: < 5000 ppm; A3: sure adequate ventilation. This can aust extraction or by general ventila- for determining inhalation exposur lar to the mixing / stirring area. In c seep the concentrations under the c ts then respiration protection measures	 known or anticipated oduct and the safe work- 10000 ppm be achieved by local ation. (EN 689 - Meth- re). This applies in par- case this is not sufficent occupational exposure
Environmental exposure	controls		
General advice		not flush into surface water or saniti te product contaminates rivers and	

respective authorities.

Version 5.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Appearance Colour Odour		liquid viscous various very faint
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper/lower flammability or e	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	No data available
		No data available No data available
per flammability limit	:	

Sikafloor[®]-263 SL N Part A

Print Date 07.12.2023

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0

Auto-ignition temperature	:	ca. 436 °C
Decomposition temperature	:	No data available
рН	:	ca. 6,5 (20 °C) Concentration: 100 %
Viscosity		
Viscosity, dynamic	:	ca. 3.600 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	0,01 hPa
		0,01 hPa
Density	:	ca. 1,6 g/cm3 (20 °C)
Relative vapour density	:	No data available
Particle characteristics	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Sikafloor[®]-263 SL N Part A

Revision Date: 07.12.2023 Date of last issue: 21.04.2023

Acute toxicity

Version 5.0



10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Components: bis-[4-(2,3-epoxipropoxi)pbery]propane: Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg coxirane, mono[(C12-14-alky/vymethyl] derivs.: Acute oral toxicity : Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg benzyl alcohol: : LD50 Oral (Rat): > 5.000 mg/kg Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg Acute oral toxicity : LD50 Oral (Rat): > 6.000 mg/kg Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist Acute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method Acute toxicity estimate: 4,178 mg/l P-tert-butylphenyl 1-(2,3-epoxypropyl ether: Acute toxicity estimate: 4,178 mg/l Acute oral toxicity : LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mist Acute oral toxicity : LC50 (Dermal (Rabbit): 6.000 mg/kg Acute dermal toxicity :	Not classified based on available information.			
Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute dermal toxicity:LD50 Dermal (Rabbit): > 5.000 mg/kgoxirane, mono[(C12-14-alkyloxy)methyl] derivs.: Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgbenzyl alcohol: Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute oral toxicity:LD50 Oral (Rat): 1.620 mg/kg Method: Calculation methodAcute oral toxicity:LD50 Oral (Rat): 1.620 mg/kg Method: Calculation methodAcute inhalation toxicity:LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation methodp-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicity:LC50 (Rat): > 5.000 mg/kgAcute inhalation toxicity:LC50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 6.000 mg/kgAcute oral toxicity:LD50 Oral (Rat): > 6.000 mg/kgAcute inhalation toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kg	Components:			
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.:Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgbenzyl alcohol:.Acute oral toxicity:LD50 Oral (Rat): 1.620 mg/kgAcute oral toxicity:LD50 Oral (Rat): 1.620 mg/kgAcute inhalation toxicity:LC50 (Rat): > 4,178 mg/lExposure time: 4 h Test atmosphere: dust/mistAcute toxicity estimate: 4,178 mg/lP-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute oral toxicity:LD50 Oral (Rat): > 6.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 6.000 mg/kgAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.:.				
Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgbenzyl alcohol: Acute oral toxicity:LD50 Oral (Rat): 1.620 mg/kg Acute toxicity estimate: 1.620 mg/kg Method: Calculation methodAcute inhalation toxicity:LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation methodp-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicity:LC50 (Rat): > 5.000 mg/kgAcute inhalation toxicity:LC50 Oral (Rat): > 5.000 mg/kgp-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.:	Acute dermal toxicity :	LD50 Dermal (Rabbit): > 5.000 mg/kg		
benzyl alcohol:Acute oral toxicity:LD50 Oral (Rat): 1.620 mg/kg Acute toxicity estimate: 1.620 mg/kg Method: Calculation methodAcute inhalation toxicity:LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation methodp-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicity:LC50 (Rat): > 5.000 mg/kgAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.:	oxirane, mono[(C12-14-alkylox	y)methyl] derivs.:		
Acute oral toxicity:LD50 Oral (Rat): 1.620 mg/kg Acute toxicity estimate: 1.620 mg/kg Method: Calculation methodAcute inhalation toxicity:LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method P-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 6.000 mg/kgAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.:	Acute oral toxicity :	LD50 Oral (Rat): > 5.000 mg/kg		
Acute oral toxicity:LD50 Oral (Rat): 1.620 mg/kg Acute toxicity estimate: 1.620 mg/kg Method: Calculation methodAcute inhalation toxicity:LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method P-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LD50 Oral (Rat): > 6.000 mg/kgAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.:	benzvl alcohol:			
Method: Calculation methodAcute inhalation toxicity:LC50 (Rat): > 4,178 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation method p-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicityAcute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.	•	LD50 Oral (Rat): 1.620 mg/kg		
Exposure time: 4 h Test atmosphere: dust/mistAcute toxicity estimate: 4,178 mg/l Test atmosphere: dust/mist Method: Calculation methodp-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicityAcute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.				
Test atmosphere: dust/mist Method: Calculation methodp-tert-butylphenyl 1-(2,3-epoxy)propyl ether: Acute oral toxicity:Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.:	Acute inhalation toxicity :	Exposure time: 4 h		
Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.:		Test atmosphere: dust/mist		
Acute oral toxicity:LD50 Oral (Rat): > 5.000 mg/kgAcute inhalation toxicity:LC50 (Rat): 3.466 mg/l Exposure time: 4 h Test atmosphere: dust/mistAcute dermal toxicity:LD50 Dermal (Rabbit): 6.000 mg/kgSkin corrosion/irritation Causes skin irritation.:	p-tert-butylphenyl 1-(2.3-epoxy	npropyl ether:		
Exposure time: 4 h Test atmosphere: dust/mist Acute dermal toxicity : LD50 Dermal (Rabbit): 6.000 mg/kg Skin corrosion/irritation Causes skin irritation.				
Skin corrosion/irritation Causes skin irritation.	Acute inhalation toxicity :	Exposure time: 4 h		
Causes skin irritation.	Acute dermal toxicity :	LD50 Dermal (Rabbit): 6.000 mg/kg		
	Serious eye damage/eye irritation			

Causes serious eye irritation.

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0



Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,8 mg/l Exposure time: 48 h

bis-[4-(2,3-epoxypropoxy)phenyl]methane:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 2,54 mg/l

Sikafloor®-263 SL N Part A



Revision Date: 07.12.2023 Date of last issue: 21.04.2023		Version 5.0	Print Date 07.12.20
		Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 2,55 mg/l Exposure time: 48 h	
Toxicity to algae/aquatic plants	:	EC50 (algae): 1,8 mg/l Exposure time: 72 h	
benzyl alcohol:			
Toxicity to fish	:	LC50 (Fish): > 100 mg/l Exposure time: 96 h	
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h	
12.2 Persistence and degradabil No data available	lity		
12.3 Bioaccumulative potential No data available			
12.4 Mobility in soil No data available			
12.5 Results of PBT and vPvB as	sse	ssment	
Product:			
Assessment	:	This substance/mixture contains no components to be either persistent, bioaccumulative and toxic very persistent and very bioaccumulative (vPvB) 0.1% or higher	: (PBT), or
12.6 Endocrine disrupting prope	ertie	S	
Product:			
Assessment	:	The substance/mixture does not contain componered to have endocrine disrupting properties accers REACH Article 57(f) or Commission Delegated re (EU) 2017/2100 or Commission Regulation (EU) levels of 0.1% or higher.	ording to egulation
12.7 Other adverse effects			
Product:			
Additional ecological infor- mation	:	An environmental hazard cannot be excluded in unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.	the event of

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0



Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

octamethylcyclotetrasiloxane [D4]:

20-year global warming potential: 2,66 100-year global warming potential: 0,739 500-year global warming potential: 0,211 Atmospheric lifetime: 0,027 yr Radiative efficiency: 0,12 Wm2ppb Further information: Miscellaneous compounds

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	: 08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number		
ADR	:	UN 3082
IMDG	:	UN 3082
ΙΑΤΑ	:	UN 3082
14.2 UN proper shipping name		
ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.



Revision Date: 07.12.2023 Date of last issue: 21.04.2023		Version 5.0	Print Date 07.12.20
	(epoxy res	sin)	
IMDG	: ENVIRON N.O.S. (epoxy res	MENTALLY HAZARDOUS SU	IBSTANCE, LIQUID,
ΙΑΤΑ	: Environme (epoxy res	entally hazardous substance, li sin)	quid, n.o.s.
14.3 Transport hazard class(es)			
	Class	Subsidiary risks	
ADR	: 9		
IMDG	: 9		
ΙΑΤΑ	: 9		
14.4 Packing group			
ADR Packing group Classification Code Hazard Identification Number Labels Tunnel restriction code Remarks	: III : M6 : 90 : 9 : (-) : Transport	in accordance with special pro	vision 375
IMDG Packing group Labels EmS Code Remarks	: III : 9 : F-A, S-F : Transport	in accordance with 2.10.2.7 of	the IMDG-Code
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels Remarks	: 964 : Y964 : III : Miscellane		
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	: 964 : Y964 : III : Miscellane		
14.5 Environmental hazards			
ADR Environmentally hazardous	: yes		
IMDG Marine pollutant	: yes		
IATA (Passenger) Environmentally hazardous	: yes		

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0



IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

International Chemical Weapons Convention (CWC) Not applicable Schedules of Toxic Chemicals and Precursors **REACH Information:** All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration. REACH - Restrictions on the manufacture, placing on Conditions of restriction for the fol-: lowing entries should be considered: the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Number on list 3 REACH - Candidate List of Substances of Very High None of the components are listed : Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation Not applicable (Annex XIV) Regulation (EC) No 1005/2009 on substances that de-Not applicable 2 plete the ozone layer Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable tants (recast) Regulation (EC) No 649/2012 of the European Parlia-Not applicable ÷ ment and the Council concerning the export and import of dangerous chemicals Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. **ENVIRONMENTAL HAZARDS** E2

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

Sikafloor[®]-263 SL N Part A

Revision Date: 07.12.2023 Date of last issue: 21.04.2023 Version 5.0



(VOCV)

Volatile organic compounds (VOC) content: 2,88% w/w no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,88% w/w

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H302:H315:H317:H319:H332:H411:	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. Toxic to aquatic life with long lasting effects.
Full text of other abbreviation	S
Acute Tox.:Aquatic Chronic:Eye Irrit.:Skin Irrit.:Skin Sens.:GR OEL:GR OEL / TWA:ADR:	Acute toxicity Long-term (chronic) aquatic hazard Eye irritation Skin irritation Skin sensitisation Greece. Exposure limit values Long term exposure limit European Agreement concerning the International Carriage of
CAS :: DNEL :: EC50 :: GHS :: IATA :: IMDG :: LD50 ::	Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level Half maximal effective concentration Globally Harmonized System International Air Transport Association International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50 :	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL :	International Convention for the Prevention of Pollution from
OEL :	Ships, 1973 as modified by the Protocol of 1978 Occupational Exposure Limit

Sikafloor®-263 SL N Part A

Print Date 07.12.2023

Revision Date: 07.12.2023
Date of last issue: 21.04.2023

PBT PNEC REACH	:	Persistent, bioaccumulative and toxic Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg-
SVHC vPvB	:	istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency Substances of Very High Concern Very persistent and very bioaccumulative

Version 5.0

Further information

Classification of th	Classification procedure:	
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN