Sikagard®-PoolCoat

Revision Date 17.01.2020 Version 3.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikagard®-PoolCoat

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street 145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No. 1272/2008.

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains 1,2-benzisothiazol-3(2H)-one (BIT), mixture of: 5-chloro-2-methyl-4-

isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no.

220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Contains a biocide in order to protect the product. Active ingredient: 1,2-benzisothiazol-3(2H)-one (BIT), 2634-33-5, mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)), 55965-84-9. Please use treated articles responsibly.

Sikagard®-PoolCoat



Revision Date 17.01.2020 Version 3.0 Print Date 17.01.2020

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) | | | |
|--|--|---|--------------------------|--|--|--|
| 2-(2-butoxyethoxy)ethanol | 112-34-5 203-961-6 01-2119475104-44- XXXX | Eye Irrit. 2; H319 | >= 1 - < 2,5 | | | |
| 1,2-benzisothiazol-3(2H)-one (BIT) | 2634-33-5 220-120-9 01-2120761540-60- XXXX | Acute Tox. 4; H302 Acute Tox. 2; H330 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 | >= 0,0025 - < 0,025 | | | |
| mixture of: 5-chloro-2-methyl-4- isothiazolin-3-one [EC no. 247- 500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239- 6] (3:1) (C(M)IT/MIT (3:1)) | 55965-84-9 911-418-6 01-2120764691-48- XXXX | Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | >= 0,0002 - < 0,0015 | | | |
| REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : | | | | | | |
| Nonylphenol, branched, ethox- ylated (30 EO) | 68412-54-4 Not Assigned | Aquatic Chronic 3; H412 | >= 0,025 - < 0,25 | | | |

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

according to Regulation (EC) No. 1907/2006

Sikagard®-PoolCoat



Revision Date 17.01.2020 Version 3.0 Print Date 17.01.2020

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects **Symptoms**

and symptoms.

Risks No known significant effects or hazards.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : For personal protection see section 8.

6.2 Environmental precautions

Environmental precautions No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Methods for cleaning up

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

Sikagard®-PoolCoat

Revision Date 17.01.2020



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.

No special handling advice required.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated

place. Store in accordance with local regulations.

Advice on common storage : No special restrictions on storage with other products.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any

use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters * | Basis * |
|---------------------------|---------------|---------------------------------|-----------------------|------------|
| 2-(2-butoxyethoxy)ethanol | 112-34-5 | STEL | 15 ppm 101,2 mg/m3 | 2006/15/EC |
| | Further infor | Further information: Indicative | | |
| | | TWA | 10 ppm 67,5 mg/m3 | 2006/15/EC |
| | | TWA | 10 ppm 67,5 mg/m3 | GR OEL |
| | | STEL | 15 ppm 101,2 mg/m3 | GR OEL |

^{*}The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

Sikagard®-PoolCoat

Revision Date 17.01.2020

Version 3.0 Print Date 17.01.2020

facturer specifications.

Butyl rubber/nitrile rubber gloves (0,4 mm)

Recommended: Butyl rubber/nitrile rubber gloves.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor (Type A) and particulate filter

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm P1: Inert material; P2, P3: hazardous substances

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : No special environmental precautions required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : viscous
Colour : various
Odour : very faint

Odour Threshold : No data available

pH : ca. 8,5 (20 °C)

Melting point/range / Freezing :

point

No data available

Boiling point/boiling range : No data available

Flash point : > 101 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

according to Regulation (EC) No. 1907/2006

Sikagard®-PoolCoat

Revision Date 17.01.2020 Version 3.0 Print Date 17.01.2020

Vapour pressure : 23 hPa

Relative vapour density : No data available

Density : ca. 1,3 g/cm3 (20 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20,5 mm2/s (40 °C)

Explosive properties : No data available

Oxidizing properties : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

Sikagard®-PoolCoat

Revision Date 17.01.2020 Version 3.0



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

2-(2-butoxyethoxy)ethanol:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): ca. 2.700 mg/kg

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : LD50 Oral (Rat): 597 mg/kg

Acute inhalation toxicity : LC50: 0,4 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-

one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

Sikagard®-PoolCoat

Revision Date 17.01.2020 Version 3.0 Print Date 17.01.2020

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 3 mg/l

aquatic invertebrates Exposure time: 48 h

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-

one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)):

M-Factor (Acute aquatic tox- : 100

icity)

M-Factor (Chronic aquatic : 100

toxicity)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological infor-

: There is no data available for this product.

mation

SECTION 13: Disposal considerations


13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

according to Regulation (EC) No. 1907/2006

Sikagard®-PoolCoat





Revision Date 17.01.2020

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue

08 01 12 waste paint and varnish other than those mentioned

in 08 01 11

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Nonylphenol, branched, ethoxylated (30 EO) (Number on list 46b, 46a.)

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

Not applicable

Nonylphenol, branched, ethoxylated

(30 EO)

Sikagard®-PoolCoat

Revision Date 17.01.2020 Version 3.0 Print Date 17.01.2020

REACH - List of substances subject to authorisation

(Annex XIV)

: Nonylphenol, branched, ethoxylated

(30 EO)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol- : Not applicable

lutants

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

Not applicable

Not applicable

of dangerous chemicals

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

excluded from the regulation, and/or
exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 2 %

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,59 %

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

| H301 | : Toxic if swall | owed. |
|-------|--------------------|----------|
| H302 | : Harmful if sw | allowed. |
| H310 | 310 : Fatal in con | |
| 11044 | ^ | |

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H330 : Fatal if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.
 H411 : Toxic to aquatic life with long lasting effects.
 H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Sikagard®-PoolCoat



Revision Date 17.01.2020 Version 3.0 Print Date 17.01.2020

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

2006/15/EC : Europe. Indicative occupational exposure limit values

GR OEL

2006/15/EC / TWA

2006/15/EC / STEL

GR OEL / TWA

: Limit Value - eight hours

Short term exposure limit

Long term exposure limit

GR OEL / STEL

: Short term exposure limit

Short term exposure limit

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006

Sikagard®-PoolCoat

Revision Date 17.01.2020 Version 3.0

