

Revision Date: 06.02.2024 Date of last issue: - Version 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikasil[®] SG-550 Part B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Catalyst for 2 Comp. sealants/adhesives.

1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		-

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Acute toxicity, Category 4 Skin irritation, Category 2 Serious eye damage, Category 1 Skin sensitisation, Category 1 Specific target organ toxicity - repeated	 H302: Harmful if swallowed. H315: Causes skin irritation. H318: Causes serious eye damage. H317: May cause an allergic skin reaction. H372: Causes damage to organs through pro-
Specific target organ toxicity - repeated exposure, Category 1	H372: Causes damage to organs through pro- longed or repeated exposure if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:		
Signal word	:	Danger	•
Hazard statements	:	H302 H315 H317 H318 H372	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes damage to organs through prolonged or

Print Date 06.02.2024

Revision Date: 06.02.2024 Date of last issue: - Version 1.0

repeated exposure if inhaled.

Precautionary statements	Prevention: P260 P264 P280	Do not breathe mist or vapours. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.
	Response:	
	P305 + P351 +	P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove con- tact lenses, if present and easy to do. Con- tinue rinsing. Immediately call a POISON CENTER/ doctor.
	P314	Get medical advice/ attention if you feel un- well.
	P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.

Hazardous components which must be listed on the label:

N-[3-(triethoxysilyl)propyl]ethylenediamine 4,4,7,7-tetraethoxy-3,8-dioxa-4,7-disiladecane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

oomponenta			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
tetraethyl silicate	78-10-4	Flam. Liq. 3; H226	>= 10 - < 20
	201-083-8	Acute Tox. 4; H332	
	01-2119496195-28-	Eye Irrit. 2; H319	
	XXXX	STOT SE 3; H335	

Sikasil[®] SG-550 Part B

Revision Date: 06.02.2024

Date of last issue: -



Version 1.0

N-[3- (triethoxysi- lyl)propyl]ethylenediamine Contains: N,N'-bis[3- (triethoxysi- lyl)propyl]ethylenediamine >= 15 - <= 20 % di- aminoethylaminopropyltetraethox- ydisiloxane >= 3 - <= 5 %	5089-72-5 225-806-1 01-2120767929-30- XXXX	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317	>= 10 - < 20
4,4,7,7-tetraethoxy-3,8-dioxa-4,7- disiladecane	16068-37-4 240-212-2 01-2120764364-51- XXXX	Acute Tox. 3; H301 Acute Tox. 4; H312 STOT RE 1; H372 Aquatic Chronic 3; H412 Acute toxicity esti- mate Acute oral toxicity: 161 mg/kg Acute dermal toxicity: 1.971 mg/kg	>= 10 - < 20
bis(ethyl acetoacetato- O1',O3)bis(2-methylpropan-1- olato)titanium Contains: 2-methylpropan-1-ol <= 2 %	83877-91-2 281-161-6 01-2119968551-31- XXXX	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 (Respiratory system) STOT SE 3; H336 (Central nervous system)	>= 5 - < 10
[3-(2,3- epoxypro- poxy)propyl]trimethoxysilane Contains: methanol <= 0,2 %	2530-83-8 219-784-2 01-2119513212-58- XXXX	Eye Dam. 1; H318 Aquatic Chronic 3; H412	>= 3 - < 5
1,2-Bis(triethoxysilyl)ethene	87061-56-1 Not Assigned	Acute Tox. 3; H301 Acute Tox. 4; H312 Aquatic Chronic 3; H412 EUH071 Acute toxicity esti- mate Acute oral toxicity: 161 mg/kg Acute dermal toxicity: 1.971 mg/kg	>= 1 - < 2,5

For explanation of abbreviations see section 16.

Print Date 06.02.2024

Revision Date: 06.02.2024 Date of last issue: - Version 1.0

SECTION 4: First aid measures

4.1 Description of first aid measures					
General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.				
If inhaled	: Move to fresh air. Consult a physician after significant exposure.				
In case of skin contact	 Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician. 				
In case of eye contact	 Small amounts splashed into eyes can cause irreversible tissue damage and blindness. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Continue rinsing eyes during transport to hospital. Remove contact lenses. Keep eye wide open while rinsing. 				
If swallowed	 Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. 				
4.2 Most important symptoms ar	nd effects, both acute and delayed				
Symptoms	 Gastrointestinal discomfort Allergic reactions Excessive lachrymation Erythema Dermatitis See Section 11 for more detailed information on health effects and symptoms. 				
Risks	: irritant effects sensitising effects				
	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Causes damage to organs through prolonged or repeated exposure if inhaled.				
4.3 Indication of any immediate medical attention and special treatment needed					
Treatment	· Treat symptomatically				

Treatment : Treat symptomatically.



Revision Date: 06.02.2024 Date of last issue: - Version 1.0

SECTION 5: Firefighting measures

5.1	Extinguishing media		
	Suitable extinguishing media	:	In case of fire, use water/water spray/water jet/carbon diox- ide/sand/foam/alcohol resistant foam/chemical powder for extinction.
5.2	Special hazards arising from the second s	he	substance or mixture
	Hazardous combustion prod- ucts	:	No hazardous combustion products are known
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
	Further information	:	Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	•	Deny access to unprotected persons.
6.2 Environmental precautions		
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	: Avoid exceeding the given occupational exposes section 8).	sure limits (see
	Do not get in eyes, on skin, or on clothing.	
	For personal protection see section 8.	
	Persons with a history of skin sensitisation pro	oblems or asth-
	ma, allergies, chronic or recurrent respiratory	disease should

Sikasil[®] SG-550 Part B



Revision Date: 06.02.2024 Date of last issue: -		Version 1.0	Print Date 06.02.20
		not be employed in any process in which this m used. Smoking, eating and drinking should be prohibit plication area. Follow standard hygiene measures when handl products	ted in the ap-
Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.	
Hygiene measures	:	Handle in accordance with good industrial hygic practice. When using do not eat or drink. When smoke. Wash hands before breaks and at the e	using do not
7.2 Conditions for safe storage,	inc	luding any incompatibilities	
Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-well-well-well-well-well-well-well	
Further information on stor- age stability	:	No decomposition if stored and applied as direc	ted.
7.3 Specific end use(s)			
Specific use(s)	:	Consult most current local Product Data Sheet use.	prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
tetraethyl silicate	78-10-4	TWA	5 ppm 44 mg/m3	2017/164/EU
	Further informa	ation: Indicative		
		TWA	5 ppm 44 mg/m3	GR OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *	
ethanol	64-17-5	TWA	1.000 ppm 1.900 mg/m3	GR OEL	
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC	
		Further information: Indicative, Identifies the possibility of cant uptake through the skin			
		TWA	200 ppm 260 mg/m3	GR OEL	
		Further information: The notation 'skin' (D), pointing of chemical factors of the table of paragraph of 1 article			



Revision Date: 06.02.2024 Date of last issue: -

	bution to of these c workers which are vith these.		
	STEL	250 ppm 325 mg/m3	GR OEL

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Hand protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Vittee gloves (> 0,4 mm)					
		Viton gloves (0.4 mm), breakthrough time >30 min.					
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.					
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Meth- ods for determining inhalation exposure). This applies in par- ticular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.					
Environmental exposure controls							
General advice		Do not flush into surface water or sanitary sewer system.					

General advice : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Sikasil[®] SG-550 Part B

Print Date 06.02.2024

Revision Date: 06.02.2024 Date of last issue: - Version 1.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

	a chemical properties
÷	solid paste
:	black
:	odourless
:	No data available
:	No data available
:	No data available
exp	losive limits
:	No data available
:	No data available
:	Not applicable
:	No data available
:	No data available
:	ca. 8 - 10 Concentration: 100 %
:	ca. 200.000 mPa.s (20 °C)
:	> 20,5 mm2/s (40 °C)
:	insoluble
:	No data available
:	0,01 hPa
:	ca. 1,08 g/cm3 (20 °C)
:	No data available
	No data available
	exp : : : : : : :

Revision Date: 06.02.2024 Date of last issue: - Version 1.0

9.2 Other information

Flammable solids Burning rate

: > 120 s Method: UN-Test N1

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Hazardous decomposition	:	ethanol, methanol
products		

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Harmful if swallowed. Components: 4,4,7,7-tetraethoxy-3,8-dioxa-4,7-disiladecane: Acute oral toxicity : LD50 Oral (Rat): 161 mg/kg Acute oral toxicity : LD50 Oral (Rat): 161 mg/kg Acute toxicity estimate: 161 mg/kg Method: Calculation method Acute toxicity estimate: 1.971 mg/kg Acute toxicity estimate: 1.971 mg/kg Method: Calculation method

Revision Date: 06.02.2024 Date of last issue: - Version 1.0



[3-(2,3-epoxypropoxy)propy	l]tri	-			
Acute oral toxicity	:	LD50 Oral (Rat): 7.010 mg/kg			
Acute inhalation toxicity	:	LC50 (Rat): > 5,3 mg/l			
		Exposure time: 4 h Test atmosphere: dust/mist			
Acute dermal toxicity		LD50 Dermal (Rabbit): 4.248 mg/kg			
nouto donnar toxiony	•				
1,2-Bis(triethoxysilyl)ethene	:				
Acute oral toxicity	:	LD50 Oral (Rat): 161 mg/kg			
		Acute toxicity estimate: 161 mg/kg Method: Calculation method			
Acute inhalation toxicity	:	Assessment: Corrosive to the respiratory tract.			
Acute dermal toxicity	:	LD50 Dermal (Rat): 1.971 mg/kg			
		Acute toxicity estimate: 1.971 mg/kg Method: Calculation method			
Skin corrosion/irritation					
Causes skin irritation.					
Serious eye damage/eye irri Causes serious eye damage.	tati	on			
Respiratory or skin sensitis	atio	n			
Skin sensitisation					
May cause an allergic skin reaction.					
Respiratory sensitisation					
Not classified due to lack of da	ata.				
Germ cell mutagenicity Not classified due to lack of da	ata.				
Carcinogenicity					
Not classified due to lack of da	ata.				
Reproductive toxicity Not classified due to lack of da	ata				
	ala.				
STOT - single exposure Not classified due to lack of data.					
STOT - repeated exposure					
Causes damage to organs through prolonged or repeated exposure if inhaled.					
Aspiration toxicity					
Not classified due to lack of da	ata.				

Revision Date: 06.02.2024 Date of last issue: - Version 1.0



11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

N-[3-(triethoxysilyl)propyl]ethylenediamine:

Toxicity to fish (Chronic tox-	:	LC50: 597 mg/l
icity)		Exposure time: 96 h
		Species: Danio rerio (zebra fish)

[3-(2,3-epoxypropoxy)propyl]trimethoxysilane:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 55 mg/l Exposure time: 96 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components consid-
	ered to have endocrine disrupting properties according to
	REACH Article 57(f) or Commission Delegated regulation
	(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

Revision Date: 06.02.2024 Date of last issue: - Version 1.0

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-	:	There is no data available for this product.
mation		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	The generation of waste should be avoided or minimiz wherever possible. Empty containers or liners may retain some product re This material and its container must be disposed of in a way. Dispose of surplus and non-recyclable products via a l waste disposal contractor. Disposal of this product, solutions and any by-products at all times comply with the requirements of environme protection and waste disposal legislation and any region local authority requirements. Avoid dispersal of spilled material and runoff and contains soil, waterways, drains and sewers.	sidues. a safe icensed s should ental onal
European Waste Catalogue	08 04 09* waste adhesives and sealants containing or solvents or other dangerous substances	rganic
Contaminated packaging	15 01 10* packaging containing residues of or contami by dangerous substances	nated

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.2 UN proper shipping name		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
ΙΑΤΑ	:	Not regulated as a dangerous good
14.3 Transport hazard class(es)		
ADR	:	Not regulated as a dangerous good



Revision Date: 06.02.2024 Date of last issue: -

IMDG IATA	:	Not regulated as a dangerous good Not regulated as a dangerous good
14.4 Packing group		
ADR	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)		Conditions of restriction for the fol- lowing entries should be considered: Number on list 75, 3
		bis(neodecanoyloxy)dioctylstannane (Number on list 20)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	None of the components are listed (=> 0.1 %).
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable

Sikasil[®] SG-550 Part B



Revision Date: 06.02.2024 Date of last issue: -	Version 1.0		Print Date 06.02.2
Regulation (EU) 2019/1021 on pe tants (recast)	rsistent organic pollu- :	Not applicable	
Regulation (EU) No 649/2012 of the ment and the Council concerning of dangerous chemicals	•	Not applicable	
Seveso III: Directive 2012/18/EU o jor-accident hazards involving dar	•	and of the Council on th	ne control of ma-
Volatile organic compounds :	mpounds : Law on the incentive tax for volatile organic compounds (VOCV) Volatile organic compounds (VOC) content: < 0,01% w/w no VOC duties		
	Directive 2010/75/EU of 24 emissions (integrated pollu Volatile organic compound	ution prevention and con	trol)

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

H226 : Flammable liquid and vapour.	Ill text of H-Statements	ents	
	226	: Flammable liquid and vapour.	
H301 : Toxic if swallowed.	301	· · ·	
H312 : Harmful in contact with skin.	312	: Harmful in contact with skin.	
H315 : Causes skin irritation.	315	: Causes skin irritation.	
H317 : May cause an allergic skin reaction.	317	: May cause an allergic skin reaction	n.
H318 : Causes serious eye damage.	318		
H319 : Causes serious eye irritation.	319	: Causes serious eye irritation.	
H332 : Harmful if inhaled.	332	: Harmful if inhaled.	
H335 : May cause respiratory irritation.	335	: May cause respiratory irritation.	
H336 : May cause drowsiness or dizziness.	336	: May cause drowsiness or dizzines	S.
H372 : Causes damage to organs through prolonged or repeated	372	: Causes damage to organs through	n prolonged or repeated
exposure if inhaled.		exposure if inhaled.	
H412 : Harmful to aquatic life with long lasting effects.	112	: Harmful to aquatic life with long las	sting effects.
Full text of other abbreviations			
Acute Tox. : Acute toxicity	cute Tox.	: Acute toxicity	
Aquatic Chronic : Long-term (chronic) aquatic hazard	quatic Chronic	: Long-term (chronic) aquatic hazar	d
Eye Dam. : Serious eye damage	ve Dam.	: Serious eye damage	
Eye Irrit. : Eye irritation	/e Irrit.	: Eye irritation	
Flam. Liq. : Flammable liquids	am. Liq.	: Flammable liquids	
Skin Irrit. : Skin irritation	kin Irrit.	: Skin irritation	
Skin Sens. : Skin sensitisation	kin Sens.	: Skin sensitisation	
STOT RE : Specific target organ toxicity - repeated exposure	TOT RE	: Specific target organ toxicity - repe	eated exposure
STOT SE : Specific target organ toxicity - single exposure	TOT SE	: Specific target organ toxicity - sing	le exposure

Jika ®
Print Date 06.02.2024

Revision Date: 06.02.2024 Date of last issue: -

2006/15/EC 2017/164/EU	:	Europe. Indicative occupational exposure limit values Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GR OEL 2006/15/EC / TWA 2017/164/EU / TWA GR OEL / TWA GR OEL / STEL ADR	::	Greece. Exposure limit values Limit Value - eight hours Limit Value - eight hours Long term exposure limit Short term exposure limit European Agreement concerning the International Carriage of
CAS DNEL	:	Dangerous Goods by Road Chemical Abstracts Service Derived no-effect level
EC50 GHS	:	Half maximal effective concentration Globally Harmonized System
IATA IMDG	:	International Air Transport Association International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL PBT	:	Occupational Exposure Limit Persistent, bioaccumulative and toxic
PNEC REACH	:	Predicted no effect concentration Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC vPvB	:	Substances of Very High Concern Very persistent and very bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Acute Tox. 4	H302	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
STOT RE 1	H372	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

Sikasil[®] SG-550 Part B

Revision Date: 06.02.2024 Date of last issue: - Version 1.0



GR / EN