

Sika MonoTop[®]-723 Finiro

DECLARATION OF PERFORMANCE No. 38207955

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	38207955
2	INTENDED USE/S:	EN 1504-3:2005 Repair mortar PCC for structural repair of concrete structures in buildings and civil engineering works, Class R3 Principles 3 & 7, Methods 3.1, 3.3, 7.1 & 7.2 according to EN 1504-9:2008
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ plus 3
6a	HARMONISED STANDARD:	EN 1504-3:2005
	Notified body/ies:	1128 0370 (Reaction to fire)

7 DECLARED PERFORMANCE/S


Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compressive Strength	Class R3	System 2+	EN 1504-3:2005
Chloride ion content	≤ 0.05 %	System 2+	
Adhesive Bond	≥ 1.5 MPa	System 2+	
Restrained shrinkage / expansion	≥ 1.5 MPa	System 2+	
Carbonation resistance	Passes	System 2+	
Capillary absorption	≤ 0.5 kg·m ⁻² ·h ^{-0.5}	System 2+	
Dangerous substances	comply with 5.4	System 2+	
Reaction to fire	Class A1	System 2+ plus 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: Target Market Manager
Refurbishment
At Athens on 18 June 2022



Name: Angeliki Zacharopoulou
Function: QEHS Manager

At Athens on 18 June 2022



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sika MonoTop®-723 Finiro	EN 1504-2:2004	37971709

Declaration of Performance

Sika MonoTop®-723 Finiro
38207955
2022.06 , Version 2
1200



19

Sika Hellas ABEE, Athens - Greece

DoP No. 38207955

EN 1504-3:2005

Notified Body 1128, 0370

Concrete repair product for structural repair
PCC mortar, Class R3

Compressive Strength	Class R3
Chloride ion content	≤ 0.05 %
Adhesive Bond	≥ 1.5 MPa
Restrained shrinkage / expansion	≥ 1.5 MPa
Carbonation resistance	Passes
Capillary absorption	≤ 0.5 kg·m ⁻² ·h ^{-0.5}
Dangerous substances	comply with 5.4
Reaction to fire	Class A1

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika MonoTop®-723 Finiro
38207955
2022.06 , Version 2
1200



Sika Hellas ABEE
15 Protomagias Str.
GR 145 68 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance
Sika MonoTop®-723 Finiro
38207955
2022.06 , Version 2
1200