Sikafloor®-3 QuartzTop GR by SIKA Hellas

Health Product Declaration v2.3

created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 1453384704 CLASSIFICATION: 03 35 00 Concrete Finishing

PRODUCT DESCRIPTION: Sikafloor®-3 QuartzTop GR is a one part, preblended, coloured mineral dry shake hardener for concrete comprising of

cement, specially selected quartz mineral aggregates and admixtures.



Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format

C Nested Materials Method

Basic Method

Threshold Disclosed Per

Material

Product

Threshold Level

C 100 ppm

€ 1,000 ppm C Per GHS SDS

Other

Residuals/Impurities Evaluation

Completed

C Partially Completed

Not Completed

Explanation(s) provided:

For all contents above the threshold, the manufacturer has:

Characterized

Yes ○ No

Provided weight and role.

Screened

Yes ○ No

Provided screening results using HPDC-approved

methods.

Identified ○ Yes ⊙ No

Provided name and CAS RN or other identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SIKAFLOOR®-3 QUARTZTOP GR [UNDISCLOSED BM-1 * | CAN | MAM | GEN UNDISCLOSED LT-P1 | CAN | END | MAM]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Materials listed as Undisclosed is done to preserve integrity of formula and maintain competitive advantage

*Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. For this reason, this score is intentionally omitted from the "Contents highest concern" line above. See HPDC's Special Conditions policy for more information.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

Material (g/l): <1 Regulatory (g/l): 50

Does the product contain exempt VOCs: No

Are colorants available that do not increase the VOC content of the base paint when tinted: N/A

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: Emicode EC1 PLUS- very low emission VOC content: SCAQMD Rule 1113 Architectural Coatings - Concrete curing compounds, Industrial Maintenance (IM) Coatings, Zinc-Rich IM Primers, Primers, Sealers, and Undercoaters, including Quick-Dry Primers, Sealers, and Undercoaters and Specialty Primers, Rust Prevent

CONSISTENCY WITH OTHER PROGRAMS

Pre-checked for LEED v4 Option 1. Pre-checked for LEED v4.1 Option 1.

Third Party Verified?

Yes

No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2024-09-25 PUBLISHED DATE: 2024-09-25

EXPIRY DATE: 2027-09-25

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- · Nested Material Inventory method with Product-level threshold
- · Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

SIKAFLOOR®-3 QUARTZTOP GR

PRODUCT THRESHOLD: 1000 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: Residuals and Impurities are determined based on information provided in supplier documentation. All residuals and impurities within the threshold are included

OTHER PRODUCT NOTES:

UNDISCLOSED ID: Undisclosed						
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-09-25 3:50:56			
%: 60.0000 - 80.0000	GreenScreen: BM-1	RC: None	NANO: No	SUBSTANCE ROLE: Filler		
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS			
CAN	US CDC - Occupational Card	US CDC - Occupational Carcinogens		Occupational Carcinogen**		
CAN	CA EPA - Prop 65	CA EPA - Prop 65		Carcinogen - specific to chemical form or exposure route**		
CAN	US NIH - Report on Carcino	US NIH - Report on Carcinogens		Known to be Human Carcinogen (respirable size - occupational setting)**		
CAN	MAK	MAK		Carcinogen Group 1 - Substances that cause cancer in man**		
CAN	IARC	IARC		Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources**		
CAN	IARC	IARC		Group 1 - Agent is Carcinogenic to humans**		
CAN	US NIH - Report on Carcino	US NIH - Report on Carcinogens		Known to be a human Carcinogen**		
CAN	GHS - Japan	GHS - Japan		H350 - May cause cancer [Carcinogenicity - Category 1A]**		
CAN	GHS - Australia	GHS - Australia		H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]**		
CAN	GHS - New Zealand	GHS - New Zealand		Carcinogenicity category 1**		
MAM	GHS - Japan	GHS - Japan		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**		
GEN	GHS - Japan	GHS - Japan		H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]**		
MAM	GHS - Australia	GHS - Australia		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]**		
MAM	GHS - New Zealand	GHS - New Zealand		Specific target organ toxicity - repeated exposure category 1**		

None found No listings found on Additional Hazard Lists

SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards.

**Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.

This substance is part of a powder or aerosol; however, its potential for respiration is limited, as demonstrated by this report or certification

UNDISCLOSED ID: Undisclosed						
HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-09-25 3:50:56			
%: 25.0000 - 35.0000	GreenScreen: LT-P1	RC: PreC	NANO: No	SUBSTANCE ROLE: Binder		
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS			
CAN	MAK	MAK		Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
END	TEDX - Potential Endocrine	TEDX - Potential Endocrine Disruptors		Potential Endocrine Disruptor		
MAM	GHS - Japan	GHS - Japan		H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
МАМ	GHS - Japan	GHS - Japan		H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION			
None found			No	listings found on Additional Hazard Lists		

SUBSTANCE NOTES: The percentage of this substance used is given as a range in order to protect the proprietary nature of this formulation. This substance is shown as undisclosed to preserve integrity of formula and maintain competitive advantage. The component CAS# was used to identify associated hazards.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS

Emicode EC1 PLUS- very low emission

CERTIFYING PARTY: Third Party

APPLICABLE FACILITIES: Sika Hellas at Kryoneri, Athens,

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES:

ISSUE DATE: 2022-12-21 00:00:00

ISSUE DATE: 2022-12-22 00:00:00

CERTIFIER OR LAB: Eurofins

CERTIFIER OR LAB: Eurofins

EXPIRY DATE:

EXPIRY DATE:

VOC CONTENT

SCAQMD Rule 1113 Architectural Coatings - Concrete curing compounds, Industrial Maintenance (IM) Coatings, Zinc-Rich IM Primers, Primers, Sealers, and Undercoaters, including Quick-Dry Primers, Sealers, and Undercoaters and Specialty Primers, Rust Prevent

CERTIFYING PARTY: Third Party

APPLICABLE FACILITIES: Sika Hellas at Kryoneri, Athens,

Greece

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: Product type declared by SCAQMD 1113 is Concrete Surface Retarder

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

Sikafloor®-3 QuartzTop GR may only be used by experienced professionals.

- Sikafloor®-3 QuartzTop GR provides a hard wearing, mineral dry shake topping for monolithic floors. When sprinkled and trowelled onto fresh wet concrete floors, it forms a wear resistant smooth surface.
- Typical uses are in warehouses, factories, shopping malls, where wear durable and wear resistant floor is the key requirement.

CHARACTERISTICS / ADVANTAGES

- Medium wear resistance rating
- Impact resistance
- Dust proof
- Cost effective surface hardener
- Fast application
- Increased resistance to oils and grease
- Quality assured factory blending
- Easy cleaning
- Wide range of colours

APPROVALS / CERTIFICATES

CE Marking and Declaration of Performance to EN 13813 - Screed material and floor screeds. Class CT-C70-F7-AR1

MANUFACTURER INFORMATION

MANUFACTURER: SIKA Hellas ADDRESS: Protomagias 15

Athens, Attica 14568
COUNTRY: Greece

WEBSITE: http://grc.sika.com/

CONTACT NAME: Aggeliki Zacharopoulou

TITLE: EHS-QA-Manager PHONE: 2111080246

EMAIL: zacharopoulou.aggeliki@gr.sika.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity

END Endocrine activity

EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

LAN Land toxicity

MAM Mammalian/systemic/organ toxicity

MUL Multiple

NEU Neurotoxicity

NF Not found on Priority Hazard Lists

OZO Ozone depletion

PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or reactive)

REP Reproductive

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (due to insufficient data)

LT-P1 List Translator Possible 1 (Possible Benchmark-1)

LT-1 List Translator 1 (Likely Benchmark-1)

LT-UNK List Translator Benchmark Unknown

NoGS No GreenScreen.

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content

PostC Post-consumer recycled content

UNK Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material

Nested Method / Product Threshold Substances listed within each material per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and