

# SikaMur<sup>®</sup>-200 M15

## DECLARATION OF PERFORMANCE N. 57386054

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:</b>	57386054
2	<b>INTENDED USE/S:</b>	EN 998-1:2016 General purpose rendering / plastering mortar for external and internal use (GP)
3	<b>MANUFACTURER:</b>	Sika Italia SpA Via L. Einaudi, 6 20668 Peschiera Borromeo (MI)
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 4
6a	<b>HARMONISED STANDARD:</b>	EN 998-1:2016
	Notified body/ies:	-

---

**7 DECLARED PERFORMANCE/S**

---

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	Class A1	EN 998-1:2016
Water absorption	W1	
Water vapour permeability	$\mu \leq 20$	
Adhesion	> 0,8 MPa    FP: B	
Thermal conductivity	1,00 W/mK ( $\lambda_{10, dry}$ value tab., P=50%)	
Durability	NPD	
Dangerous substances	NPD	

---

NPD - No performance determined

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

---

Name: Nikos Anagnostopoulos  
Function: Target Market Manager  
Refurbishment  
At Athens on 08 March 2024

---

Name: Angeliki Zacharopoulou  
Function: QEHS Manager  
At Athens on 08 March 2024

.....  


.....  


---


End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

SikaMur®-200 M15  
57386054  
2024.03 , ver. 3  
1167

## RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
SikaMur®-200 M15	EN 998-2:2016	54851380

 17	
DoP No. 57386054	
Sika Italia SpA, 20068 Peschiera Borromeo (MI)	
EN 998-1:2016	
General purpose rendering / plastering mortar for external and internal use (GP)	
Reaction to fire	Class A1
Water absorption	W1
Water vapour permeability	$\mu \leq 20$
Adhesion	> 0,8 MPa    FP: B
Thermal conductivity	1,00 W/mK ( $\lambda_{10, dry}$ value tab., P=50%)
<a href="http://dop.sika.com">http://dop.sika.com</a>	

### ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

### LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

#### Declaration of Performance

SikaMur®-200 M15  
57386054  
2024.03 , ver. 3  
1167



**Sika Italia SpA**  
Via Luigi Einaudi, 6  
20068 Peschiera Borromeo  
(MI)  
ITALIA  
<http://ita.sika.com/>

**Declaration of Performance**  
SikaMur®-200 M15  
57386054  
2024.03 , ver. 3  
1167