

Sikafloor®-2650

DECLARATION OF PERFORMANCE No 13331016

1	Unique identification code of the product-type:	13331016
2	Intended use/es:	For uses in buildings and civil engineering works: moisture control (2.2), increasing resistivity (8.2) — Surface protection products — coating For uses in buildings and civil engineering works: physical resistance (5.1) — Surface protection products — coating For uses in buildings and civil engineering works: ingress protection (1.3) — Surface protection products — coating For uses in buildings and civil engineering works: chemical resistance (6.1) — Surface protection products — coating For uses subject to reaction to fire regulations — Surface protection products — coating
3	Manufacturer:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	System/s of AVCP:	System 2+ (For uses in buildings and civil engineering works: moisture control (2.2), increasing resistivity (8.2)) System 2+ (For uses in buildings and civil engineering works: physical resistance (5.1)) System 2+ (For uses in buildings and civil engineering works: ingress protection (1.3)) System 2+ (For uses in buildings and civil engineering works: chemical resistance (6.1)) System 3 (For uses subject to reaction to fire regulations)
6a	Harmonised standard:	EN 1504-2:2004 Products and systems for the protection and repair of concrete structures — Definitions, requirements, quality control and evaluation of conformity — Part 2: Surface protection systems for concrete
	Notified body/ies:	0921, 1611

Declaration of performance

Sikafloor®-2650

13331016

18/05/2022 1.0

1008

1 / 3

7 Declared performance/s:

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Linear shrinkage	NPD	System 2+	EN 1504-2:2004
Compressive strength	NPD	System 2+	
Coefficient of thermal expansion	NPD	System 2+	
Abrasion resistance	< 3000 mg (H22 / 1000 cycles / 1000 g)	System 2+	
Cross cut	NPD	System 2+	
Permeability to CO2	$s_D > 50$ m	System 2+	
Water vapour permeability	Class III: $S_D > 50$ m	System 2+	
Capillary absorption and permeability to water	$w < 0.1 \text{ kg}\cdot\text{m}^{-2}\cdot\text{h}^{-0.5}$	System 2+	
Thermal compatibility	NPD	System 2+	
Resistance to thermal shock	NPD	System 2+	
Chemical resistance	NPD	System 2+	
Resistance to severe chemical attack	NPD	System 2+	
Crack bridging ability	NPD	System 2+	
Impact resistance	Class I: ≥ 4 Nm	System 2+	
Adhesion strength by pull off test	≥ 2.5 (2.0) N/mm ²	System 2+	
Reaction to fire	Class B _{fl} -s1	System 3	
Skid resistance	NPD	System 2+	
Artificial weathering	NPD	System 2+	
Antistatic behaviour	NPD	System 2+	
Adhesion on wet concrete	NPD	System 2+	
Dangerous substances	NPD	System 2+	

The product is tested as a part of a system build-up.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomek Gutowski

Function: Corporate Standardisation and Approvals

At Warsaw on 2022/05/18



Name: Maciej Michalewski

Function: Standardisation and Approvals

At Warsaw on 2022/05/18



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of performance

Sikafloor®-2650

13331016

18/05/2022 1.0

1008

2 / 3

BUILDING TRUST



CE

22

Sika Services AG, Zürich, Switzerland

13331016

Abrasion resistance	< 3000 mg (H22 / 1000 cycles / 1000 g)
Permeability to CO2	$s_D > 50$ m
Water vapour permeability	Class III: $S_D > 50$ m
Capillary absorption and permeability to water	$w < 0.1 \text{ kg}\cdot\text{m}^{-2}\cdot\text{h}^{-0.5}$
Impact resistance	Class I: ≥ 4 Nm
Adhesion strength by pull off test	≥ 2.5 (2.0) N/mm ²
Reaction to fire	Class B _{fi} -s1

EN 1504-2:2004

0921, 1611

For uses in buildings and civil engineering works: moisture control (2.2), increasing resistivity (8.2) — Surface protection products — coating

For uses in buildings and civil engineering works: physical resistance (5.1) — Surface protection products — coating

For uses in buildings and civil engineering works: ingress protection (1.3) — Surface protection products — coating

For uses in buildings and civil engineering works: chemical resistance (6.1) — Surface protection products — coating

For uses subject to reaction to fire regulations — Surface protection products — coating

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of performance

Sikafloor®-2650

13331016

18/05/2022 1.0

1008

3 / 3

BUILDING TRUST

