

Sika® Elastic Roof

DECLARATION OF PERFORMANCE

No. 12069458

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	EN 1504-2:2004 Surface protection product – Coating Principle 1 (Protection against ingress) – Method 1.3 Principle 2 (Moisture control) – Method 2.3 and Principle 8 (Increasing resistivity) – Method 8.3 according to EN 1504-9:2008	
2	INTENDED USE/S		
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr	
4	AUTHORISED REPRESENTATIVE:		
5	SYSTEM/S OF AVCP:	System 2+ System 3 (for reaction to fire)	
6a	HARMONISED STANDARD:	EN 1504-2:2004	
	Notified body/ies:	1128	

Sika® Elastic Roof 12069458 2021.10, Revision 1

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performanc	AVCP	Harmonised Technical Specification
Permeability to CO ₂	S _D > 50 m	System 2+	
Permeability to water vapour	Class I, S _D < 5 m	System 2+	
Capillary absorption and permeability to water	$w < 0.1 \text{ kg/m}^2 \cdot h^{0.5}$	System 2+	EN 1504-2:2004
Adhesion strength by pull off test	≥ 1.0 MPa	System 2+	
Dangerous substances	comply with 5.3	System 2+	
Reaction to fire	Class B-s1,d0	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Angeliki Zacharopoulou Function: QEHS Manager At Athens on 22 October 2021 Name: Stamatis Antonakos Function: Target Market Manager Waterproofing/Roofing

At Athens on 22 October 2021

End of information as required by Regulation (EU) No 305/2011





2

Sika Hellas	ARFF	Athons	- Graaca
SIKA HEIIAS	S ADEE.	Autens	- Greece

DoP No. 12069458

EN 1504-2:2004

Notified Body 1128

Surface protection product – coating: Protection against ingress (1.3), Moisture control (2.3), Increasing resistivity (8.3)

Permeability to CO ₂	S _D > 50 m
Permeability to water vapour	Class I, S _D < 5 m
Capillary absorption and permeability to water	w < 0.1 kg/m ² ·h ^{0.5}
Adhesion strength by pull off test	≥ 1.0 MPa
Dangerous substances	comply with 5.3
Reaction to fire	Class B-s1,d0

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.





Sika Hellas ABEE

15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

Sika® Elastic Roof 12069458 2021.10 , Revision 1

