



Sikafloor[®] Marine Litosilo FC

FAST CURING HIGH STRENGTH COMPOUND

- Fast curing
- Non-combustible
- Magnesium-chloride-free

BUILDING TRUST



Sikafloor® Marine Litosilo FC

Sikafloor® Marine Litosilo FC is a one-component non-combustible levelling mortar based on polymer modified cement. The product is applied on interior decks, as part of a sound reducing floating floor prior to the application of deck finishing materials such as carpets, tiles, parquet, rubber and vinyl. Furthermore, Sikafloor® Marine Litosilo FC can be used as a primary deck covering.

For specific applications consult the product data sheet or Sika technical service.

PRODUCT BENEFITS

- Fast curing
- High compressive strength
- Non-combustible
- Part of A60 rated floating floor
- Great pumpability
- 1-Component mortar
- Ideal for heavy duty areas
- Ideal for refits

Technical Properties

Chemical base	1-Component polymer
Density	1.3 kg/m ² /mm
Applied thickness	
– Deck covering	Minimum 6 mm
– Floating floor	Minimum 25 mm
Ready to walk on	Approx. 2 hr.
Compressive strength	> 30 MPa
Flexural strength	4.5 MPa
E-Modules	13 GPa

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.



SIKA SERVICES AG
Tueffenwies 16
8048 Zurich
Switzerland

Contact
Phone: +41 58 436 40 40
Fax: +41 58 436 55 30
www.sika.com/marine

BUILDING TRUST

