
SikaMur[®]-1000 SP

DECLARATION OF PERFORMANCE

No. 81579490

1	UNIQUE IDENTIFICATION CODE OF PRODUCT-TYPE:	81579490
2	INTENDED USE/S	EN 998-1:2010 Factory made rendering and plastering renovation mortar (R) intended for use in walls, ceilings, columns and partitions
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8048 Zürich www.sika.com
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 998-1:2010
	Notified body/ies:	Not necessary under AVCP system 4

Declaration of Performance

SikaMur[®]-1000 SP
81579490
2017.05, Revision 6
1026

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Euroclass A1	EN 998-1:2010
Compressive strength	CS II	
Water absorption	≥ 0.3 kg/m ²	
Water vapor permeability coefficient	μ ≤ 15	
Adhesion	≥ 1.1 MPa - FP: B	
Thermal conductivity (λ _{10, dry})	0,27 W/mK	
Durability (against freeze-thaw)	Pass	
Dangerous substances	NPD	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: TMM Refurbishment
At Athens on 12 May 2020

Name: Alexandros Melissourgos
Function: Technical Manager
At Athens on 12 May 2020



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaMur®-1000 SP
81579490
2017.05, Revision 6
1026





13

Sika Services AG, Zurich, Switzerland

DoP No. 81579490

EN 998-1:2010

Notified body 1026

Factory made rendering and plastering renovation mortar (R) intended for use in walls, ceilings, columns and partitions

Reaction to fire	Euroclass A1
Compressive strength	CS II
Water absorption	$\geq 0.3 \text{ kg/m}^2$
Water vapor permeability coefficient	$\mu \leq 15$
Adhesion	$\geq 1.1 \text{ MPa}$ - FP: B
Thermal conductivity ($\lambda_{10, dry}$)	0,27 W/mK
Durability (against freeze-thaw)	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaMur®-1000 SP
81579490
2017.05, Revision 6
1026

3/4

BUILDING TRUST





Sika Hellas ABEE
Protomagias 15
14568, Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
SikaMur®-1000 SP
81579490
2017.05, Revision 6
1026