

Sikafloor®-2100

DECLARATION OF PERFORMANCE

No. 75917624

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	75917624
2	INTENDED USE/S	EN 1504-2:2004 Surface protection products – coating: physical resistance (5.1)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ System 3
6a	HARMONISED STANDARD:	EN 1504-2:2004
	Notified body/ies:	0099

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Linear shrinkage	NPD	System 2+	_
Compressive strength	NPD	System 2+	_
Coefficient of thermal expansion	NPD	System 2+	_
Abrasion resistance	< 3000 mg	System 2+	_
Cross cut	NPD	System 2+	_
Capillary absorption and permeability to water	$w < 0.1 \text{ kg/(m}^2 \times h^{0.5})$	System 2+	_
Thermal compatibility	≥ 1.5 N/mm²	System 2+	_
Resistance to thermal shock	NPD	System 2+	 EN 1504-
Crack bridging ability	NPD	System 2+	2:2004
Impact resistance	ClassIII	System 2+	_
Adhesion strength by pull off test	≥ 1.5 N/mm²	System 2+	_
Reaction to fire	BflS1	System 3	_
Skid resistance	NPD	System 2+	_
Artificial weathering	NPD	System 2+	_
Antistaticbehavior	NPD	System 2+	_
Adhesion on wet concrete	NPD	System 2+	_
Dangerous substances	NPD	System 2+	_

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis Function: TMM Flooring At Athens on 04 March 2020 Name: Alexandros Melissourgos Function: Technical Manager At Athens on 04 March 2020

............

End of information as required by Regulation (EU) No 305/2011



RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sikafloor®-2100	EN 13813:2002	32897084

 ϵ

16

Sika Services AG, Zurich, Switzerland

DoP No. 75917624

EN 1504-2:2004

Notified Body 0099

Surface protection products - coating: physical resistance (5.1)

Abrasion resistance < 3000 mg

Capillary absorption and permea bility to water $w < 0.1 \text{ kg/(m}^2 \text{ x h}^{0.5})$

Thermal compatibility $\geq 1.5 \text{ N/mm}^2$ Impact resistance Class III Adhesion strength by pull off test $\geq 1.5 \text{ N/mm}^2$

Reaction to fire BflS1

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikafloor®-2100 75917624 2018.05, ver. 1 1053







Sika Hellas ABEE

Protomagias 15 14568 Kryoneri Attica - Greece www.sika.gr

Declaration of Performance

Sikafloor®-2100 75917624 2018.05, ver. 1 1053

