Version 5.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### **1.1 Product identifier**

Trade name

: Sikaflex®-11FC+

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Sealant/adhesive

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		

### 1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	(!)	
Signal word	:	Warning	
Hazard statements	:	H317	May cause an allergic skin reaction.
Precautionary statements	:	P101	If medical advice is needed, have product container or label at hand.
		P102	Keep out of reach of children.
		Prevention:	
		P261	Avoid breathing dust/ fume/ gas/ mist/ va- pours/ spray.
		P280	Wear protective gloves.

### Sikaflex<sup>®</sup>-11FC+

Print Date 18.02.2021

Revision Date: 18.02.2021 Date of last issue: 21.01.2019 Version 5.0

	<b>Response:</b> P302 + P352	IF ON SKIN: Wash with plenty of water.		
	<b>Disposal:</b> P501	Dispose of contents/container in accordance with local regulation.		
Hazardous components which must be listed on the label:				

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane Pentamethyl piperidylsebacate

Hardener LI (İsophoronedialdimine) 4,4'-methylenediphenyl diisocyanate 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate m-tolylidene diisocyanate

### Additional Labelling

EUH204 Contains isocyanates. May produce an allergic reaction.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

### Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
	Registration number		
Urea,N,N''-(methylenedi-4,1- phenylene)bis[N'-butyl-	77703-56-1 416-600-4 01-0000016345-72- XXXX	Aquatic Chronic 4; H413	>= 2,5 - < 5
Reaction product of Hexameth- ylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	192526-20-8 924-669-1 01-2120768758-32- XXXX	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 0,1 - < 0,25

# Sikaflex<sup>®</sup>-11FC+

Print Date 18.02.2021

Revision Date: 18.02.2021 Date of last issue: 21.01.2019

Pentamethyl piperidylsebacate Contains: bis(1,2,2,6,6-pentamethyl-4- piperidyl) sebacate methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40- XXXX	Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,25
Hardener LI (Isophoronedial- dimine) 4,4'-methylenediphenyl diisocya- nate	932742-30-8 700-071-4 01-2119880654-28- XXXX, 01- 2119442290-50- XXXX 101-68-8 202-966-0 01-2119457014-47- XXXX	Skin Sens. 1B; H317 Aquatic Chronic 3; H412 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H317 Carc. 2; H351 STOT RE 2; H373 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %	>= 0,025 - < 0,25 < 0,1

### Sikaflex<sup>®</sup>-11FC+

Revision Date: 18.02.2021 Date of last issue: 21.01.2019 Version 5.0



3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 01-2119490408-31- XXXX	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 %	>= 0,025 - < 0,25
m-tolylidene diisocyanate	26471-62-5 247-722-4 01-2119454791-34- XXXX	Carc. 2; H351 Acute Tox. 1; H330 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H317 Aquatic Chronic 3; H412 specific concentration limit Resp. Sens. 1; H334 >= 0,1 %	>= 0,025 - < 0,1

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures General advice Move out of dangerous area. : Consult a physician. Show this safety data sheet to the doctor in attendance. If inhaled ÷ Move to fresh air. Consult a physician after significant exposure. In case of skin contact Take off contaminated clothing and shoes immediately. ÷ Wash off with soap and plenty of water. If symptoms persist, call a physician. In case of eye contact : Remove contact lenses. Keep eye wide open while rinsing.



Revision Date: 18.02.2021 Date of last issue: 21.01.2019		Version 5.0	Print Date 18.02.20
		If eye irritation persists, consult a specialist.	
If swallowed	:	Do not induce vomiting without medical advid Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconsc	
4.2 Most important symptoms ar	nd	effects, both acute and delayed	
Symptoms	:	Allergic reactions See Section 11 for more detailed information and symptoms.	on health effects
Risks	:	sensitising effects	
		May cause an allergic skin reaction.	
4.3 Indication of any immediate	me	dical attention and special treatment neede	d
Treatment	:	Treat symptomatically.	-
Suitable extinguishing media	:	In case of fire, use water/water spray/water ji ide/sand/foam/alcohol resistant foam/chemic extinction.	
5.2 Special hazards arising from	th	e substance or mixture	
Hazardous combustion prod- ucts	:	No hazardous combustion products are know	vn
5.3 Advice for firefighters			
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breat	thing apparatus.
Further information	:	Standard procedure for chemical fires.	
SECTION 6: Accidental releas	se	measures	
6.1 Personal precautions, protect	tiv	e equipment and emergency procedures	
Personal precautions	:	Use personal protective equipment. Deny access to unprotected persons.	
6.2 Environmental precautions			
Environmental precautions		Do not flush into surface water or sanitary se	wersystem



Revision Date: 18.02.2021 Date of last issue: 21.01.2019 Version 5.0

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up

: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

	Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
	Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
	Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, i	incl	uding any incompatibilities
	Requirements for storage areas and containers	:	Keep container tightly closed in a dry and well-ventilated place. Store in accordance with local regulations.
	Further information on stor- age stability	:	No decomposition if stored and applied as directed.

7.3 Specific end use(s)

### **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0,02 ppm 0,2 mg/m3	GR OEL
		STEL	0,02 ppm	GR OEL

### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikaflex®-11FC+



Revision Date: 18.02.2021 Date of last issue: 21.01.2019

3-isocyanatomethyl-3,5,5- trimethylcyclohexyl isocyanate	4098-71-9	TWA	0,2 mg/m3 0,01 ppm 0,09 mg/m3	GR OEL
	chemical fact the likely con	nation: The notatic ors of the table of tribution to of these o workers which a t with these.	n 'skin' (D), pointin paragraph of 1 arti e chemical factors	cle 3, implies to the quantity
		STEL	0,02 ppm 0,18 mg/m3	GR OEL
m-tolylidene diisocyanate	26471-62-5	TWA	0,01 ppm 0,07 mg/m3	GR OEL
		STEL	0,02 ppm 0,14 mg/m3	GR OEL

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction product of Hexamethylene diisocy- anate, oligomers with Mercaptopropyltri- methoxysilane	Workers	Inhalation	Long-term systemic effects	1,7 mg/m3
	Workers	Dermal	Long-term systemic effects	4,7 mg/kg
	Consumers	Inhalation	Long-term systemic effects	0,3 mg/m3
	Consumers	Dermal	Long-term systemic effects	1,7 mg/kg

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction product of Hexamethylene	Fresh water	0,1 mg/l
diisocyanate, oligomers with Mercap-		-
topropyltrimethoxysilane		
	Intermittent use/release	1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	23,28 mg/kg
	Marine sediment	2,33 mg/kg
	Sewage treatment plant	100 mg/l
	Soil	4,58 mg/kg

#### 8.2 Exposure controls

### Personal protective equipment

Eye protection	:	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water
Hand protection	: Chemical proved st chemical	Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
		Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm)



Revision Date: 18.02.2021 Date of last issue: 21.01.2019	Version 5.0	Print Date 18.02.20
	Contaminated gloves should be remov	ved.
	Suitable for permanent exposure:	
	Viton gloves (0.4 mm),	
	breakthrough time >30 min.	
Skin and body protection	: Protective clothing (e.g. Safety shoes a long-sleeved working clothing, long tro and protective boots are additionaly re and stirring work.	users). Rubber aprons
Respiratory protection	<ul> <li>In case of inadequate ventilation wear Respirator selection must be based on exposure levels, the hazards of the pro- ing limits of the selected respirator. organic vapor filter (Type A)</li> </ul>	h known or anticipated oduct and the safe work-
	A1: < 1000 ppm; A2: < 5000 ppm; A3:	< 10000 ppm

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

#### **Environmental exposure controls**

General advice	: Do not flush into surface water or sanitary sewer system.
----------------	---

### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state Appearance Colour Odour Odour Threshold	:	liquid paste various odourless No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/range / Freezing	:	No data available
point Boiling point/boiling range	:	No data available
Flash point	:	> 150 °C Method: closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available

### SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 Sikaflex®-11FC+

### Revision Date: 18.02.2021 Date of last issue: 21.01.2019



Vapour pressure	:	0,01 hPa
Relative vapour density	:	No data available
Density	:	ca. 1,36 g/cm3 (20 °C)
Solubility(ies) Water solubility Solubility in other solvents	:	insoluble No data available
Partition coefficient: n-	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Explosive properties	:	No data available
Oxidizing properties	:	No data available
0th an in fammatian		

Version 5.0

### 9.2 Other information

No data available

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

### 10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

### 10.5 Incompatible materials

Materials to avoid : No data available

### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.



Revision Date: 18.02.2021 Date of last issue: 21.01.2019 Version 5.0

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Not classified based on available information.

### **Components:**

Urea,N,N"-(methylenedi-4,1	-ph	enylene)bis[N'-butyl-:
Acute oral toxicity		LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 401
Reaction product of Hexam ysilane:	eth	ylene diisocyanate, oligomers with Mercaptopropyltrimethox-
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg Method: OECD Test Guideline 423
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2.000 mg/kg Method: OECD Test Guideline 402
Pentamethyl piperidylsebad	cate	::
Acute oral toxicity	:	LD50 Oral (Rat): 3.230 mg/kg
Hardener LI (Isophoronedia		•
Acute oral toxicity		LD50 Oral (Rat): > 2.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 2.000 mg/kg
4,4'-methylenediphenyl diis	ocy	vanate:
Acute oral toxicity		LD50 Oral (Rat): > 4.700 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement
3-isocyanatomethyl-3,5,5-tr	ime	thvlcvclohexvl isocvanate:
Acute oral toxicity		LD50 Oral (Rat): 4.814 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0,031 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rat): > 7.000 mg/kg
m tolylidono diisooyanato:		



Revision Date: 18.02.2021 Date of last issue: 21.01.2019 Version 5.0

Acute inhalation toxicity : LC50 (Rat): 0,107 mg/l Exposure time: 4 h Test atmosphere: vapour

### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitisation

### Skin sensitisation

May cause an allergic skin reaction.

### **Respiratory sensitisation**

Not classified based on available information.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Aspiration toxicity

Not classified based on available information.

2

### 11.2 Information on other hazards

### **Endocrine disrupting properties**

### Product:

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Revision Date: 18.02.2021 Date of last issue: 21.01.2019 Print Date 18.02.2021

### Version 5.0

### **SECTION 12: Ecological information**

### 12.1 Toxicity

<u>Components:</u>		
Urea,N,N"-(methylenedi-4,1-p Toxicity to fish	one :	LC50 (Brachydanio rerio (zebrafish)): > 250 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Raphidocelis subcapitata (freshwater green alga)): > 100 mg/l Exposure time: 72 h
Reaction product of Hexamery ysilane:	thy	ylene diisocyanate, oligomers with Mercaptopropyltrimethox-
Toxicity to fish	:	LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Pentamethyl piperidylsebaca	ate	:
Toxicity to fish	:	LC50 (Fish): 0,97 mg/l Exposure time: 96 h
M-Factor (Acute aquatic tox- icity)	:	1
M-Factor (Chronic aquatic toxicity)	:	1
Hardener LI (Isophoronedial	diı	nine):
Toxicity to fish	:	LC50 (Fish): 87,2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): > 100 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): 180,4 mg/l Exposure time: 72 h

Revision Date: 18.02.2021 Date of last issue: 21.01.2019 Version 5.0



### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

### Product:

Assessment	<ul> <li>The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.</li> </ul>

### 12.7 Other adverse effects

#### Product:

Additional ecological infor- mation	: There is no data available for this product.
mation	

### **SECTION 13: Disposal considerations**

### **13.1 Waste treatment methods**

Product	<ul> <li>The generation of waste should be avoided or minimized wherever possible.</li> <li>Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.</li> <li>Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.</li> <li>Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.</li> <li>Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.</li> </ul>	
European Waste Catalogue	: 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances	

### Sikaflex<sup>®</sup>-11FC+



Revision Date: 18.02.2021	Version 5.0	Print Date 18.0
Date of last issue: 21.01.2019		

Contaminated packaging

: 15 01 10\* packaging containing residues of or contaminated by dangerous substances

### **SECTION 14: Transport information**

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the folthe market and use of certain dangerous substances, lowing entries should be considered: preparations and articles (Annex XVII) Number on list 3 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (Number on list 52) International Chemical Weapons Convention (CWC) Not applicable 5 Schedules of Toxic Chemicals and Precursors REACH - Candidate List of Substances of Very High None of the components are listed 5 Concern for Authorisation (Article 59). (=> 0.1 %). REACH - List of substances subject to authorisation Not applicable 2 (Annex XIV) Regulation (EC) No 1005/2009 on substances that de-2 Not applicable plete the ozone layer Regulation (EU) 2019/1021 on persistent organic pollu-Not applicable Ξ. tants (recast) Regulation (EC) No 649/2012 of the European Parlia-: Not applicable ment and the Council concerning the export and import

# Sikaflex<sup>®</sup>-11FC+

Print Date 18.02.2021

Revision Date: 18.02.2021 Date of last issue: 21.01.2019	Version 5.0	Print Date 18.02.202
of dangerous chemicals REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or - registered by us, and/or - excluded from the regulation, and/or - exempted from the registration.	
Seveso III: Directive 2012/18/EU jor-accident hazards involving da	of the European Parliament and of the Council o ngerous substances. Not applicable	n the control of ma-
Volatile organic compounds :	Law on the incentive tax for volatile organic cor (VOCV) no VOC duties	npounds
	Directive 2010/75/EU of 24 November 2010 on emissions (integrated pollution prevention and Not applicable	

### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

### **SECTION 16: Other information**

	Full text of H-Statements				
	H315	:	Causes skin irritation.		
	H317	:	May cause an allergic skin reaction.		
	H319	:	Causes serious eye irritation.		
	H330	:	Fatal if inhaled.		
	H332	:	Harmful if inhaled.		
	H334	:	May cause allergy or asthma symptoms or breathing difficul- ties if inhaled.		
	H335	:	May cause respiratory irritation.		
	H351	:	Suspected of causing cancer.		
	H373	:	May cause damage to organs through prolonged or repeated exposure.		
	H400	:	Very toxic to aquatic life.		
	H410	:	Very toxic to aquatic life with long lasting effects.		
	H411	:	Toxic to aquatic life with long lasting effects.		
	H412	:	Harmful to aquatic life with long lasting effects.		
	H413	:	May cause long lasting harmful effects to aquatic life.		
Full text of other abbreviations					
	Acute Tox.	:	Acute toxicity		
	Aquatic Acute	:	Short-term (acute) aquatic hazard		
	Aquatic Chronic	:	Long-term (chronic) aquatic hazard		
	Carc.	:	Carcinogenicity		
	Eye Irrit.	:	Eye irritation		
	Resp. Sens.	:	Respiratory sensitisation		
	Skin Irrit.	:	Skin irritation		

### Full text of H-Statements

### Sikaflex<sup>®</sup>-11FC+

Revision Date: 18.02.2021 Date of last issue: 21.01.2019



Version 5.0

Skin Sens. STOT RE STOT SE GR OEL GR OEL / TWA GR OEL / STEL		Skin sensitisation Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure Greece. Exposure limit values Long term exposure limit
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Reg- istration, Evaluation, Authorisation and Restriction of Chemi- cals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative
Further information		

Classification of the mixtur	Classification procedure:	
Skin Sens. 1	H317	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN