Jika®

Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

: Sikafloor®-14 Pronto

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use

: Acrylate coating, Product is not intended for consumer use

1.3 Details of the supplier of the safety data sheet

Company name of supplier	: Sika Hellas ABEE
	15 Protomagias Street
	145 68 Kryoneri / Athens
Telephone	: +30 210 81 60 600
Telefax	: +30 210 81 60 606
E-mail address of person responsible for the SDS	: EHS@gr.sika.com

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777 Poison Information Center: 1401 (Cyprus)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single ex-	H335: May cause respiratory irritation.
posure, Category 3, Respiratory system	

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	grams :			
Signal word	:	Danger	•	
Hazard statements	:	H225 H315 H317 H335	Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.	

Sikafloor[®]-14 Pronto

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Jika

Revision Date: 13.02.2025 Date of last issue: 12.01.2023	Version 2.0		Print Date 13.02.2025
Precautionary statements :	Prevention:		
	P210	Keep away from heat, hot surfa open flames and other ignition s smoking.	
	P233	Keep container tightly closed.	
	P261	Avoid breathing mist or vapours	6.
	P264	Wash skin thoroughly after han	dling.
	P280	Wear protective gloves/ protection/ face protection.	ive clothing/
	Response:		
	P370 + P378	In case of fire: Use dry sand, dr	y chemical or

alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

methyl methacrylate tetramethylene dimethacrylate aromatic amine ethoxylated 2-(N-methyl-p-toluidino)ethanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
methyl methacrylate	80-62-6	Flam. Liq. 2; H225	>=80
	201-297-1	Skin Irrit. 2; H315	
	01-2119452498-28-	Skin Sens. 1; H317	
	XXXX	STOT SE 3; H335	
		(Respiratory system)	

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Jika®

Revision Date: 13.02.2025 Date of last issue: 12.01.2023

Sikafloor[®]-14 Pronto

Version 2.0

Print Date 13.02.2025

tetramethylene dimethacrylate	2082-81-7 218-218-1 01-2119967415-30- XXXX	Skin Sens. 1B; H317	>= 1 - < 2,5
aromatic amine ethoxylated	Not Assigned 911-490-9 01-2119979579-10- XXXX	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 0,25 - < 0,5
2-(N-methyl-p-toluidino)ethanol	2842-44-6 220-638-5 01-2120827830-56- XXXX	Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 0,25 - < 0,5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Move to fresh air. Consult a physician after significant exposure.
In case of skin contact : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact : Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed : Do not induce vomiting without medical advice. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
4.2 Most important symptoms and effects, both acute and delayed
Symptoms : Cough Respiratory disorder Allergic reactions Erythema Dermatitis See Section 11 for more detailed information on health effer and symptoms.
Risks : irritant effects

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878 Sikafloor®-14 Pronto



Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

sensitising effects

Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

```
Treatment : Treat symptomatically.
```

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	Water High volume water jet
5.2 Special hazards arising from	the	e substance or mixture
Specific hazards during fire- fighting	:	Do not use a solid water stream as it may scatter and spread fire.
Hazardous combustion prod- ucts	:	Carbon dioxide (CO2) Carbon monoxide
		No hazardous combustion products are known
5.3 Advice for firefighters		
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Further information	:	Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures					
Personal precautions	Use personal protective equipment. Remove all sources of ignition. Deny access to unprotected persons. Beware of vapours accumulating to form explosive concentra- tions. Vapours can accumulate in low areas.				
6.2 Environmental precautions					
Environmental precautions	Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform				

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-14 Pronto



Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up
- : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

	Advice on safe handling :	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure.
		Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products
	Advice on protection against : fire and explosion	Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
	Hygiene measures :	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, inc	luding any incompatibilities
	Requirements for storage : areas and containers	Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.
		Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-14 Pronto



Revision Date: 13.02.2025 Date of last issue: 12.01.2023		Version 2.0	Print Date 13.02.2025
		in accordance with local regulations.	
Further information on stor- age stability	:	No decomposition if stored and applied as dir	ected.
7.3 Specific end use(s) Specific use(s)	:	Consult most current local Product Data Shee use.	et prior to any

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parame-	Basis *		
		of exposure)	ters *			
methyl methacrylate	80-62-6	TWA	50 ppm	2009/161/EU		
	Further inform	Further information: Indicative				
		STEL 100 ppm 2009/161/EU				
		TWA 50 ppm				
		STEL	100 ppm	GR OEL		

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

8.2 Exposure controls

Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Hand protection		Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications. Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection	:	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
Respiratory protection	:	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator.

SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-14 Pronto



Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

organic vapor filter (Type A) A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice	: Prevent product from entering drains.
	If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Colour Odour		liquid dark blue unpleasant
Melting point/freezing point	:	-48 °C
Boiling point/boiling range	:	100 °C
Flammability (solid, gas)	:	No data available
Upper/lower flammability or	exp	losive limits
Upper explosion limit / Up- per flammability limit	:	Upper flammability limit 12,5 %(V)
Lower explosion limit / Lower flammability limit	:	Lower flammability limit 2,1 %(V)
Flash point	:	ca. 10 °C Method: closed cup
Auto-ignition temperature	:	ca. 430 °C
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	ca. 300 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm2/s (40 °C)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-14 Pronto

Vapour pressure

Relative vapour density

Particle characteristics

Density



Revision Date: 13.02.2025 Date of last issue: 12.01.2023	Version 2.0	Print Date 13.02.2025
Solubility(ies) Water solubility	: insoluble	
Partition coefficient: n- octanol/water	: No data available	

: ca. 38,7 hPa (20 °C)

: No data available

: No data available

: ca. 0,99 g/cm3 (20 °C)

SECTION 10:	Stability and	reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

9.2 Other information No data available

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions.
		Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid :	No data available
----------------------	-------------------

10.6 Hazardous decomposition products

No hazardous decomposition products are known.



Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Not classified due to lack of c <u>Components:</u>	lata.	
methyl methacrylate: Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 29,8 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg
2-(N-methyl-p-toluidino)eth	ano	l:
Acute oral toxicity	:	LD50 Oral (Rat): > 2.000 mg/kg
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye irr Not classified due to lack of c		
Respiratory or skin sensitis	satio	on
Skin sensitisation May cause an allergic skin re	acti	on.
Respiratory sensitisation Not classified due to lack of c	lata.	
Germ cell mutagenicity Not classified due to lack of c	lata.	
Carcinogenicity Not classified due to lack of c	lata.	
Reproductive toxicity Not classified due to lack of data.		
STOT - single exposure May cause respiratory irritation	on.	
STOT - repeated exposure Not classified due to lack of c	lata.	
Aspiration toxicity		

Not classified due to lack of data.

Jika®

Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

methyl	methacrylate:
--------	---------------

Toxicity to fish	:	NOEC (Danio rerio (zebra fish)): 9,4 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 69 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
		NOEC : 37 mg/l Exposure time: 21 d Method: OECD Test Guideline 202
Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	NOEC: 37 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment	: This substance/mixture contains no components considered
	to be either persistent, bioaccumulative and toxic (PBT), or
	very persistent and very bioaccumulative (vPvB) at levels of
	0.1% or higher.



Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

12.6 Endocrine disrupting properties

Product:

Assessment

t	:	The substance/mixture does not contain components consid-
		ered to have endocrine disrupting properties according to
		REACH Article 57(f) or Commission Delegated regulation
		(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at
		levels of 0.1% or higher.
		· · · · · · · · · · · · · · · · · · ·

12.7 Other adverse effects

8	:	There is no data available for this product.
mation		

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
Product	 The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
European Waste Catalogue	: 08 01 11* waste paint and varnish containing organic sol- vents or other dangerous substances
Contaminated packaging	: 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

:	UN 1247
:	UN 1247
:	UN 1247
	:

14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-14 Pronto



Revision Date: 13.02.2025 Date of last issue: 12.01.2023		Version 2.0	Print Date 13.02.2025
ADR IMDG IATA 14.3 Transport hazard class(es)	:	METHYL METHACRYLATE MONOME METHYL METHACRYLATE, MONOME Methyl methacrylate monomer, stabilize	R, STABILIZED
ADR IMDG IATA	:	Class Subsidiary risks 3 3 3	
14.4 Packing group ADR Packing group		11	
Classification Code Hazard Identification Number Labels Tunnel restriction code	: :	F1 339 3 (D/E)	
IMDG Packing group Labels EmS Code	::	ll 3 F-E, S-D	
IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	364 Y341 II Flammable Liquids	
IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	353 Y341 II Flammable Liquids	
14.5 Environmental hazards			
ADR Environmentally hazardous	:	no	
IMDG Marine pollutant IATA (Passenger)	:	no	
Environmentally hazardous	:	no	
Environmentally hazardous	:	no	

Sikafloor[®]-14 Pronto



Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

REACH Information:

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or

All substances contained in our Products are

- exempted from the registration.

REACH - Restrictions on the mar the market and use of certain dan mixtures and articles (Annex XVII	ngerous substances,	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
			Number on list 75
REACH - Candidate List of Subst Concern for Authorisation (Article		:	None of the components are listed (=> 0.1 %).
REACH - List of substances subje (Annex XIV)	ect to authorisation	:	Not applicable
Regulation (EU) No 2024/590 on plete the ozone layer	substances that de-	:	Not applicable
Regulation (EU) 2019/1021 on per tants (recast)	ersistent organic pollu-	:	Not applicable
Regulation (EU) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals			Not applicable
Seveso III: Directive 2012/18/EU jor-accident hazards involving dar P5c	•		and of the Council on the control of ma-
Volatile organic compounds :	Law on the incentive tax	x fc	or volatile organic compounds

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-14 Pronto



Revision Date: 13.02.2025 Date of last issue: 12.01.2023 Version 2.0

Print Date 13.02.2025

(VOCV)

Volatile organic compounds (VOC) content: < 0,01% w/w no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: < 0,01% w/w

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements		
H225	:	Highly flammable liquid and vapour.
H302	:	Harmful if swallowed.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H335	:	May cause respiratory irritation.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
Full text of other abbreviation	ons	
Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT SE	:	Specific target organ toxicity - single exposure
2009/161/EU	:	Europe. COMMISSION DIRECTIVE 2009/161/EU establishing
		a third list of indicative occupational exposure limit values in
		implementation of Council Directive 98/24/EC and amending
		Commission Directive 2000/39/EC
GR OEL	:	Greece. Exposure limit values
2009/161/EU / TWA	:	Limit Value - eight hours
2009/161/EU / STEL	:	Short term exposure limit
GR OEL / TWA	:	Long term exposure limit
GR OEL / STEL	:	Short term exposure limit
ADR	:	European Agreement concerning the International Carriage of
0.1.0		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	÷	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878

Sikafloor®-14 Pronto



Revision Date: 13.02.2025 Version 2.0 Print Date 13.02.2025 Date of last issue: 12.01.2023 IMDG International Maritime Code for Dangerous Goods : LD50 Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) Median lethal concentration (concentrations of the chemical in LC50 : air that kills 50% of the test animals during the observation period) MARPOL International Convention for the Prevention of Pollution from : Ships, 1973 as modified by the Protocol of 1978 OEL **Occupational Exposure Limit** : PBT Persistent, bioaccumulative and toxic : PNEC Predicted no effect concentration : REACH Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency Substances of Very High Concern SVHC : Very persistent and very bioaccumulative vPvB

Further information

Classification of the mixture:		Classification procedure:
Flam. Liq. 2	H225	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Skin Sens. 1	H317	Calculation method
STOT SE 3	H335	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

GR / EN