

SikaEmaco® S 285 TIX

DECLARATION OF PERFORMANCE N. 78905511

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	78905511
2	INTENDED USE/S:	EN 998-1:2016 Factory made rendering and plastering renovation mortar (R) intended for use in walls, ceilings, columns and partitions
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 998-1:2016
	Notified body/ies:	0546

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Euroclass A1	System 4	EN 998-1:2016
Water absorption	0,1 kg/m ² h ^{0,5}	System 4	
Water vapor permeability coefficient	μ14	System 4	
Adhesion	0,72 MPa FP: A/C	System 4	
Thermal conductivity	0,83 W/mK (λ _{10, dry} value tab., P=50%)	System 4	
Durability	NPD		
Dangerous substances	NPD		

NPD - No performance determined

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: Target Market Manager
Refurbishment
At Athens on 27 January 2025

Name: Angeliki Zacharopoulou
Function: QEHS
At Athens on 27 January 2025



.....



.....

End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaEmaco® S 285 TIX
78905511
2025.01 , ver. 1
1026

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
SikaEmaco® S 285 TIX	EN 998-2:2016	68859766

 25	
DoP No. 78905511	
Sika Services AG, Zurich, Switzerland	
EN 998-1:2016	
Notified Body 0925	
Factory made rendering and plastering renovation mortar (R) intended for use in walls, ceilings, columns and partitions	
Reaction to fire	Euroclass A1
Water absorption	0,1 kg/m ² h ^{0,5}
Water vapor permeability coefficient	μ14
Adhesion	0,72 MPa FP: A/C
Thermal conductivity	0,83 W/mK (λ _{10, dry} value tab., P=50%)
http://dop.sika.com	

Declaration of Performance

SikaEmaco® S 285 TIX
78905511
2025.01 , ver. 1
1026

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Sika Italia SpA

Via Luigi Einaudi, 6
20068 Peschiera Borromeo
(MI)
ITALIA
<http://ita.sika.com/>

Declaration of Performance

SikaEmaco® S 285 TIX
78905511
2025.01 , ver. 1
1026