

SikaGrout®-311

DECLARATION OF PERFORMANCE No. 52480276

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	52480276
2	INTENDED USE/S	EN 1504-6:2006 Anchoring product for strengthening concrete by installing reinforcing steel in buildings and civil engineering works
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ for type testing
6a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body/ies:	1139

Declaration of Performance

SikaGrout®-311
52480276
2023.02 , ver. 1
1029

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
Pull-out strength	Displacement \leq 0.6 mm at load of 75 kN	EN 1504-6:2006
Chloride ion content	\leq 0.05 %	
Glass transition temperature	NPD	
Creep under tensile load	NPD	
Reaction to fire	NPD	
Durability	NPD	
Dangerous substances	NPD	

*NPD - No performance determined


8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos
Function: Target Market Manager
Refurbishment
At Athens on 12 February 2023

Name: Angeliki Zacharopoulou
Function: QEHS Manager
At Athens on 12 February 2023

.....


.....


End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaGrout®-311
52480276
2023.02 , ver. 1
1029



13

DoP No. 52480276

Sika Services AG, Zurich, Switzerland

EN 1504-6:2006

Notified Body 1139

Anchoring product for strengthening concrete by installing reinforcing steel in buildings and civil engineering works

Pull-out

Displacement \leq 0.6 mm at load of 75 kN

Chloride ion content

\leq 0.05 %

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaGrout®-311
52480276
2023.02 , ver. 1
1029



Sika Services AG
Tuffenwies 16- 22
8048, Zurich
Switzerland
www.sika.com

Declaration of Performance

SikaGrout®-311
52480276
2023.02 , ver. 1
1029