

## PRODUCT DATA SHEET

# Sarnafil® T Pipe Flashing

### PREFABRICATED FPO PIPE/VENT FLASHING

#### DESCRIPTION

Sarnafil® T Pipe Flashing is made of synthetic roof waterproofing membrane based on premium-quality flexible polyolefins (FPO), containing stabilizers, with inlay of glass non-woven.

#### USES

Sarnafil® T Pipe Flashing is used as a prefabricated part for pipe/vent flashing on Sarnafil® T flat roof systems.

#### CHARACTERISTICS / ADVANTAGES

- Resistant to permanent UV irradiation
- Easy and safe application
- Hot air welding without use of open flame
- Recyclable



#### APPROVALS / CERTIFICATES

- Quality management system EN ISO 9001/14001
- Reaction to fire according to EN 13501-1, class E

#### PRODUCT INFORMATION

|                            |  |                          |
|----------------------------|--|--------------------------|
| <b>Composition</b>         | Flexible polyolefins (FPO) based on polypropylene (PP)   |                          |
| <b>Packaging</b>           | Depending on the order quantity and product size, the products are packaged on pallets or in cartons             |                          |
| <b>Appearance / Colour</b> | Surface:   | smooth                   |
|                            | Colour:  | Beige                    |
|                            |  | Grey (nearest RAL 7040)  |
|                            |  | Other colours on request |
| <b>Shelf life</b>          | 5 years from date of production  |                          |
| <b>Storage conditions</b>  | Sarnafil® T Pipe Flashing must be stored between +5 °C and +30 °C protected from direct sunlight, rain and snow. |                          |

**Dimensions**

| Art. No. | Colour   | Inside diameter | Sleeve height | Flange size  |
|----------|----------|-----------------|---------------|--------------|
| 110461   | beige    | 82 mm           | 400 mm        | 300 × 300 mm |
| 135689   | RAL 7040 | 82 mm           | 400 mm        | 300 × 300 mm |
| 110462   | beige    | 92 mm           | 400 mm        | 300 × 300 mm |
| 135692   | RAL 7040 | 92 mm           | 400 mm        | 300 × 300 mm |
| 110456   | beige    | 102 mm          | 400 mm        | 300 × 300 mm |
| 135693   | RAL 7040 | 102 mm          | 400 mm        | 300 × 300 mm |
| 110457   | beige    | 112 mm          | 400 mm        | 300 × 300 mm |
| 125517   | RAL 7040 | 112 mm          | 400 mm        | 300 × 300 mm |
| 110458   | beige    | 127 mm          | 400 mm        | 300 × 300 mm |
| 135695   | RAL 7040 | 127 mm          | 400 mm        | 300 × 300 mm |
| 110459   | beige    | 142 mm          | 400 mm        | 300 × 300 mm |
| 135696   | RAL 7040 | 142 mm          | 400 mm        | 300 × 300 mm |
| 110460   | beige    | 167 mm          | 400 mm        | 300 × 300 mm |
| 135462   | RAL 7040 | 167 mm          | 400 mm        | 300 × 300 mm |

|                  |        |
|------------------|--------|
| <b>Thickness</b> | 1.5 mm |
|------------------|--------|

**SYSTEMS**

|                         |                      |  |
|-------------------------|----------------------|--|
| <b>System Structure</b> | Compatible products: | Sarnafil® TG 66-types<br>Sarnafil® TG 76 -types<br>Sarnafil® TS 77-types |
|-------------------------|----------------------|--|

**APPLICATION INFORMATION**

|                                |                           |
|--------------------------------|---------------------------|
| <b>Ambient Air Temperature</b> | -20 °C min. / +60 °C max. |
|--------------------------------|---------------------------|

|                              |                           |
|------------------------------|---------------------------|
| <b>Substrate Temperature</b> | -30 °C min. / +60 °C max. |
|------------------------------|---------------------------|

**APPLICATION INSTRUCTIONS****APPLICATION**

Installation works to be carried out only by Sika instructed contractors for roofing.

**APPLICATION METHOD / TOOLS**

According to the valid installation instructions for Sarnafil® flat roof waterproofing membranes.

**IMPORTANT CONSIDERATIONS**

The use of Sarnafil® T Pipe Flashing is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1% (w/w).

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE  
15 Protomagias Str.  
14568 Kryoneri  
Attica-Greece  
Tel.: +30 210 8160 600  
Fax: +30 210 8160 606  
www.sika.gr | sika@gr.sika.com



Product Data Sheet  
Sarnafil® T Pipe Flashing  
August 2019, Version 01.01  
020945032100001000

SarnafilTPipeFlashing-en-GR-(08-2019)-1-1.pdf