

Sikafloor®-300 Level (GR)

DECLARATION OF PERFORMANCE No. 48819306

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	48819306
2	INTENDED USE/S	EN 13813:2002 Cementitious screed for internal uses
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4 / System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 13813:2002
	Notified body/ies:	0370

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	A1/A1fl	System 3	EN 13813-2002
Release of corrosive substances	CT	System 4	
Compressive strength	C30	System 4	
Flexural strength	F7	System 4	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Angeliki Zacharopoulou
Function: QEHS Manager
At Athens on 29 April 2021

Name : Kostas Mourikis
Function: Target Market Manager Flooring
At Athens on 29 April 2021



End of information as required by Regulation (EU) No 305/2011





21

Sika Hellas ABEE, Athens, Greece

DoP No. 48819306

EN 13813:2002

Notified Body 0370

Cementitious screed for internal uses

Reaction to fire	A1/A1fl
Release of corrosive substances	CT
Compressive strength	C30
Flexural strength	F7

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikafloor®-300 Level (GR)

48819306

2021.02, ver. 1

1200

3/4

BUILDING TRUST





Sika Hellas ABEE
Protomagias 15
145 68 Athens
Greece
www.sika.gr

Declaration of Performance

Sikafloor®-300 Level (GR)
48819306
2021.02 , ver. 1
1200