

PRODUCT DATA SHEET

S-Felt GK-400

POLYPROPYLENE PROTECTION AND SLIP LAYER

DESCRIPTION

S-Felt GK-400 is a protection and slip layer made of polypropylene (PP) with a polyethylene (PE) coating on one side.

USES

- Protective and slip-layer beneath paving or poured cementitious toppings.

CHARACTERISTICS / ADVANTAGES

- Bitumen resistant
- Acid resistant (pH 2,4)
- Easily applied



PRODUCT INFORMATION

Composition	100 % polypropylene (PP) (foil PE)	
Packaging	Wrapped individually in black PE-foil.	
	Roll length	50,00 m
	Roll width	2,00 m
	Roll weight	40,00 kg
Appearance / Colour	Surfaces	Structured and smooth
	Colours	Multi-coloured/black
Shelf life	5 years from date of production.	
Storage conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Store in a horizontal position. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage. Always refer to packaging.	
Length	50,00 m	
Width	2,00 m (+/-2 %)	

serves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE
15 Protomagias Str.
14568 Kryoneri
Attica-Greece
Tel.: +30 210 8160 600
Fax: +30 210 8160 606
www.sika.gr | sika@gr.sika.com



Product Data Sheet
S-Felt GK-400
May 2019, Version 01.01
020945051050000005

S-FeltGK-400-en-GR-(05-2019)-1-1.pdf

