

SikaTard® R-3

DECLARATION OF PERFORMANCE

No. 67547897

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	67547897
2	INTENDED USE/S:	EN934-3:2009+A1:2012
		To be used in masonry mortar
		Set retarding admixture for long term retarded masonry mortar (Table 3)
3	MANUFACTURER:	Sika Hellas ABEE
		15 Protomagias Str.
		GR 145 68 Kryoneri
		Athens - Greece
		www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN934-3:2009+A1:2012
-	Notified body/ies:	1128

SikaTard® R-3 67547897 2016.10 , Revision 1

7 DECLARED PERFORMANCE/S:


Essential Characteristics	Performance	Harmonised Technical Specification
Table 3	Tatal air agustant huuraluna A (47 + 2)0/	
Air content after standard mixing	Total air content by volume $A_2 = (17 \pm 3)\%$	
Air content after extended mixing	$\leq A_2 + 5 \%$ and $\geq A_2 - 5 \%$	
Consistence after 28h standing	Within 15mm of initial value	
Air content after 28h standing	≥ 0.70 A ₂ %	
Resistance to penetration after 72h	Test mix ≥ 1.0 N/mm ²	EN934- 3:2009+A1:2012
Compressive strength	At 28 days: Test mix ≥ 70 % of control mix	
General Characteristics	Performance	
Chloride ion content	Chloride free	
Alkali content	≤ 4.0 % by mass	
Comparison habenion	Contains components only	_
Corrosion behavior	from EN934-1:2008, Annex A.1	
Dangerous Substances	NPD*	
*NPD - No performance determined		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Manolis Mavratzotis Function: R&D/QC Manager At Athens on 05 October 2016 Name: Spyros Hatzifotis Function: General Manager At Athens on 05 October 2016





07

Sika Hellas ABEE, Athens - Greece

67547897

EN934-3:2009+A1:2012

1128

SikaTard® R-3

To be used in masonry mortar

Set retarding admixture for long term retarded masonry mortar

(Table 3)

For essential characteristics please refer to Declaration of Performance

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.





Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance

SikaTard® R-3 67547897 2016.10 , Revision 1

