

Declaration of Performance

No DoP: 73904106

BUILDING TRUST



1.	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE: Identification of the construction product as required under Article 11(4) of the regulation n° 305/2011/EU:	Sika ThermoCoat® -2 HS MW 20		
		MW-EN 13162-T5-DS(70,90)-CS(10)20-TR7,5-PL(5)200-WS-WL(P)-MU1-AW0,95-AF50		
2.	INTENDED USE/S:	EN 13162:2012 Thermal Insulation of Building (ThIB)		
3.	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr		
4.	AUTHORISED REPRESENTATIVE:			
5.	SYSTEM/S OF AVCP:	AVCP - System 1 - System 3		
6α.	HARMONISED STANDARD: Notified Certification bodies:	Notified Certification bodies:		0751, 0764
		Certificate number:		0751-CPR-223.4-01
		Harmonised standard		EN 13162:2012+A1:2015

7.	Declared performance:	EN 13162:2012+A1:2015			
Essential characteristics	Performance	Abbreviation	Unit	Declared performance	
Reaction to fire	Reaction to fire	RtF	Euroclass	A1	
Release of dangerous substances	Release of dangerous substances			NPD	
Acoustic absorption index	Sound absorption	AW	-	0,95	
Impact noise transmission index	Dynamic stiffness	SD	MN/m ³	NPD	
	Thickness	dl	mm	NPD	
	Compressibility	CP	mm	NPD	
	Air flow resistivity	Afr	kPa.s/m ²	50	
Direct airborne sound insulation index	Air flow resistivity	Afr	kPa.s/m ²	50	
Continous glowing combustion	Continous glowing combustion			NPD	
Thermal resistance	Thermal resistance	R ₀	m ² K/W	see table below	
	Thermal conductivity	λ _D	W/m K	0,034	
	Thickness	d _n	mm	40-300	
	Thickness class	T	Class	T5	
Water permeability	Short term water absorption	WS	kg/m ²	<1	
	Long term water absorption	WL(P)	kg/m ²	<3	
Water vapour permeability	Water vapour transmission	MU	-	1	
		Z	m ² hPa/mg	NPD	
Compressive strength	Compressive stress	CS(10)	kPa	20	
	Point Load	PL(5)	N	200	
Durability of reaction to fire against heat, weathering, ageing/degradation	Reaction to fire	RtF	Euroclass	A1	
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance	R ₀	m ² K/W	see table below	
	Thermal conductivity	λ _D	W/m K	0,034	
	Durability characteristics	DS(70,90)	%	≤1	
Tensile/Flexural strength	Tensile strength perpendicular to faces	TR	kPa	7,5	
Durability of compressive strength against heat, weathering, ageing/degradation	Compressive creep	CC(i1/i2/y) cc	mm	NPD	
NPD: No Performance Determined					

7.	DECLARED PERFORMANCE/S:								
Thickness - d _n (mm)	40	50	60	70	80	90	100	110	120
Thermal resistance R _s , m ² K/W	1,15	1,45	1,75	2,05	2,35	2,60	2,90	3,20	3,50
Thickness - d _n (mm)	130	140	150	160	180	200			
Thermal resistance R _s , m ² K/W	3,80	4,10	4,40	4,70	5,25	5,85			


8. APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Name : Nikos Anagnostopoulos
Function: Target Market Manager Refurbishment

At Athens 3 November 2022



Name : Angeliki Zacharopoulou
Function: QEHS Manager

At Athens 3 November 2022



End of information as required by Regulation (EU) No 305/2011

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Hellas ABEE
15 Protomagias Str.
GR 145 68 Kriyomeri
Athens - Greece
www.sika.gr

BUILDING TRUST

