
Sikafloor[®]-2350 ESD

DECLARATION OF PERFORMANCE

No. 76963205

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	76963205
2	INTENDED USE/S	Synthetic resin screed for internal uses
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	EN 13813: System 4 (for internal uses) EN 13813: System 3 (for reaction to fire)
6a	HARMONISED STANDARD:	EN 13813:2002
	Notified body/ies:	1611

Declaration of Performance

Sikafloor[®]-2350 ESD

76963205

20.05.2022 , ver. 1

1008

7	DECLARED PERFORMANCE/S	Tested as a part of a system build-up with Sikafloor®-151 and Sikafloor®-220 W Conductive		
	Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
	Reaction to fire:	B _{fl}	System 3	EN 13813:2002
	Release of corrosive substances:	SR	System 4	
	Water permeability:	NPD	System 4	
	Wear resistance:	≤ AR0,5 ¹⁾	System 4	
	Bond strength:	≥ B2,0	System 4	
	Impact resistance:	≥ IR6	System 4	
	Sound insulation:	NPD	System 4	
	Sound absorption:	NPD	System 4	
	Thermal resistance:	NPD	System 4	
	Chemical resistance:	NPD	System 4	

¹⁾ Min. classification, please refer to the individual test certificate.

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Aggeliki Zacharopoulou
 Function: QEHS Manager
 At Athens on 20 May 2022

Name: Kostas Mourikis
 Function: TMM Flooring
 At Athens on 20 May 2022





End of information as required by Regulation (EU) No 305/2011


Declaration of Performance

Sikafloor®-2350 ESD
 76963205
 20.05.2022 , ver. 1
 1008



RELATED DECLARATION OF PERFORMANCE

Product name	Harmonised standard	DoP number
Sikafloor®-2350 ESD	EN 1504-2:2004	87201505

 20	
EN 13813: 2002	
DoP No. 76963205	
Sika Services AG, Zürich, Switzerland	
Notified Body 1611	
Synthetic resin screed for internal uses	
Reaction to fire:	B _{fl}
Release of corrosive substances:	SR
Wear resistance:	≤ ARO,5
Bond strength:	≥ B2,0
Impact resistance:	≥ IR6
http://dop.sika.com	

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)


For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikafloor®-2350 ESD
76963205
20.05.2022 , ver. 1
1008



Declaration of Performance

Sikafloor®-2350 ESD

76963205

20.05.2022 , ver. 1

1008