

PRODUCT DATA SHEET

SikaCeram® Epoxy Remover

CLEANER FOR EPOXY GROUTING RESIDUALS

DESCRIPTION

SikaCeram® Epoxy Remover is a water-based product used to remove epoxy grouting residuals.

USES

- Removal, from ceramic or porcelain stoneware tile, of light or even heavy residues of epoxy grouting such as SikaCeram® Epoxy Remover.
- Used thinned, it cleans and degrease very dirty floors in porcelain stoneware and ceramic.

CHARACTERISTICS / ADVANTAGES

- Specific for Sika epoxy grouting
- Efficient also after several days from grouting application
- Easy to use

PRODUCT INFORMATION

Chemical base	Water-based product. Containing: EDTA and salts ≤ 5%, soap between 5 % and 15 %. Other components: fragrance.
Packaging	2 kg plastic bottle
Colour	Pale yellow liquid
Shelf life	24 months from date of production
Storage conditions	Store at temperature between +5°C and +30°C
Density	~ 1.01 kg/l
pH-Value	~ 11.3

APPLICATION INSTRUCTIONS

APPLICATION

SikaCeram® Epoxy Remover should be used either undiluted or diluted with water, as required.

How to remove consistent epoxy grouting residues
Pour on the undiluted product; allow to act for 15-20 minutes, then rub with abrasive felt and rinse off; if necessary, use a metal trowel to remove built up grouting from the tiles, then rub with the abrasive felt.

How to remove the stains left by epoxy grouting or use as a dewaxer

Dilute the product in water in ratio of 1:5, apply and allow it to act for a few minutes; rub with felt, or use a scrubbing brush or single-disc cleaner; vacuum or wipe up dirt and rinse with plenty of water.

How to remove stains from porcelain stoneware

Pour the undiluted product on to the stain and all over the tile; allow the product to act for 15-20 min, then rub with abrasive felt and rinse.

LIMITATIONS

- The use of SikaCeram® Epoxy Remover on epoxy grouts must be done 48 h at least after the grouting, 24 hours if the ambient temperature is $\geq +20^{\circ}\text{C}$.
- Do not use on polished marble or stone.
- Do not use on wood.
- Do not use on methacrylate tubs.
- Test the surface to make sure it is not damaged before applying SikaCeram® Epoxy Remover

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE
15 Protomagias Str.
14568 Kryoneri
Attica-Greece
Tel.: +30 210 8160 600
Fax: +30 210 8160 606
www.sika.gr | sika@gr.sika.com



SikaCeramEpoxyRemover_en_GR_(03-2017)_1_1.pdf

Product Data Sheet
SikaCeram® Epoxy Remover
March 2017, Version 01.01
020404200010000054