

Sikalastic®-152 HP

DECLARATION OF PERFORMANCE

No. 56291523

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	56291523
2	INTENDED USE/S	EN 1504-2:2004 Surface protection product – Coating. Principle 1 (Protection against ingress) – Method 1.3. Principle 2 (Moisture control) – Method 2.3 and Principle 8 (Increasing resistivity) – Method 8.3 according to EN 1504-9:2008
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ plus 3
6a	HARMONIZED STANDARD:	EN 1504-2:2004
	Notified body/ies:	1128 0370 (Reaction to fire)

Declaration of Performance

Sikalastic®-152 HP
56291523
2022.07, ver. 1
1200

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Permeability to CO ₂	S _D > 50 m	System 2+ plus 3	
Permeability to water vapour	Class I, S _D < 5 m	System 2+ plus 3	
Capillary absorption and permeability to water	w < 0.1 kg/m ² × h ^{0.5}	System 2+ plus 3	
Freeze-thaw cycling with de-icing salt immersion	≥ 0.8 MPa	System 2+ plus 3	
Adhesion strength by pull off test	≥ 0.8 MPa	System 2+ plus 3	EN 1504-2:2004
Determination of crack bridging properties, Method A	Class A4 (23 °C)- without mesh	System 2+ plus 3	
	Class A3(-10 °C)- without mesh-	System 2+ plus 3	
	Class A5 (23 °C)- with mesh	System 2+ plus 3	
	Class A4(-10 °C)- with mesh	System 2+ plus 3	
Determination of crack bridging properties, Method B	No Crack (23 °C)-Class B.4.2- with mesh	System 2+ plus 3	
Reaction to fire	Class B-s1,d0	System 2+ plus 3	
Dangerous substances	Comply with 5.3	System 2+ plus 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Name: Stamatis Antonakos
Function: TMM Waterproofing & σιτηοθητ Roofing
At Athens on 26 July 2022

Name: Angeliki Zacharopoulou
Function: QEHS Manager

At Athens on 26 July 2022



.....



.....


End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikalastic®-152 HP
56291523
2022.07, ver. 1
1200

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sikalastic®-152 HP	EN 14891:2017	30160568

 22	
Sika Hellas ABEE, Athens, Greece	
DoP No. 56291523	
EN 1504-2:2004	
Notified Body 1128, 0370	
Surface protection product – Coating. Principle 1 (Protection against ingress) – Method 1.3. Principle 2 (Moisture control) – Method 2.3 and Principle 8 (Increasing resistivity) – Method 8.3 according to EN 1504-9:2008	
Permeability to CO ₂	S _D > 50 m
Permeability to water vapour	Class I, S _D < 5 m
Capillary absorption and permeability to water	w < 0.1 kg/m ² × h ^{0,5}
Freeze-thaw cycling with de-icing salt immersion	≥ 0.8 MPa
Adhesion strength by pull off test	≥ 0.8 MPa
Determination of crack bridging properties, Method A	Class A4 (23 °C)- without mesh
	Class A3 (-10 °C)- without mesh
	Class A5 (23 °C)- with mesh
	Class A4 (-10 °C)- with mesh
Determination of crack bridging properties, Method B	No Crack - Class B 4.2.(23 °C)- with mesh
Reaction to fire	Class B-s1,d0
Dangerous substances	Comply with 5.3
http://dop.sika.com	

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Declaration of Performance

Sikalastic®-152 HP
 56291523
 2022.07, ver. 1
 1200

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Hellas ABEE
Protomagias 15
14568 Kryoneri
Attica - Greece
www.sika.gr

Declaration of Performance
Sikalastic®-152 HP
56291523
2022.07, ver. 1
1200