



# Sikalastic®-670 TC

1-COMPONENT POLYURETHANE TOPCOAT FOR  
Sikalastic® ROOF WATERPROOFING SYSTEMS

## UNIQUE SELLING POINTS

- Resistant to UV exposure – reflective and resistant to yellowing
- Highly elastic and crack-bridging – retains flexibility even at low temperatures
- Single component, easy to apply
- Easily recoated – no stripping required
- Water vapor permeable
- Good resistance to common atmospheric chemicals

## APPLICATION FIELDS:

- UV-stable top coat for Sikalastic® roof waterproofing systems
- Reflective top coat for excellent cool roof characteristics and solar roofs
- Color stable aliphatic PU top coat for use on roofs exposed to ponding water

## TECHNICAL CHARACTERISTICS:

- Aliphatic polyurethane
- Packaging: in metal containers of 1kg, 5kg and 20kg
- Color: White (others colors available upon request)
- Consumption: ~0.2-0.6 kg/m<sup>2</sup> in 1 or 2 coats depending on traffic conditions

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.

### Sika HELLAS ABEE

15 Protomagias str.  
GR 145 68, Kryoneri,  
Attica, Greece

### Contact

Tel. + 30 210 81 60 600  
E-mail: [export@gr.sika.com](mailto:export@gr.sika.com)  
[www.sika.gr](http://www.sika.gr)

**BUILDING TRUST**

