

PRODUCT DATA SHEET

Sikacryl[®]-625 Fire

FIRE RESISTANT ABLATIVE COATING FOR SIKASEAL[®]-626 FIRE BOARD

DESCRIPTION

Sikacryl[®]-625 Fire is a 1-part fire resistant, ablativ acrylic coating used for the installation of SikaSeal[®]-626 Fire Board

CHARACTERISTICS / ADVANTAGES

- 1-part ready to use, easy to apply, easy to clean
- Provides a neat finish to the cut edges of SikaSeal[®]-626 Fire Board

USES

- Touching up SikaSeal[®]-626 Fire Board after installation
- Edge coating of SikaSeal[®]-626 Fire Board when installed on the outer face of a wall or floor

PRODUCT INFORMATION

Composition	Water based acrylic
Packaging	5 kg container. Refer to current price list for packaging variations.
Appearance / Colour	White
Shelf life	12 months from the date of production.
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.
Density	~1,40 kg/l (ISO 1183-1)

TECHNICAL INFORMATION

Resistance to Fire	Refer to SikaSeal [®] -626 Fire Board 'Approvals / Certificates', Sika Passive Fire Protection Handbook or contact Sika Technical Services for specific information.
---------------------------	---

APPLICATION INFORMATION

Layer Thickness	2 mm (wet film thickness)
Ambient Air Temperature	+5 °C min. / +40 °C max.
Substrate Temperature	+5 °C min. / +40 °C max., min. 3 °C above dew point temperature

APPLICATION INSTRUCTIONS

APPLICATION

Reference must be made to the Sika Passive Fire Protection Handbook or contact Sika Technical Services for specific information.

CLEANING OF EQUIPMENT

Clean all tools and application equipment with water immediately after use. Hardened material can only be removed mechanically.

FURTHER INFORMATION

- Sika Method Statement: SikaSeal®-626 Fire Board
- Sika Passive Fire Protection Handbook

IMPORTANT CONSIDERATIONS

- Limitations regarding dimensions and configuration described in the relevant fire resistance classification reports must be considered.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE
15 Protomagias Str.
14568 Kryoneri
Attica-Greece
Tel.: +30 210 8160 600
Fax: +30 210 8160 606
www.sika.gr | sika@gr.sika.com



Product Data Sheet
Sikacryl®-625 Fire
April 2020, Version 01.01
020515110000000002

Sikacryl-625Fire-en-GR-(04-2020)-1-1.pdf