

# Sikaflex® PRO-3 Purform®

## DECLARATION OF PERFORMANCE

### No. 33809346

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	33809346
2	<b>INTENDED USE/S</b>	EN 15651-4:2012 Sealant for non-structural joints in floors for exterior and interior application PW EXT-INT CC
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 3
6a	<b>HARMONISED STANDARD:</b>	EN 15651-4:2012
	Notified body/ies:	1213

#### Declaration of Performance

Sikaflex® PRO-3 Purform®  
33809346  
2022.07 , ver. 1  
1003, 1009

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	EN 15651-4:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Water tightness and air tightness			
Tensile properties at maintained extension	NF at 100 % elongation	System 3	
Loss of volume	≤ 10%	System 3	
Tear resistance	NF at 50 % elongation	System 3	
Adhesion/cohesion properties at maintained extension after 28 days water immersion	NF at 100 % elongation, change of secant modulus: ≤ 50 %	System 3	
Adhesion/cohesion properties at maintained extension after 28 days salt water immersion	NF at 100 % elongation	System 3	
Tensile properties (i.e. secant modulus) at (-30 ± 2)°C for cold climate areas	1,3 MPa	System 3	
Tensile properties at maintained extension at (-30±2)°C for cold climate areas	NF at 100 % elongation	System 3	
Durability	Pass	System 3	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Stamatios Kollias  
 Function: TMM Sealing & Bonding/Industry  
 At Athens on 09 July 2022

Name : Aggeliki Zacharopoulou  
 Function: EHS-QA-PRICING Manager  
 At Athens on 09 July 2022


.....

End of information as required by Regulation (EU) No 305/2011



## RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikaflex® PRO-3 Purform®	EN 14188-2:2004	15886099

 20	
Sika Services AG, Zurich, Switzerland	
33809346	
EN 15651-4:2012	
Notified Body 1213	
Sealant for non-structural joints in floors for exterior and interior application PW EXT-INT CC	
Reaction to fire	Class E
Water tightness and air tightness	
Tensile properties at maintained extension	NF at 100 % elongation
Loss of volume	≤ 10%
Tear resistance	NF at 50 % elongation
Adhesion/cohesion properties at maintained extension after 28 days water immersion	NF at 100 % elongation, change of secant modulus ≤ 50 %
Adhesion/cohesion properties at maintained extension after 28 days salt water immersion	NF at 100 % elongation
Tensile properties (i.e. secant modulus) at (-30 ± 2)°C for cold climate areas	1,3 MPa
Tensile properties at maintained extension at (-30±2)°C for cold climate areas	NF at 100 % elongation
Durability	Pass
<a href="http://dop.sika.com">http://dop.sika.com</a>	

### ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

#### Declaration of Performance

Sikaflex® PRO-3 Purform®  
33809346  
2022.07 , ver. 1  
1003, 1009

---

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

---



Sika Hellas ABEE  
Protomagias 15  
14568 Athens  
Greece  
[www.sika.gr](http://www.sika.gr)

### Declaration of Performance

Sikaflex® PRO-3 Purform®  
33809346  
2022.07 , ver. 1  
1003, 1009