

**BUILDING TRUST** 

# SikaFill®-90 MP DECLARATION OF PERFORMANCE No. 31014158

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	31014158
2	INTENDED USE/S	EN 1504-2:2004 Surface protection product – Coating Principle 1 (Protection against ingress) – Method 1.3 Principle 2 (Moisture control) – Method 2.3 and Principle 8 (Increasing resistivity) – Method 8.3 according to EN 1504-9:2008
3	MANUFACTURER:	Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ System 3 (for reaction to fire)
6a	HARMONISED STANDARD:	EN 1504-2:2004
	Notified body/ies:	1128

Declaration of Performance SikaFill®-90 MP 31014158 2023.05 , Revision 1

#### 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Permeability to CO <sub>2</sub>	S <sub>D</sub> > 50 m	System 2+	EN 1504-2:2004
Permeability to water vapour	Class I, S <sub>D</sub> < 5 m	System 2+	
Capillary absorption and permeability to water	w < 0.1 kg/m <sup>2</sup> ·h <sup>0.5</sup>	System 2+	
Adhesion strength by pull off test	≥ 1.0 MPa	System 2+	
Dangerous substances	comply with 5.3	System 2+	
Reaction to fire	Class B-s1,d0	System 3	

#### 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Angeliki Zacharopoulou Function: QEHS Manager At Athens on 22 May 2023

Name : Stamatis Antonakos Function: Target Market Manager Waterproofing/Roofing At Athens on 22 May 2023

End of information as required by Regulation (EU) No 305/2011



**BUILDING TRUST** 

Declaration of Performance SikaFill®-90 MP 31014158 2023.05 , Revision 1

23	
Sika Hellas ABEE, At	thens - Greece
DoP No. 310	014158
EN 1504-2	:2004
Natified Pod	ly 1128
Notified Bod	
Surface protection pr Principle 1 (Protection agains Principle 2 (Moisture control) – Method 2.3 and Pr	oduct – Coating st ingress) – Method 1.3
Surface protection pr Principle 1 (Protection agains	oduct – Coating st ingress) – Method 1.3
Surface protection pr Principle 1 (Protection agains Principle 2 (Moisture control) – Method 2.3 and Pr	roduct – Coating st ingress) – Method 1.3 rinciple 8 (Increasing resistivity) – Method 8.3
Surface protection pr Principle 1 (Protection agains Principle 2 (Moisture control) – Method 2.3 and Pr Permeability to CO <sub>2</sub>	roduct – Coating st ingress) – Method 1.3 rinciple 8 (Increasing resistivity) – Method 8.3 
Surface protection pr Principle 1 (Protection agains Principle 2 (Moisture control) – Method 2.3 and Pr Permeability to CO <sub>2</sub> Permeability to water vapour	roduct – Coating st ingress) – Method 1.3 rinciple 8 (Increasing resistivity) – Method 8.3 $S_D > 50 \text{ m}$ Class I, $S_D < 5 \text{ m}$
Surface protection pr Principle 1 (Protection agains Principle 2 (Moisture control) – Method 2.3 and Pr Permeability to CO <sub>2</sub> Permeability to water vapour Capillary absorption and permeability to water	roduct – Coating st ingress) – Method 1.3 rinciple 8 (Increasing resistivity) – Method 8.3 S <sub>D</sub> > 50 m Class I, S <sub>D</sub> < 5 m w < 0.1 kg/m <sup>2</sup> ·h <sup>0.5</sup>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

### LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance SikaFill®-90 MP 31014158 2023.05 , Revision 1





Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr

Declaration of Performance SikaFill®-90 MP 31014158 2023.05 , Revision 1



**BUILDING TRUST**