

Revision Date: 04.02.2022 Date of last issue: - Version 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name

: Sika Boom<sup>®</sup>-S

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Polyurethane foam

#### 1.3 Details of the supplier of the safety data sheet

Company name of supplier	:	Sika Hellas ABEE
		15 Protomagias Street
		145 68 Kryoneri / Athens
Telephone	:	+30 210 81 60 600
Telefax	:	+30 210 81 60 606
E-mail address of person	:	EHS@gr.sika.com
responsible for the SDS		-

#### 1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated. Skin irritation, Category 2 H315: Causes skin irritation. Eye irritation, Category 2 H319: Causes serious eye irritation. Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin sensitisation, Category 1 H317: May cause an allergic skin reaction. Carcinogenicity, Category 2 H351: Suspected of causing cancer. Specific target organ toxicity - single ex-H335: May cause respiratory irritation. posure, Category 3, Respiratory system Specific target organ toxicity - repeated H373: May cause damage to organs through proexposure, Category 2 longed or repeated exposure if inhaled. 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word

: Danger

## Sika Boom<sup>®</sup>-S

Revision Date: 04.02.2022 Date of last issue: -



te of last issue: -		V	ersion 1.0	Print Date 04.02.202
Hazard statements	:	H222 H229 H315	Extremely flammable aerosol. Pressurised container: May burs Causes skin irritation.	st if heated.
		H317	May cause an allergic skin reac	tion.
		H319	Causes serious eye irritation.	
		H334	May cause allergy or asthma sy breathing difficulties if inhaled.	mptoms or
		H335	May cause respiratory irritation.	
		H351	Suspected of causing cancer.	
		H373	May cause damage to organs the longed or repeated exposure if it	<b>.</b>
Precautionary statements	:	P101	If medical advice is needed, hav container or label at hand.	/e product
		P102	Keep out of reach of children.	
		Prevention:		
		P202	Do not handle until all safety pre have been read and understood	
		P210	Keep away from heat, hot surface open flames and other ignition s smoking.	
		P211	Do not spray on an open flame tion source.	or other igni-
		P251	Do not pierce or burn, even afte	er use.
		P260	Do not breathe dust or mist.	
		P271	Use only outdoors or in a well-veea.	entilated ar-
		P280	Wear protective gloves/ protecti eye protection/ face protection.	ve clothing/
		Response:		
		P304 + P340 + I	P312 IF INHALED: Remove pe air and keep comfortable for bre POISON CENTER/ doctor if you	eathing. Call a
		P342 + P311	If experiencing respiratory symp POISON CENTER/ doctor.	otoms: Call a
		Storage:		
		P405	Store locked up.	
		P410 + P412	Protect from sunlight. Do not ex peratures exceeding 50 °C/ 122	
		Disposal:		
		P501	Dispose of contents/container in with local regulation.	accordance

Version 1.0

#### Hazardous components which must be listed on the label:

Diphenylmethanediisocyanate, isomeres and homologues

#### Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

## Sika Boom<sup>®</sup>-S

Version 1.0



Revision Date: 04.02.2022 Date of last issue: -

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Diphenylmethanediisocyanate, isomeres and homologues	9016-87-9 Not Assigned	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 $\longrightarrow$ specific concentration limit Eye Irrit. 2; H319 >= 5 % Resp. Sens. 1; H334 >= 0,1 % Skin Irrit. 2; H315 >= 5 % STOT SE 3; H335 >= 5 %	>= 10 - < 20

# Sika Boom®-S



Revision Date: 04.02.2022 Date of last issue: - Version 1.0

isobutane	75-28-5 200-857-2 01-2119485395-27- XXXX	Flam. Gas 1; H220	>= 5 - < 10
Reaction products of phosphoryl trichloride and methyloxirane	1244733-77-4 807-935-0 01-2119486772-26- XXXX	Acute Tox. 4; H302	>= 5 - < 10
Substances with a workplace expo	sure limit :		
dimethyl ether	115-10-6 204-065-8 01-2119472128-37- XXXX	Flam. Gas 1; H220	>= 5 - < 10
propane	74-98-6 200-827-9 01-2119486944-21- XXXX	Flam. Gas 1; H220	>= 2,5 - < 5

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air.
In case of skin contact	<ul> <li>Take off contaminated clothing and shoes immediately.</li> <li>Wash off with soap and plenty of water.</li> <li>If symptoms persist, call a physician.</li> </ul>
In case of eye contact	<ul> <li>Immediately flush eye(s) with plenty of water.</li> <li>Remove contact lenses.</li> <li>Keep eye wide open while rinsing.</li> <li>If eye irritation persists, consult a specialist.</li> </ul>
If swallowed	<ul> <li>Do not induce vomiting without medical advice.</li> <li>Rinse mouth with water.</li> <li>Do not give milk or alcoholic beverages.</li> <li>Never give anything by mouth to an unconscious person.</li> </ul>
4.2 Most important symptom	s and effects, both acute and delayed
Symptoms	: Asthmatic appearance Cough Respiratory disorder Allergic reactions Excessive lachrymation Erythema Dermatitis

# Sika Boom<sup>®</sup>-S



Revision Date: 04.02.2022 Date of last issue: -		Version 1.0	Print Date 04.02.2
		See Section 11 for more detailed information on and symptoms.	health effects
Risks	:	irritant effects sensitising effects	
		Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breat ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged exposure if inhaled.	-
4.3 Indication of any immediate	me	dical attention and special treatment needed	
Treatment	:	Treat symptomatically.	
SECTION 5: Firefighting mea	asur	es	
SECTION 5: Firefighting mea 5.1 Extinguishing media Suitable extinguishing media	. :	Water spray jet Dry powder Foam Carbon dioxide (CO2)	
SECTION 5: Firefighting mea		Water spray jet Dry powder Foam	
SECTION 5: Firefighting mea 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing	:	Water spray jet Dry powder Foam Carbon dioxide (CO2) High volume water jet	
SECTION 5: Firefighting mea 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing media	n the	Water spray jet Dry powder Foam Carbon dioxide (CO2) High volume water jet	
<ul> <li>SECTION 5: Firefighting mea</li> <li>5.1 Extinguishing media         <ul> <li>Suitable extinguishing media</li> </ul> </li> <li>Unsuitable extinguishing media</li> <li>5.2 Special hazards arising from Hazardous combustion products</li> <li>5.3 Advice for firefighters</li> </ul>	: : - :	Water spray jet Dry powder Foam Carbon dioxide (CO2) High volume water jet <b>e substance or mixture</b> Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid) Chlorine compounds	
<ul> <li>SECTION 5: Firefighting mea</li> <li>5.1 Extinguishing media</li> <li>Suitable extinguishing media</li> <li>Unsuitable extinguishing media</li> <li>5.2 Special hazards arising from Hazardous combustion products</li> </ul>	: : - :	Water spray jet Dry powder Foam Carbon dioxide (CO2) High volume water jet <b>e substance or mixture</b> Carbon dioxide (CO2) Carbon monoxide Nitrogen oxides (NOx) Hydrogen cyanide (hydrocyanic acid)	g apparatus.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Revision Date: 04.02.2022	Version 1.0	Print Date 04.0
Date of last issue: -		

Deny access to unprotected persons.

### 6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system.
		If the product contaminates rivers and lakes or drains inform
		respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Allow to solidify, use mechanical handling equipment.

### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

	Advice on safe handling :		Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asth- ma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the ap- plication area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Follow standard hygiene measures when handling chemical products
	Advice on protection against : fire and explosion		Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Do not spray on a naked flame or any incandescent material. Take precautionary measures against electrostatic discharges.
	Hygiene measures :		Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.
7.2	Conditions for safe storage, inc	clu	iding any incompatibilities
	Requirements for storage : areas and containers		BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Store in accordance with local regulations.
	Further information on stor- :		No decomposition if stored and applied as directed.

Print Date 04.02.2022

Revision Date: 04.02.2022 Date of last issue: - Version 1.0

# age stability

## 7.3 Specific end use(s)

Specific use(s)

: Cleaning with aprotic polar solvents must be avoided. Consult most current local Product Data Sheet prior to any use.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parame-	Basis *
		of exposure)	ters *	
dimethyl ether	115-10-6	TWA	1.000 ppm	2000/39/EC
			1.920 mg/m3	
	Further informa	ation: Indicative		
		TWA	1.000 ppm	GR OEL
			1.920 mg/m3	
propane	74-98-6	TWA	1.000 ppm	GR OEL
			1.800 mg/m3	

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

#### Engineering measures

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye protection : Hand protection :	Safety glasses with side-shields conforming to EN166 Eye wash bottle with pure water Chemical-resistant, impervious gloves complying with an ap- proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu- facturer specifications.
	Suitable for short time use or protection against splashes: Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed. Suitable for permanent exposure: Viton gloves (0.4 mm), breakthrough time >30 min.
Skin and body protection :	Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers).
Respiratory protection :	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work- ing limits of the selected respirator. organic vapor (Type A) and particulate filter A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

<b>Jika</b> ®
Print Date 04.02.2022

Revision Date: 04.02.2022 Date of last issue: -	Version 1.0	Print Date 04.02.2

P1: Inert material; P2, P3: hazardous substances Ensure adequate ventilation, especially in confined areas. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

#### Environmental exposure controls

General advice

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

information on basic physical	all	u chemical properties
Physical state	:	aerosol
Colour	:	various
Odour	:	ether-like
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flammability	:	Extremely flammable aerosol.
Upper/lower flammability or e	exp	losive limits
Upper explosion limit / Up- per flammability limit	-	
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
рН	:	Not applicable substance/mixture reacts with water
Viscosity		
Viscosity, kinematic	:	Not applicable
Solubility(ies)		
Water solubility	:	No data available
Water Solubility	•	
Partition coefficient: n- octanol/water	:	No data available
Vapour pressure	:	5100 hPa

# Sika Boom<sup>®</sup>-S



Revision Date: 04.02.2022 Date of last issue: -		Version 1.0	Print Date 04.02.202
Density	:	ca. 0,95 g/cm3 (23 °C)	
Relative vapour density	:	No data available	
Particle characteristics	:	No data available	
<b>9.2 Other information</b> No data available			
SECTION 10: Stability and r	eacti	vity	
<b>10.1 Reactivity</b> No dangerous reaction know	vn un	der conditions of normal use.	
<b>10.2 Chemical stability</b> The product is chemically st	able.		
10.3 Possibility of hazardous r	eactio		
Hazardous reactions	:	Stable under recommended storage conditions.	
10.4 Conditions to avoid			
Conditions to avoid	:	Heat, flames and sparks.	
10.5 Incompatible materials			
Materials to avoid	:	Oxidizing agents	
<b>10.6 Hazardous decomposition</b> No decomposition if stored a	-		
SECTION 11: Toxicological	infor	mation	
11.1 Information on hazard cla	sses	as defined in Regulation (EC) No 1272/2008	
Acute toxicity Not classified based on avai	lable	information.	
Components:			
Diphenylmethanediisocya Acute oral toxicity	nate, :	isomeres and homologues: LD50 Oral (Rat): > 10.000 mg/kg	

Acute inhalation toxicity	:	LC50: 1,5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement Assessment: The component/mixture is moderately toxic after short term inhalation.

# Sika Boom<sup>®</sup>-S



Revision Date: 04.02.2022 Date of last issue: -	Version 1.0	Print Date 04.02.2
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 9.400 mg/kg	
Reaction products of phos	sphoryl trichloride and methyloxirane:	
Acute oral toxicity	: LD50 Oral (Rat): > 630 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): > 7 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 5.000 mg/kg	
Skin corrosion/irritation Causes skin irritation.		
Serious eye damage/eye in Causes serious eye irritatior		
Respiratory or skin sensit	isation	
<b>Skin sensitisation</b> May cause an allergic skin r	eaction.	
Respiratory sensitisation		
May cause allergy or asthma	a symptoms or breathing difficulties if inhaled.	
Germ cell mutagenicity Not classified based on avai	ilable information.	
Carcinogenicity Suspected of causing cance	er.	
Reproductive toxicity		
Not classified based on avai	ilable information.	
STOT - single exposure May cause respiratory irritat	ion.	
STOT - repeated exposure May cause damage to organ	e ns through prolonged or repeated exposure if inh	naled.
Aspiration toxicity Not classified based on avail	ilable information.	
11.2 Information on other haza	rds	
Endocrine disrupting prop	perties	
Product:		
Assessment	<ul> <li>The substance/mixture does not contain of ered to have endocrine disrupting propert REACH Article 57(f) or Commission Deleg (EU) 2017/2100 or Commission Regulation levels of 0.1% or higher.</li> </ul>	ies according to gated regulation

<b>Jika</b> ®
Print Date 04.02.2022

Revision Date: 04.02.2022 Date of last issue: - Version 1.0

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Components:				
Diphenylmethanediisocyanate	, isomeres and homologues:			
Toxicity to fish :	LC50 (Brachydanio rerio (zebrafish)): > 1.000 mg/l Exposure time: 96 h			
Toxicity to algae/aquatic : plants	EC50 (Desmodesmus subspicatus (green algae)): > 1.640 mg/l Exposure time: 72 h			
Reaction products of phospho	ryl trichloride and methyloxirane:			
Toxicity to algae/aquatic : plants	EC50 (Pseudokirchneriella subcapitata (green algae)): 82 mg/l Exposure time: 72 h Method: OECD Test Guideline 201			
	NOEC (Pseudokirchneriella subcapitata (green algae)): 13 mg/l Exposure time: 72 h Method: OECD Test Guideline 201			
Toxicity to daphnia and other : aquatic invertebrates (Chron- ic toxicity)	NOEC: 32 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 202			

#### 12.2 Persistence and degradability

No data available

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

```
Assessment
```

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

#### 12.6 Endocrine disrupting properties

#### Product:

Assessment
------------

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to

# Sika Boom®-S



Revision Date: 04.02.2022	Version 1.0	Print Date (
Date of last issue: -		

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

Additional ecological infor- : There is no data available for this product. mation

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	<ul> <li>The generation of waste should be avoided or minimized wherever possible.</li> <li>Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.</li> <li>Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.</li> <li>Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.</li> <li>Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.</li> </ul>
European Waste Catalogue	: 16 05 04* gases in pressure containers (including halons) containing dangerous substances
	: 08 05 01* waste isocyanates
Contaminated packaging	<ul> <li>15 01 10* packaging containing residues of or contaminated by dangerous substances</li> </ul>

### **SECTION 14: Transport information**

#### 14.1 UN number

ADR	:	UN 1950
IMDG	:	UN 1950
ΙΑΤΑ	:	UN 1950
14.2 UN proper shipping name		
ADR	:	AEROSOLS
IMDG	:	AEROSOLS
ΙΑΤΑ	:	Aerosols, flammable

Revision Date: 04.02.2022 Date of last issue: -



Version 1.0

14.3 Transport hazard class(es)								
	ADR	:	2					
	IMDG	:	2.1					
	ΙΑΤΑ	:	2.1					
14.4	Packing group							
	ADR Packing group Classification Code Labels Tunnel restriction code Remarks	:	Not assigned by regulation 5F 2.1 (D) Transport according to chapter 3.4 (LQ) possible					
	<b>IMDG</b> Packing group Labels EmS Code	:	Not assigned by regulation 2.1 F-D, S-U					
	IATA (Cargo) Packing instruction (cargo aircraft) Packing instruction (LQ) Packing group Labels	:	203 Y203 Not assigned by regulation Flammable Gas					
	IATA (Passenger) Packing instruction (passen- ger aircraft) Packing instruction (LQ) Packing group Labels	:	203 Y203 Not assigned by regulation Flammable Gas					
14.5	5 Environmental hazards							
	<b>ADR</b> Environmentally hazardous	:	no					
	IMDG Marine pollutant	:	no					
	IATA (Passenger) Environmentally hazardous	:	no					
	<b>IATA (Cargo)</b> Environmentally hazardous	:	no					

#### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Print Date 04.02.2022

Revision Date: 04.02.2022 Date of last issue: - Version 1.0

## **SECTION 15: Regulatory information**

15.1	1 Safety, health and environment	tal regulations/legislat	ion	specific for the substance or mixture			
	REACH - Restrictions on the mar the market and use of certain dar mixtures and articles (Annex XVII	ngerous substances,		Conditions of restriction for the fol- lowing entries should be considered:			
	X X	,		Diphenylmethanediisocyanate, iso- meres and homologues (Number on list 74, 56)			
	International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors			Not applicable			
	REACH - Candidate List of Subst Concern for Authorisation (Article	e 59). ject to authorisation		None of the components are listed (=> 0.1 %).			
	REACH - List of substances subjection (Annex XIV)			Not applicable			
	Regulation (EC) No 1005/2009 or plete the ozone layer			Not applicable			
	Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)			Not applicable			
	Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals			Not applicable			
	REACH Information:	All substances contained in our Products are - registered by our upstream suppliers, and/or					
		<ul> <li>registered by us, and/or</li> <li>excluded from the regulation, and/or</li> </ul>					
	- exempted from the registration.						
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the contro jor-accident hazards involving dangerous substances.							
	P3a	FLAMMABLE AEROS	OLS				
	Volatile organic compounds :	Law on the incentive ta (VOCV)		or volatile organic compounds			

Volatile organic compounds (VOC) content: 22,81% w/w Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 22,81% w/w

Other regulations:

75/324/EEC

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Revision Date: 04.02.2022 Date of last issue: - Version 1.0



### **SECTION 16: Other information**

### Full text of H-Statements

H220 H302 H315 H317 H319 H332 H334 H335 H351 H373		Extremely flammable gas. Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficul- ties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure if inhaled.
Full text of other abbreviation	ns	
Acute Tox.		Acute toxicity
Carc.	:	Carcinogenicity
	:	
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Resp. Sens.	•	Respiratory sensitisation
Skin Irrit.	•	Skin irritation
Skin Sens.	÷	Skin sensitisation
STOT RE	•	Specific target organ toxicity - repeated exposure
STOT SE	÷	Specific target organ toxicity - single exposure
2000/39/EC	•	Europe. Commission Directive 2000/39/EC establishing a first
	_	list of indicative occupational exposure limit values
GR OEL	•	Greece. Exposure limit values
2000/39/EC / TWA	÷	Limit Value - eight hours
GR OEL / TWA	•	Long term exposure limit
ADR	:	European Agreement concerning the International Carriage of
		Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dosis (the amount of a material, given all at
		once, which causes the death of 50% (one half) of a group of
		test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in
		air that kills 50% of the test animals during the observation
		period)
MARPOL	:	International Convention for the Prevention of Pollution from
		Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament
		and of the Council of 18 December 2006 concerning the Reg-



Revision Date: 04.02.2022 Date of last issue: -	Version 1	Print Date 04.02.202		
SVHC vPvB	<ul> <li>istration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency</li> <li>Substances of Very High Concern</li> <li>Very persistent and very bioaccumulative</li> </ul>			
Further information				
Classification of the mixture	):	Classification procedu	ire:	
Aerosol 1	H222, H229	Based on product data	or assessment	
Skin Irrit. 2	H315	Calculation method		
Eye Irrit. 2	H319	Calculation method		
Resp. Sens. 1	H334	Calculation method		
Skin Sens. 1	H317	Calculation method		
Carc. 2	H351	Calculation method		

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Calculation method

Calculation method

Changes as compared to previous version !

H335

H373

GR / EN

STOT SE 3

STOT RE 2