

Sikaplan® WP 1100-15 HL

Declaration of Performance No 89013897

1	Unique identification code of the product-type:	89013897
2	Intended use/es:	Damp proofing in buildings, including basement tanking subject to reaction to fire — Plastic and rubber sheets Damp proofing in buildings, including basement tanking — Plastic and rubber sheets
3	Manufacturer:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	System/s of AVCP:	System 3 (Damp proofing in buildings, including basement tanking subject to reaction to fire) System 2+ (Damp proofing in buildings, including basement tanking)
6a	Harmonised standard:	EN 13967:2012
	Notified body/ies:	1213

Declaration of Performance

Sikaplan® WP 1100-15 HL

89013897

26/03/2024 1

1011

1 / 3

7 Declared performance/s:

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	EN 13967:2012
Watertightness	Pass	System 2+	
Tear resistance	Longitudinal (MD) ≥ 400 N	System 2+	
	Transversal (CMD) ≥ 400 N		
Joint strength	> 750 N/50mm	System 2+	
Impact resistance	Method A, Hard support ≥ 750 mm	System 2+	
	Method B, Soft support ≥ 750 mm		
Tensile strength	Tensile strength, Longitudinal (MD) $17 \text{ N/mm}^2 \pm 2 \text{ N/mm}^2$	System 2+	
	Tensile strength, Transversal (CMD) $16 \text{ N/mm}^2 \pm 2 \text{ N/mm}^2$		
Resistance to static loading	≥ 20 kg	System 2+	
Durability	Durability of watertightness against ageing Pass	System 2+	
	Durability of watertightness against chemicals (calcium hydroxide) Pass		
Dangerous substances	NPD	System 2+	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomek Gutowski
 Function: Corporate Product Certification Manager
 At Warsaw on 2024-03-26

Name: Wiktor Karpala
 Function: Data Processing Specialist CTD
 At Warsaw on 2024-03-26




End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

Sikaplan® WP 1100-15 HL

89013897

26/03/2024 1

1011



CE

23

Sika Services AG, Zürich, Switzerland

89013897

Reaction to fire	Class E	
Tear resistance	Longitudinal (MD)	≥ 400 N
	Transversal (CMD)	≥ 400 N
Joint strength	> 750 N/50mm	
Impact resistance	Method A, Hard support	≥ 750 mm
	Method B, Soft support	≥ 750 mm
Tensile strength	Tensile strength, Longitudinal (MD)	17 N/mm ² ± 2 N/mm ²
	Tensile strength, Transversal (CMD)	16 N/mm ² ± 2 N/mm ²
Resistance to static loading	≥ 20 kg	

EN 13967:2012

1213

Damp proofing in buildings, including basement tanking subject to reaction to fire — Plastic and rubber sheets
Damp proofing in buildings, including basement tanking — Plastic and rubber sheets

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY (REACH)

For information and advice on the safe handling, storage and use of this product, users shall refer to the most recent Product Data Sheet (PDS).

LEGAL NOTES

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sikaplan® WP 1100-15 HL

89013897

26/03/2024 1

1011

3 / 3

BUILDING TRUST

