

## TAPES AND LABELS ADHESIVES SELECTOR GUIDE



## SikaMelt® ADHESIVES SELECTOR GUIDE

Tape and label producers demand high performance hot melt pressure sensitive adhesives for self adhesion coatings, labels, high performance technical and hygienic tapes.

SikaMelt® wide range of HM-PSA adhesives are designed to fulfill the needs, whether it is high tack, high SAFT, excellent low service temperature or heat resistance, Sika has solutions with a broad adhesion spectrum.





Adhesive	Type	Viscosity at 160°C	Tack	Application
SikaMelt®-9200	HM-PSA	17,000 mPa.s	- <del></del> High	Tapes and self adhesion coatings with low service temperature demands
SikaMelt®-9230	HM-PSA	18,000 mPa.s	High	Tapes with high tack and balanced SAFT performance
SikaMelt®-9209	HM-PSA	12,000 mPa.s	High	Tapes and self adhesion coatings with a high demand for heat resistance and low service temperature
SikaMelt®-9209 HT	HM-PSA	13,000 mPa.s	High	High performance tapes and self adhesion coatings with high heat resistance and very low service temperature demands
SikaMelt®-9255	HM-PSA	30,000 mPa.s	Removable	Removable tapes and self adhesion coatings such as masking tapes
SikaMelt®-9255 CV	HM-PSA	22,000 mPa.s	Medium	Very clear adhesive for self adhesion coatings that require a medium tack level
SikaMelt®-9285 HT	HM-PSA	40,000 mPa.s	Medium	High performance tapes and assembly that require a low service temperature
SikaMelt®-9289	HM-PSA	 20,000 mPa.s	Medium	High performance tapes and assembly with lower viscosity
SikaMelt®-9285	HM-PSA	25,000 mPa.s (at 180°C)	Medium	High performance tapes and assembly
SikaMelt®-9287 UV	HM-PSA	25,000 mPa.s (at 180°C)	Medium	High performance assembly with a very high SAFT performance

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.







