

Sikafloor®-2100

DECLARATION OF PERFORMANCE

No. 32897084

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	32897084
2	INTENDED USE/S	EN 13813:2002 Synthetic resin screed for internal uses
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4 System 3

EN 13813:2002

0099

HARMONISED STANDARD:

Notified body/ies:

Sikafloor®-2100 32897084 2018.05, ver. 1 1053

6a

7 DECLARED PERFORMANCE/S


Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire:	B _{fl} s1	System 3	
Release of corrosive substances:	SR	System 4	
Water permeability:	$w < 0.1 \text{ kg/(m}^2 \text{ x h}^{0.5})$	System 4	
Wear resistance:	AR 0.4	System 4	
Bond strength:	B 3.0	System 4	
Impact resistance:	IR 24.5	System 4	— EN — 13813:2002
Sound insulation:	NPD	System 4	13013.2002
Sound absorption:	NPD	System 4	<u> </u>
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis Function: TMM Flooring At Athens on 03 March 2020 Name: Alexandros Melissourgos Function: Technical Manager At Athens on 03 March 2020



RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikafloor®-2100	EN 1504-2:2004	75917624

Declaration of Performance Sikafloor®-2100 32897084 2018.05, ver. 1 1053



16

Sika Services AG, Zurich, Switzerland

DoP No. 32897084

EN 13813:2002

Notified Body 0099

Synthetic resin screed for internal uses

Reaction to fire: B_{f} s1 Release of corrosive substances: SR

Water permeability: $w < 0.1 \text{ kg/(m}^2 \text{ x h}^{0.5})$

Wear resistance: AR 0.4
Bond strength: B 3.0
Impact resistance: IR 24.5

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.







Sika Hellas ABEE

Protomagias 15 14568 Kryoneri Attica - Greece www.sika.gr

Declaration of Performance

Sikafloor®-2100 32897084 2018.05, ver. 1 1053

