



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : EVERBUILD TEAK OIL

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Surfaces protection

### 1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE  
15 Protomagias Street  
145 68 Kryoneri / Athens  
Telephone : +30 210 81 60 600  
Telefax : +30 210 81 60 606  
E-mail address of person : EHS@gr.sika.com  
responsible for the SDS

### 1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 1, Central nervous system	H372: Causes damage to organs through prolonged or repeated exposure if inhaled.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

## EVERBUILD TEAK OIL



Revision Date: 09.05.2023  
Date of last issue: 28.04.2023

Version 2.1

Print Date 09.05.2023

Hazard statements	:	H226 H304 H317 H336 H372  H411	Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause drowsiness or dizziness. Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled. Toxic to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066	Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	P101 P102 <b>Prevention:</b> P210  P260 P271 P280  <b>Response:</b> P301 + P310  P331 P370 + P378	If medical advice is needed, have product container or label at hand. Keep out of reach of children.  Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.  IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Do NOT induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
		<b>Storage:</b> P405	Store locked up.
		<b>Disposal:</b> P501	Dispose of contents/container in accordance with local regulation.

### Hazardous components which must be listed on the label:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)  
dipentene

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Not Assigned 919-446-0 265-185-4 01-2119458049-33-XXXX [corresponding group CAS 64742-82-1]	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT RE 1; H372 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 50 - <= 100
dipentene	138-86-3 205-341-0	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 1 - < 2,5

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.



#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.  
Allergic reactions  
Erythema  
Loss of balance  
Vertigo  
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Risk of serious damage to the lungs (by aspiration).  
sensitising effects
- May be fatal if swallowed and enters airways.  
May cause an allergic skin reaction.  
May cause drowsiness or dizziness.  
Causes damage to organs through prolonged or repeated exposure if inhaled.  
Repeated exposure may cause skin dryness or cracking.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
- 

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : Water  
High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.  
Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known

#### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This



must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Remove all sources of ignition.  
Deny access to unprotected persons.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 6.4 Reference to other sections

For personal protection see section 8.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharge.  
Open drum carefully as content may be under pressure.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).  
Follow standard hygiene measures when handling chemical products



## EVERBUILD TEAK OIL

Revision Date: 09.05.2023  
Date of last issue: 28.04.2023

Version 2.1

Print Date 09.05.2023

- Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.
- Further information on storage stability : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters *	Basis *
------------	---------	-------------------------------	----------------------	---------

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Personal protective equipment

- Eye/face protection : Safety glasses with side-shields conforming to EN166  
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:  
Butyl rubber/nitrile rubber gloves (> 0,1 mm)  
Contaminated gloves should be removed.
- Suitable for permanent exposure:  
Viton gloves (0.4 mm),  
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : No special measures required.

#### Environmental exposure controls

- General advice : Prevent product from entering drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.



---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : liquid  
Colour : brown  
Odour : hydrocarbon-like

Melting point/range / Freezing point : No data available

Initial boiling point and boiling range : 158 - 191 °C

Flammability (solid, gas) : No data available

#### Upper/lower flammability or explosive limits

Upper explosion limit / Upper flammability limit : 7 %(V)

Lower explosion limit / Lower flammability limit : 0,7 %(V)

Flash point : ca. 40 °C

Auto-ignition temperature : 235 °C

Decomposition temperature : No data available

pH : Not applicable

#### Viscosity

Viscosity, dynamic : 33 - 38 mPa.s

Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

#### Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 1,9 hPa

Density : ca. 0,82 g/cm<sup>3</sup> (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available



**9.2 Other information**

No data available

---

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

The product is chemically stable.

**10.3 Possibility of hazardous reactions**

Hazardous reactions : Stable under recommended storage conditions.  
Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Conditions to avoid : Heat, flames and sparks.

**10.5 Incompatible materials**

Materials to avoid : Strong acids and oxidizing agents  
No data available

**10.6 Hazardous decomposition products**

Hazardous decomposition products : Carbon monoxide  
Aldehydes  
Hydrocarbons  
Carbon dioxide (CO<sub>2</sub>)

---

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Not classified based on available information.

**Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

**Components:**

**Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%):**

Assessment : Repeated exposure may cause skin dryness or cracking.  
Result : Repeated exposure may cause skin dryness or cracking.

---





**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitisation**

**Skin sensitisation**

May cause an allergic skin reaction.

**Respiratory sensitisation**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

May cause drowsiness or dizziness.

**STOT - repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

**Aspiration toxicity**

May be fatal if swallowed and enters airways.

**11.2 Information on other hazards**

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

No data available

**12.2 Persistence and degradability**

No data available

**12.3 Bioaccumulative potential**

No data available

**12.4 Mobility in soil**

No data available

**12.5 Results of PBT and vPvB assessment**

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..



**12.6 Endocrine disrupting properties**

No data available

**12.7 Other adverse effects**

**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

- Product : The generation of waste should be avoided or minimized wherever possible.  
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.  
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.  
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- European Waste Catalogue : 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances
- Contaminated packaging : 15 01 10\* packaging containing residues of or contaminated by dangerous substances

---

**SECTION 14: Transport information**

**14.1 UN number or ID number**

- ADR : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

**14.2 UN proper shipping name**

- ADR : PAINT  
IMDG : PAINT  
IATA : Paint

**14.3 Transport hazard class(es)**

## EVERBUILD TEAK OIL



Revision Date: 09.05.2023  
Date of last issue: 28.04.2023

Version 2.1

Print Date 09.05.2023

	Class	Subsidiary risks
<b>ADR</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

<b>ADR</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)
Remarks	: Transport according to 2.2.3.1.4 ADR.

<b>IMDG</b>	
Packing group	: III
Labels	: 3
EmS Code	: F-E, S-E
Remarks	: Transport according to 2.3.2.2 IMDG.

<b>IATA (Cargo)</b>	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids
Remarks	: Transport according to 3.3.3.1.1 IATA.

<b>IATA (Passenger)</b>	
Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids

### 14.5 Environmental hazards

<b>ADR</b>	
Environmentally hazardous	: yes

<b>IMDG</b>	
Marine pollutant	: yes

<b>IATA (Passenger)</b>	
Environmentally hazardous	: yes

<b>IATA (Cargo)</b>	
Environmentally hazardous	: yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



---

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable for product as supplied.

---

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed  
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH Information: All substances contained in our Products are  
- registered by our upstream suppliers, and/or  
- registered by us, and/or  
- excluded from the regulation, and/or  
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)  
Volatile organic compounds (VOC) content: 61% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content:  
61% w/w, 500,2 g/l  
VOC content excluding water

**15.2 Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this mixture by the supplier.



---

## SECTION 16: Other information

### Full text of H-Statements

H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H336	:	May cause drowsiness or dizziness.
H372	:	Causes damage to organs through prolonged or repeated exposure if inhaled.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Flam. Liq.	:	Flammable liquids
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

### Further information

**Classification of the mixture:**

**Classification procedure:**

**EVERBUILD TEAK OIL**



Revision Date: 09.05.2023  
Date of last issue: 28.04.2023

Version 2.1

Print Date 09.05.2023

---

Flam. Liq. 3	H226	On basis of test data.
Skin Sens. 1	H317	Calculation method
STOT SE 3	H336	Calculation method
STOT RE 1	H372	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

GR / EN