

Sika[®] ViscoCrete[®]-400

DECLARATION OF PERFORMANCE No. 59921059

| | | |
|----|--|---|
| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE: | 59921059 |
| 2 | INTENDED USE/S: | EN934-2:2009+A1:2012 To be used in concrete High range water reducing / Superplasticizing admixture (Tables 3.1 & 3.2) Set retarding / High range water reducing / Super plasticizing admixture (Tables 11.1 & 11.2) |
| 3 | MANUFACTURER: | Sika Hellas ABEE 15 Protomagias Str. GR 145 68 Kryoneri Athens - Greece www.sika.gr |
| 4 | AUTHORISED REPRESENTATIVE: | |
| 5 | SYSTEM/S OF AVCP: | System 2+ |
| 6a | HARMONISED STANDARD: | EN934-2:2009+A1:2012 |
| | Notified body/ies: | 1128 |

Declaration of Performance

Sika[®] ViscoCrete[®]-400

59921059

2016.10 , Revision 1

7 DECLARED PERFORMANCE/S:

| Essential Characteristics | Performance | Harmonised Technical Specification | |
|-------------------------------|--|------------------------------------|--|
| Tables 3.1 & 3.2 | | | |
| Water reduction | In test mix $\geq 12\%$ compared with control mix | EN934-2:2009+A1:2012 | |
| Compressive strength | T3.1: At 1 day: Test mix $\geq 140\%$ of control mix, At 28 days: Test mix $\geq 115\%$ of control mix T3.2: At 28 days: test mix $\geq 90\%$ of control mix | | |
| Air content in fresh concrete | Test mix $\leq 2\%$ by volume above control mix | | |
| Increase in consistence | Increase in slump ≥ 120 mm from initial (30 ± 10) mm | | |
| Retention of consistence | 30 min after the addition the consistence of the test mix does not fall below the value of the initial consistence of the control mix | | |
| Tables 11.1 & 11.2 | | | |
| Compressive strength | T11.1: At 7 days: test mix $\geq 100\%$ of control mix, At 28 days: test mix $\geq 115\%$ of control mix T11.2: At 28 days: test mix $\geq 90\%$ of control mix | | |
| Setting time | Initial: test mix \geq control mix + 90 min Final: test mix \leq control mix + 360 min | | |
| Water reduction | In test mix $\geq 12\%$ compared with control mix | | |
| Air content in fresh concrete | Test mix $\leq 2\%$ by volume above control mix | | |
| Retention of consistence | 60 min after the addition the consistence of the test mix does not fall below the value of the initial consistence of the control mix | | |

Declaration of Performance

Sika® ViscoCrete®-400

59921059

2016.10 , Revision 1

| General Characteristics | Performance |
|----------------------------------|---|
| Chloride ion content | Chloride free |
| Alkali content | ≤ 3.0 % by mass |
| Corrosion behavior | Contains components only from EN934-1:2008, Annex A.1 |
| Dangerous Substances | NPD* |
| *NPD - No performance determined | |

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Manolis Mavratzotis
Function: R&D/QC Manager
At Athens on 05 October 2016

Name : Spyros Hatzifotis
Function: General Manager
At Athens on 05 October 2016

End of information as required by Regulation (EU) No 305/2011





04

Sika Hellas ABEE, Athens - Greece

59921059

EN934-2:2009+A1:2012

1128

Sika® ViscoCrete®-400

To be used in concrete

High range water reducing / Superplasticizing admixture

(Tables 3.1 & 3.2)

Set retarding / High range water reducing / Super plasticizing admixture

(Tables 11.1 & 11.2)

For essential characteristics please refer to Declaration of Performance

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sika® ViscoCrete®-400

59921059

2016.10 , Revision 1



Sika Hellas ABEE
15 Protomagias Str.
GR 145 68 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance
Sika® ViscoCrete®-400
59921059
2016.10 , Revision 1