

PRODUCT DATA SHEET

SikaDecor[®]-200 PU 2KW

2-Components transparent water based polyurethane top coat, part of SikaDecor[®] pasty decorative mortar system

DESCRIPTION

SikaDecor[®]-200 PU 2KW is a 2-components, semi matt, transparent, water based polyurethane top coat for indoor surfaces.

USES

SikaDecor[®]-200 PU 2KW may only be used by experienced professionals.

Final coat with high performance & aesthetic requirements for smooth SikaDecor[®] systems.

FEATURES

- Colourless semi matt finish
- Good UV resistance, no yellowing
- Water based

PRODUCT INFORMATION

Packaging	Container Part A	0.9 kg	3.6 kg
	Container Part B	0.1 kg	0.36 kg
	Container Part A + Part B	1 kg	3.96 kg
Colour	Part A	Milky white, liquid	
	Part B	Transparent, liquid	
Appearance and colour	Transparent, semi matt finish		
Shelf life	3 years from the date of production		
Storage conditions	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +8 °C and +30 °C. Protect from freezing. Always refer to packaging.		

APPLICATION INFORMATION

Mixing ratio	Part A : Part B	91 : 9
Consumption	~0,1 kg/m ² per layer	
Relative air humidity	<80 %	

Dew point

Beware of condensation.

The substrate and uncured applied product must be at least +3 °C above dew point to reduce the risk of condensation or blooming on the surface of the applied product. Low temperatures and high humidity conditions increase the probability of blooming.

Substrate temperature

Min.	+8 °C
Max.	+30 °C

Pot Life

~3.5 hours, at +25 °C

Waiting time to overcoating

Before overcoating SikaDecor®-200 PU 2KW with SikaDecor®-200 PU 2KW wait ~24 hours.

Before overcoating SikaDecor® 650 Paste or SikaDecor® 680 Paste Fine with SikaDecor®-200 PU 2KW wait 4 days.

Note: Times are approximate and will be affected by changing ambient conditions, particularly temperature and relative humidity.

Applied product ready for use

Dry after ~1.5 hours

Full cure after ~7 days

Note: Times are approximate and will be affected by changing ambient conditions, particularly temperature and relative humidity.

SYSTEM INFORMATION**Systems**

Coating	Product	Consumption
Floor/Wall Primer	Sikafloor®-02 Primer	0.125 kg/m²
Levelling layer	2 – 3 X SikaDecor®-650 Paste*	1.5 – 1.7 kg/mm/m²
Decorative layer	2 – 3 X SikaDecor®-680 Paste Fine	1.5 – 1.7 kg/mm/m²
Sealer for walls indoors	1 X SikaDecor®-100 AC 1KW** + 5 – 10 % water & 2 – 3 X SikaDecor®-100 AC 1KW**	~0.070 kg/m² per layer
Sealer for floors and walls indoors	1 X SikaDecor®-200 PU 2KW + 10 % water & 1 – 2 SikaDecor®-200 PU 2KW + 5 % water	~0.100 kg/m² per layer

*Glass fiber mesh for reinforcement in the first coat: Sika® Fibernet 80g/m² or Sika ThermoCoat®-4 HS 160g/m² depending on the application

**Matt, gloss or satin finish

Note: Consumption data is theoretical and does not allow for any additional material due to surface porosity, surface profile, variations in level, wastage or any other variations. Apply product to a test area to calculate the exact consumption for the specific substrate conditions and proposed application equipment.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- During application and curing process, temperature must be within the range of +8 °C to +30 °C
- Apply only on sound, prepared substrates
- Protect applied fresh material from frost, wind and direct sunlight
- Do not apply on substrates with rising moisture
- After application, protect the Product from damp, condensation and direct water contact for at least 24 hours
- For temporary heating, use only electrically powered warm air blower systems. Do not use gas, oil, paraffin or other fossil fuel heaters

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The substrate must be dry, free from dust, loose material, surface contamination such as oil, grease, old coatings.

MIXING

1. Mix Part A (resin) using an electric single paddle mixer. Mix liquid until a uniform mix has been achieved.
2. Add Part B (hardener) to Part A.
3. Mix Part A + B continuously for ~3 minutes while adding 5 % to 10 % water until a uniform mix is achieved. Note: To achieve the smoothest surface, dilute using the maximum amount of water.
IMPORTANT: Avoid excessive mixing to minimize air entrainment
4. Leave SikaDecor®-200 PU 2KW to rest for 5 minutes before application.

APPLICATION

1. Pour the mixed Product onto the substrate. Note: The consumption is specified in Application Information.
2. Apply the Product evenly over the surface with a medium pile roller.
3. Back-roll the surface in two directions at right angles with a medium-pile roller. Note: Maintain a "wet edge" during application for a seamless finish.

CLEANING OF EQUIPMENT

Removal of fresh remnants from tools and application equipment can be carried out using water immediately after use. Hardened / cured material can only be mechanically removed.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Hellas ABEE

15, Protomagias Str.
GR 145 68, Kryoneri, Attica
Tel.: +30 210 81 60 600
E-mail: info@gr.sika.com
www.sika.gr



Product Data Sheet

SikaDecor®-200 PU 2KW
October 2025, Version 01.01
020812060030000045

SikaDecor-200PU2KW-en-GR-(10-2025)-1-1.pdf