according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Date of last issue: 30.01.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Ceram EpoxyRemover

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Post treatment agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street 145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

#### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

T.

Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements : P101 If medical advice is needed, have product

container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Prevention:

P264 Wash skin thoroughly after handling.

Date of last issue: 30.01.2022

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

P280 We

Wear protective gloves/ eye protection/ face

protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.

### Hazardous components which must be listed on the label:

tetrasodium ethylene diamine tetraacetate

#### **Additional Labelling**

The data sheet for medical personnel is available at the here provided emergency address.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
benzyl alcohol	100-51-6 202-859-9 01-2119492630-38- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2; H319	>= 10 - < 20
potassium oleate	143-18-0 205-590-5	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 5 - < 10

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Version 3.1 Print Date 26.05.2022

Date of last issue: 30.01.2022

Revision Date: 26.05.2022

ethylene glycol monobutyl ether	111-76-2 203-905-0 01-2119475108-36- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 ————————————————————————————————————	>= 5 - < 10
tetrasodium ethylene diamine tetraacetate Contains: trisodium nitrilotriacetate >= 1 - <= 3 %	64-02-8 200-573-9 01-2119486762-27- XXXX	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Dam. 1; H318 STOT RE 2; H373	>= 1 - < 2,5
2-aminoethanol	141-43-5 205-483-3 01-2119486455-28- XXXX	Acute Tox. 4; H332 Acute Tox. 4; H312 Acute Tox. 4; H302 Skin Corr. 1B; H314 STOT SE 3; H335 Aquatic Chronic 3; H412 Eye Dam. 1; H318 ————————————————————————————————————	>= 1 - < 2,5

For explanation of abbreviations see section 16.

Regulation (EC) No. 648/2004, as amended

: 5 % or over but less than 15 %: Non-ionic surfactants, Soap

less than 5 %: EDTA and salts thereof

Other constituents: Perfumes

Allergens: benzyl alcohol benzyl salicylate

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Date of last issue: 30.01.2022

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Revision Date: 26.05.2022 Version 3.1 Print Date 26.05.2022

Wash off with soap and plenty of water.

If symptoms persist, call a physician.

In case of eye contact Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

**Symptoms Excessive lachrymation** 

> Erythema **Dermatitis**

See Section 11 for more detailed information on health effects

and symptoms.

Risks irritant effects

Causes skin irritation.

Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

**SECTION 5: Firefighting measures** 

5.1 Extinguishing media

Suitable extinguishing media In case of fire, use water/water spray/water jet/carbon diox-

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Standard procedure for chemical fires.

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Date of last issue: 30.01.2022

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

ance with local regulations.

Further information on stor-


age stability

: No decomposition if stored and applied as directed.

7.3 Specific end use(s)

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover



Revision Date: 26.05.2022 Date of last issue: 30.01.2022

Specific use(s)

: Consult most current local Product Data Sheet prior to any

use.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters *	Basis *		
ethylene glycol monobutyl ether	111-76-2	TWA	20 ppm 98 mg/m3	2000/39/EC		
	Further inform	Further information: Identifies the possibility of significant uptake				
		through the skin, Indicative				
		STEL	50 ppm 246 mg/m3	2000/39/EC		
		TWA	25 ppm 120 mg/m3	GR OEL		
	chemical factor	Further information: The notation 'skin' (D), pointing out certain chemical factors of the table of paragraph of 1 article 3, implies the likely contribution to of these chemical factors to the quantity				
	of exposure to	of exposure to workers which are absorbed through the skin at the direct contact with these.				
2-aminoethanol	141-43-5	TWA	1 ppm 2,5 mg/m3	2006/15/EC		
		Further information: Indicative, Identifies the possibility of significant uptake through the skin				
	,	STEL	3 ppm 7,6 mg/m3	2006/15/EC		
		TWA	1 ppm 2,5 mg/m3	GR OEL		
		Further information: The notation 'skin' (D), pointing out certain chemical factors of the table of paragraph of 1 article 3, implies				
	the likely cont	the likely contribution to of these chemical factors to the quantity				
		of exposure to workers which are absorbed through the skin at the direct contact with these.				
		STEL	3 ppm 7.6 mg/m3	GR OEL		

<sup>\*</sup>The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

#### 8.2 Exposure controls

## **Engineering measures**

Maintain air concentrations below occupational exposure standards. Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

Date of last issue: 30.01.2022

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Revision Date: 26.05.2022 Version 3.1 Print Date 26.05.2022

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

> long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection In case of inadequate ventilation wear respiratory protection.

> Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe work-

ing limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficent to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

**Environmental exposure controls** 

General advice : Try to prevent the material from entering drains or water

courses.

No special environmental precautions required.

#### **SECTION 9: Physical and chemical properties**

### 9.1 Information on basic physical and chemical properties

Physical state liauid Colour light yellow Odour characteristic

Melting point/range / Freezing :

point

No data available

No data available Boiling point/boiling range

Flammability (solid, gas) No data available

Upper/lower flammability or explosive limits

Upper explosion limit / Up- : No data available

per flammability limit

Lower explosion limit / Lower flammability limit No data available

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Flash point : ca. 65 °C

Method: closed cup

Auto-ignition temperature : Not applicable

Decomposition temperature : No data available

pH : 11 (20 °C)

Concentration: 100 %

**Viscosity** 

Viscosity, kinematic : > 7 mm2/s (40 °C)

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 23 hPa

Density : ca. 1,01 g/cm3 (20 °C)

Relative vapour density : No data available

Particle characteristics : No data available

#### 9.2 Other information

No data available

#### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

The product is chemically stable.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Date of last issue: 30.01.2022

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Not classified based on available information.

**Components:** 

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1.620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4,178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

ethylene glycol monobutyl ether:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

tetrasodium ethylene diamine tetraacetate:

Acute oral toxicity : LD50 Oral (Rat): > 1.780 mg/kg

2-aminoethanol:

Acute oral toxicity : LD50 Oral (Rat): 1.720 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.025 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Revision Date: 26.05.2022 Version 3.1 Print Date 26.05.2022

Date of last issue: 30.01.2022

## Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

#### STOT - repeated exposure

Not classified based on available information.

#### Aspiration toxicity

Not classified based on available information.

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

### **Product:**

: The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

#### **Components:**

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

aquatic invertebrates

Exposure time: 48 h

#### 12.2 Persistence and degradability

The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

#### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Date of last issue: 30.01.2022

#### 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

#### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

: There is no data available for this product.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

#### **SECTION 14: Transport information**

#### 14.1 UN number

ADR : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Revision Date: 26.05.2022 Version 3.1 Print Date 26.05.2022

Date of last issue: 30.01.2022

**ADR** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA Not regulated as a dangerous good

14.3 Transport hazard class(es)

**ADR** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good **IATA** Not regulated as a dangerous good

14.4 Packing group

**ADR** Not regulated as a dangerous good **IMDG** Not regulated as a dangerous good IATA (Cargo) Not regulated as a dangerous good IATA (Passenger) Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

None of the components are listed

(=> 0.1 %).

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

Not applicable

of dangerous chemicals

**REACH Information:** All substances contained in our Products are

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Revision Date: 26.05.2022 Version 3.1

Date of last issue: 30.01.2022

Print Date 26.05.2022

- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or - exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Volatile organic compounds Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 15,01% w/w

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 16,01% w/w

#### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

May cause respiratory irritation. H335

H373 May cause damage to organs through prolonged or repeated

exposure if inhaled.

H412 Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic Long-term (chronic) aquatic hazard

Eye Dam. Serious eye damage

Eve Irrit. Eve irritation Skin Corr. Skin corrosion Skin Irrit. Skin irritation

STOT RE Specific target organ toxicity - repeated exposure Specific target organ toxicity - single exposure STOT SE

Europe. Commission Directive 2000/39/EC establishing a first 2000/39/EC

list of indicative occupational exposure limit values

according to Regulation (EC) No. 1907/2006

## Sika® Ceram EpoxyRemover

Revision Date: 26.05.2022 Version 3.1 Print Date 26.05.2022

Date of last issue: 30.01.2022

2006/15/EC : Europe. Indicative occupational exposure limit values

GR OEL

2000/39/EC / TWA

2000/39/EC / STEL

2006/15/EC / TWA

2006/15/EC / STEL

3006/15/EC / STEL

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

#### **Further information**

Classification of the mixture: Classification procedure:

Skin Irrit. 2 H315 Calculation method Eye Dam. 1 H318 Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN

according to Regulation (EC) No. 1907/2006

# Sika® Ceram EpoxyRemover

Revision Date: 26.05.2022 Date of last issue: 30.01.2022 Version 3.1



Print Date 26.05.2022