

Sikafloor® Level-30

DECLARATION OF PERFORMANCE No. 90432755

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	90432755
2	INTENDED USE/S	EN 13813:2002 Cement based screed for interior use in buildings
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3 for Reaction to Fire System 4
6a	HARMONISED STANDARD:	EN 13813:2002
	Notified body/ies:	1139

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	A1 _{fl}	EN 13813:2002
Release of corrosive substances (cementitious screed)	CT	
Water vapour permeability	NPD	
Compressive strength	C40	
Flexural strength	F10	
Abrasion Resistance	A12	
Sound insulation	NPD	
Sound absorption	NPD	
Thermal resistance	NPD	
Chemical resistance	NPD	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Kostas Mourikis
Function: TMM Flooring
At Athens on 13 April 2020



Name: Alexandros Melissourgos
Function: Technical Manager
At Athens on 13 April 2020



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sikafloor® Level 30	EN 1504-3	365817912

Declaration of Performance

Sikafloor® Level-30
90432755
2020.04, ver. 3
1029



13

DoP No. 90432755

Sika Services AG, Zurich, Switzerland

EN 13813:2002

Notified Body 1139

Cement based screed for interior use in buildings

Reaction to fire	A1 _n
Release of corrosive substances (cementitious screed)	CT
Compressive strength	C40
Flexural strength	F10
Abrasion Resistance	A12

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikafloor® Level-30
90432755
2020.04, ver. 3
1029

3/4

BUILDING TRUST





Sika Hellas ABEE
15 Protomagias Str.
14568 Kryoneri
Athens - Greece
www.sika.gr

Declaration of Performance

Sikafloor® Level-30
90432755
2020.04 , ver. 3
1029