according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikadur® Blade Repair-30 Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Composites system

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Hellas ABEE

15 Protomagias Street 145 68 Kryoneri / Athens

Telephone : +30 210 81 60 600
Telefax : +30 210 81 60 606
E-mail address of person : EHS@gr.sika.com

responsible for the SDS

1.4 Emergency telephone number

Poison Information Center + 30 210 77 93 777

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1C H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.
Germ cell mutagenicity, Category 2 H341: Suspected of causing genetic defects.

Reproductive toxicity, Category 1B H360F: May damage fertility.

Long-term (chronic) aquatic hazard, Cat-H411: Toxic to aquatic life with long lasting effects.

egory 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Date of last issue: 12.01.2019

Precautionary statements



Prevention: P201 Obtain special instructions before use. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh P304 + P340 + P310 air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical ad-

vice/ attention.
P391 Collect spillage.

Hazardous components which must be listed on the label:

reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Trimethylolpropane triglycidylether bis-[4-(2,3-epoxipropoxi)phenyl]propane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients


3.2 Mixtures

Components

Components			
Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Registration number		
reaction product: bisphenol F-	9003-36-5	Skin Irrit. 2; H315	>= 40 - < 60
(epichlorhydrin) epoxy resin	500-006-8	Skin Sens. 1; H317	
(number average molecular	01-2119454392-40-	Aquatic Chronic 2;	
weight <= 700)	XXXX	H411	

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A



Date of last issue: 12.01.2019

Revision Date: 21.02.2021

Trimethylolpropane triglycidylether	Not Assigned 701-135-4 01-2120078341-60- XXXX	Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1B; H317 Muta. 2; H341 Repr. 1B; H360F Aquatic Chronic 2; H411	>= 25 - < 40
bis-[4-(2,3- epoxipropoxi)phenyl]propane	1675-54-3 216-823-5 01-2119456619-26- XXXX	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Eye Irrit. 2; H319 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Do not induce vomiting without medical advice.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Risks Health injuries may be delayed.

> corrosive effects sensitising effects

toxic effects for reproduction

May cause an allergic skin reaction. Causes serious eye damage.

Suspected of causing genetic defects.

May damage fertility. Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

In case of fire, use water/water spray/water jet/carbon diox-Suitable extinguishing media

ide/sand/foam/alcohol resistant foam/chemical powder for

extinction.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

ucts

Hazardous combustion prod- : No hazardous combustion products are known

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Pregnant women or women of child-bearing age should not be

exposed to this product.

Follow standard hygiene measures when handling chemical

products

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accord-

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019

ance with local regulations.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Eye wash bottle with pure water

Wear eye/face protection.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manu-

facturer specifications.

Suitable for short time use or protection against splashes:

Butyl rubber/nitrile rubber gloves (> 0,1 mm) Contaminated gloves should be removed.

Suitable for permanent exposure:

Viton gloves (0.4 mm), breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345,

long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing

and stirring work.

Respiratory protection : No special measures required.

Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : various
Odour : epoxy-like

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing : No data available

Country GR 000000120780

6/14



according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019

point

Boiling point/boiling range : No data available

> 101 °C Flash point

Method: closed cup

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower : No data available

flammability limit

Vapour pressure 0.01 hPa

Relative vapour density No data available

ca. 1,16 g/cm3 (20 °C) Density

Solubility(ies)

Water solubility insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic ca. 1.000 mPa.s (25 °C)

Viscosity, kinematic $> 20,5 \text{ mm2/s} (40 ^{\circ}\text{C})$

Explosive properties No data available

Oxidizing properties No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Trimethylolpropane triglycidylether:

Acute oral toxicity : LD50 Oral (Rat): 3.398 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Suspected of causing genetic defects.

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

SECTION 12: Ecological information

12.1 Toxicity

Components:

Trimethylolpropane triglycidylether:

Toxicity to algae/aquatic

ErC50 (Pseudokirchneriella subcapitata (microalgae)): 9 mg/l

plants

Exposure time: 72 h

Toxicity to daphnia and other : EC50: 3,7 mg/l aquatic invertebrates (Chron-

Exposure time: 48 d

ic toxicity)

Species: Daphnia magna (Water flea)

bis-[4-(2,3-epoxipropoxi)phenyl]propane:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1,8 mg/l

Exposure time: 48 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or

Date of last issue: 12.01.2019

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

very persisten



very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized

wherever possible.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe

way.

Dispose of surplus and non-recyclable products via a licensed

waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

European Waste Catalogue : 08 04 09* waste adhesives and sealants containing organic

solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated

by dangerous substances

SECTION 14: Transport information

14.1 UN number

 ADR
 : UN 1760

 IMDG
 : UN 1760

 IATA
 : UN 1760

14.2 UN proper shipping name

ADR : CORROSIVE LIQUID, N.O.S.

(Trimethylolpropane triglycidylether)

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019

CORROSIVE LIQUID, N.O.S.

(Trimethylolpropane triglycidylether)

IATA : Corrosive liquid, n.o.s.

(Trimethylolpropane triglycidylether)

14.3 Transport hazard class(es)

 ADR
 : 8

 IMDG
 : 8

 IATA
 : 8

14.4 Packing group

ADR

IMDG

Packing group : III
Classification Code : C9
Hazard Identification Number : 80
Labels : 8
Tunnel restriction code : (E)

IMDG

Packing group : III Labels : 8 EmS Code : F-A, S-B

Remarks : Alkalis

IATA (Cargo)

Packing instruction (cargo : 856

aircraft)

Packing instruction (LQ) : Y841
Packing group : III

Labels : Corrosive

IATA (Passenger)

Packing instruction (passen: 852

ger aircraft)

Packing instruction (LQ) : Y841
Packing group : III

Labels : Corrosive

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

Country GR 000000120780


11 / 14

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019



14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

None of the components are listed

Number on list 3

Not applicable

(=> 0.1 %).

Not applicable

Not applicable

Not applicable

Not applicable

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

REACH - List of substances subject to authorisation

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import of dangerous chemicals

REACH Information:

All substances contained in our Products are

- registered by our upstream suppliers, and/or

- registered by us, and/or

- excluded from the regulation, and/or

- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Law on the incentive tax for volatile organic compounds

(VOCV)

Volatile organic compounds (VOC) content: 0,19 %

no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0,19 %

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Country GR 000000120780

12 / 14

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A

Revision Date: 21.02.2021 Version 3.0 Print Date 21.02.2021

Date of last issue: 12.01.2019



SECTION 16: Other information

Full text of H-Statements

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.

H341 : Suspected of causing genetic defects.

H360F : May damage fertility.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Skin Sens.

Aguatic Chronic : Long-term (chronic) aguatic hazard

Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Muta. : Germ cell mutagenicity
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation

ADR : European Agreement concerning the International Carriage of

Skin sensitisation

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

Further information

Classification of the mixture: Classification procedure:

according to Regulation (EC) No. 1907/2006

Sikadur® Blade Repair-30 Part A



Revision Date: 21.02.2021 Date of last issue: 12.01.2019 Version 3.0

Print Date 21.02.2021

Skin Corr. 1C	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Muta. 2	H341	Calculation method
Repr. 1B	H360F	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

GR / EN