



Sikalastic® M 640

1- COMPONENT COST EFFECTIVE LIQUID APPLIED POLYURETHANE ROOF WATERPROOFING MEMBRANE

UNIQUE SELLING POINTS

- Single component, polyurethane base
- Excellent crack bridging ability
- High elasticity and flexibility, even at - 20°C
- Max shock temperature at +200°C
- Excellent thermal resistance. Max service temperature at +90°C

APPLICATION FIELDS:

Roof waterproofing for new construction and refurbishment projects, such as:

- Roofs, balconies and terraces
- Structures with numerous details (eg. penetrations, drains, roof lights and complex geometry)
- Existing substrates of concrete, bituminous membranes, asbestos cement, metal, wood, unglazed ceramic tiles

TECHNICAL CHARACTERISTICS:

- Elastomeric, aromatic polyurethane
- Packaging: In metal containers of 1kg, 6kg and 25kg
- Colors: White, Grey and Terracota
- Consumption : 1,5 - 2,0 kg/m² in 1 or 2 coats

Our most current General Sales Conditions shall apply.
Please consult the most current local Product Data Sheet prior to any use.

SIKA HELLAS ABEE
15 Protomagias str.
GR 145 68, Kryoneri,
Attica, Greece

Contact
Tel. + 30 210 81 60 600
E-mail: export@gr.sika.com
www.sika.gr

BUILDING TRUST

