

# Sikacrete<sup>®</sup>-213 F

## DECLARATION OF PERFORMANCE No. 87496006

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	87496006
2	<b>INTENDED USE/S</b>	EN 998-1:2016 Factory made lightweight rendering and plastering mortar (LW) intended for interior and exterior use in walls, ceilings, columns and partitions
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 4
6a	<b>HARMONISED STANDARD:</b>	EN 998-1:2016
	Notified body/ies:	No Notified Body required

### Declaration of Performance

Sikacrete<sup>®</sup>-213 F  
87496006  
2020.07.10, ver. 1  
1200

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to Fire	Euroclass A1	System 4	EN 998-1:2016
Water Absorption	W <sub>c</sub> 0	System 4	
Water Vapor Permeability	$\mu \leq 6$	System 4	
Adhesion	$\geq 0,15$ MPa – FP:A (Substrate: concrete)	System 4	
Thermal Conductivity	( $\lambda_{10,dry,mat}$ ) 0.12W/m·K (tab. Mean value, P = 50 %)	System 4	
Durability	NPD	System 4	
Dangerous Substances	NPD	System 4	

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos  
Function: TMM Refurbishment  
At Athens on 13 July 2020

Name: Alexandros Melissourgos  
Function: Technical Manager  
At Athens on 13 July 2020

.....

.....

End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sikacrete®-213 F  
87496006  
2020.07 , ver. 1  
1200





19

Sika Services AG, Zurich, Switzerland

87496006

EN 998-1:2016

Factory made lightweight rendering and plastering mortar (LW) intended for interior and exterior use in walls, ceilings, columns and partitions

Reaction to Fire	Euroclass A1
Water Absorption	$W_c 0$
Water Vapor Permeability	$\mu \leq 6$
Adhesion	$\geq 0,15$ MPa – FP: A (Substrate: concrete)
Thermal Conductivity	$(\lambda_{10, dry, mat}) 0.12$ W/m·K (tab. Mean value, P = 50 %)

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Sikacrete®-213 F  
87496006  
2020.07, ver. 1  
1200

3/4

**BUILDING TRUST**





Sika Hellas ABEE  
Protomagias 15  
14568 Kryoneri  
Attica - Greece  
[www.sika.gr](http://www.sika.gr)

**Declaration of Performance**

Sikacrete®-213 F  
87496006  
2020.07 , ver. 1  
1200