

# Sika® Intraplast EP

## DECLARATION OF PERFORMANCE

### No. 86941776

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	86941776
2	<b>INTENDED USE/S</b>	EN 934-4:2009 Injection aid admixture
3	<b>MANUFACTURER:</b>	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	System 2+
6a	<b>HARMONISED STANDARD:</b>	EN 934-4:2009
	Notified body/ies:	1020

#### Declaration of Performance

Sika® Intraplast EP  
86941776  
2021.09.25 , ver. 1  
1180

**7 DECLARED PERFORMANCE/S**

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Fluidity 30 minutes after mixing	≤25 s	System 2+	EN 934-4:2009
Compressive strength	≥ 30 after 28 days	System 2+	
Water separation	≤ 2% after 3 hrs	System 2+	
Volume change after 24 hours	0% ≤ S ≤ 5%	System 2+	



**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Nikos Anagnostopoulos  
Function: TMM Refurbishment  
At Athens on 25 September 2021

Name: Angeliki Zacharopoulou  
Function: QEHS Manager  
At Athens on 25 September 2021



End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sika® Intraplast EP  
6941776  
2021.09.25 , ver. 1  
1180





12

Sika Services AG, Zurich, Switzerland

86941776

EN 934-4:2009

Notified Body 1020

Injection aid admixture

Fluidity 30 minutes after mixing	≤25 s
Compressive strength	≥ 30 MPa after 28 days
Water separation	≤ 2% after 3 hrs
Volume change after 24 hours	0% ≤ S ≤ 5%

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Declaration of Performance

Sika® Intraplast EP  
6941776  
2021.09.25 , ver. 1  
1180



**Sika Hellas ABEE**  
Protomagias 15  
14568 Kryoneri  
Attica - Greece  
[www.sika.gr](http://www.sika.gr)

**Declaration of Performance**  
Sika® Intraplast EP  
6941776  
2021.09.25 , ver. 1  
1180